New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

## IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		COMP (*=N/A or A/E=ex	MEDIATE -USE -LIANCE -full in-use; th. / evap	FUEL TYPE	
2013	DTYXT03.5BER	LDT: <6000# GVW, 3751- 5750# LVW	"LEV I!" Ultra Low Emission Vehicle (LEV II	EXH / ORVR	EVAP	EXH	EVAP	Gasoline	
			ULEV)	120K	150K			Odsonie	
No.	ECS & S	SPECIAL FEATURES	EVAPORATIVE I	100	DISPLACE	MENT (L)			
1	2TWC, TWC, 2	2AFS,2HO2S, SFI, OBD(P)	DTYXR0						
*		*	DTYXR0165P22				3.	5	
*		*	*						

<sup>\*</sup>See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968,2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

# **BE IT FURTHER RESOLVED:**

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-014-0770 dated December 23, 2011.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division

day of April 2012.

#### TOYOTA MOTOR CORPORATION

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

# **ATTACHMENT**

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET N AVERAGE [g/mi]		NMOG CH4 F	NMOG @ RAF=* CH4 RAF = *		HCHO=fo	hane; <b>NMOG:</b> rmaldehyde; l RL [g/mi]=rur	PM=particu	late matter;	RAF=reac	tivity adj	ustment fact	or; 2/3 D [g/t	est]=2/3 day	diumai+	A
CERT	STD	NMOG NMHC		NMHC	mi=mile;	KE [g/m]=rur K=1000 miles	F=degree	s Fahrenhei	it; SFTP=s	uppleme	ntal federal	test procedu	re		
0.039	0.043	CERT [g/mi]	CERT [g/mi]	[g/mi]	CO	[g/mi]		x [g/mi]		CHO [n		PM [g/mi]		Hwy NOx [g/mi]	
	0.043				CERT	STD	CERT	STD	CE	RT	STD	CERT	STD	CERT	STD
	@ 50K	0.022	*	0.040	0.3	1.7	0.01	0.05	. *		8.	*		0.01	0.07
	@UL	0.023	*	0.055	0.3	2.1	0.02	0.07			11.	*	0.01	0.02	0.09
	@ 50°F & 4K	*	*	*	*	*	*	*	1				*	*	*
CO [g/mi] @ 20°F & 50K		Marie Company of the		NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
				CERT	STD	CERT	STD	CERT	STD	CER	TSTD	CERT	STD	CERT	STD
CERT	0.6	SFTP@4	000 miles	*	*	*	*	0.04	0.25	1.7	10.5	0.01	0.27	0.05	3.5
STD	12.5	SFTP@* miles *		*	*	*	*	*	*	*		*	*	*	*
		urnal + Hot ns/test) @ U				mal + Hot Soak /test) @ UL		Running Loss (grams/mile) @ UL		On-Board Refueling Recovery (grams/gallo					
			CERT	ST	TD D	CERT	5	STD Y	CER	T	STD		CERT		STD
DTYXR0165A22 0		0.24	0.	65	0.25		0.85	0.00	5	0.05		0.04		0.20	
DTYXR0165P22		0.23	0.0	65	0.25	0	0.85	0.00	4	0.05		0.02		0.20	
*		*	1		*		*			*		*		*	
*		*	,		*		*	*		*		*		w	

\*= not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U/SCR-N= selective catalytic reduction-urea/ammonia; NH3OC=SCR-U/SCR-N ammonia slip catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; HO2S/O2S=heated/oxygen sensor; AFS/HAFS=air- fuel ratio sensor / heated AFS; NOXS=NOx sensor; RDQS=reductant quality sensor; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; SFI/MFI= sequentia/ multiport fuel injection; DFI=direct fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)(P)(B)=full/partial/both on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol (\*15%"gasoline) Fuel;

# 2013 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	Model	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	INTERMEDIATE IN-USE COMPLIANCE (*=N/A or full in-use; A/E=exh. / evap. intermediate in-use)		PHASE-IN STD.	OBD II
					EXH	EVAP		
LEXUS	RX 350	DTYXR0165P22	1	3.5	*	*	SFTP	Partial
LEXUS	RX 350 AWD	DTYXR0165P22	1	3.5	*	*	SFTP	Partial
TOYOTA	Venza	DTYXR0165A22	1	3.5	w	w	SFTP	Partial
TOYOTA	Venza AWD	DTYXR0165A22	1	3.5	*	*	SFTP	Partial