| California Environmental Protection Agency | | EXECUTIVE ORDER A-003-0524 | | | | |
|--|------------|--|--|--|--|--|
| OB Air Resources Board | DAIMLER AG | New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 3 | | | | |

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| YEAR | | | EXHAUST EMISSION STANDARD CATEGORY USEFUL LIFE (mi | | | FUEL TYPE | |
|------|--------------|---|---|---------------|------------------|-----------|--|
| 2015 | FMBXT03.0HD1 | MDV: 8501-10000# GVW | "LEV II" Ultra Low Emission | EXH / ORVR | EVAP | Diesel | |
| 2015 | | | Vehicle (LEV II ULEV) | * | Diesei | | |
| No. | ECS & | SPECIAL FEATURES | EVAPORATIVE FAI | | DISPLACEMENT (L) | | |
| 1 | | HO2S, NOXS(2), DFI, EGR, EGRC, , CAC, OBD(P) | * | 2.3 | | | |
| * | | * | * | di sa a | 3 | | |
| * | | * | * | | | | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50[°] Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV, amended December 6, 2012).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT, and MDV, amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a largevolume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volumemanufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models has been determined to have seven deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$175 per vehicle for the third through seventh deficiencies for vehicles in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30)

| California Environmental Protection Agency | | E |
|--|------------|-----|
| OB Air Resources Board | DAIMLER AG | New |

days after the end of each calendar quarter during the 2015 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _ day of July 2014.

mona nette Hebert, Chief

missions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

OB Air Resources Board

MERCEDES-BENZ

DAIMLER AG

EXECUTIVE ORDER A-003-0524

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

*

Partial

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| NMOG+NOx FLEET NMOG AVERAGE [g/mi] CH4 | | NMOG (CH4 F | @ RAF=* RAF = * | NMOG or | CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitroger HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diurnal+ hot-soak; RL [g/m]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram: mg=milligram | | | | | | | | | | | |
|---|---|--|--|---|--|--|---|--|--|---|--|---|---|--|---|--|
| CERT | STD | NMOG | NMHC | NMHC | | | | | R [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram hrenheit; SFTP=supplemental federal test procedure | | | | | | | |
| * | | CERT | CERT | STD [g/ml] | CO [g/mi] | | | NOx [q/mi] | | HCHO [mg/mi] | | PM [g/mi] | | Hwy NOx [g/m] | | |
| | | [g/mi] | [g/mi] | | CERT | STD | CERT | STD | CER | | TD | CERT | STD | CERT | STE | |
| | @ 50K | | * | * | * | * | * | + | | | * | * | * | * | * | |
| 13 | @ UL | * | 0.004 | 0.143 | 0.1 | 6.4 | 0.1 | 0.2 | 0.1 | | 6. | 0.01 | 0.06 | 0.02 | 0.4 | |
| @ | 50°F & 4K | * | * | * | * | * | * | * | * | | • | * | * | * | * | |
| CO [g/m]] @ 20°F & 50K | | Ye por series | en la | NMHC+NC | | | | NMHC+NOx | | CO [g/mi] | | NMHC+NOx | | CO [g/mi] | | |
| | | | | (composite) | | (composite) | | [g/mi] [l | JS06] | | | [g/mi] [SC03] | | [SC03] | | |
| @ 20-7 0 | a DUK | | | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | STD | CERT | ST | |
| ERT | * | SFTP | @* miles | * | * | * | * | * | * | * | * | * | · * | | * | |
| STD | * | SFTP | @* miles | * | * | * | * | * | * | * | * | * | * | * | * | |
| Evap | oorative Fam | illy | | Diurnal + Hot Soak ms/test) @ UL | | 2-Days Diurnal + Hot S (grams/test) @ UL | | | Running Loss (grams/mile) @ UL | | | On-Board Refueling Vapor Recovery (grams/gallon) @ UL | | | | |
| | | | CERT ST | | D | CERT | S | STD | | CERT S | | | CERT | | STD | |
| | * | | | | | * | | * | * | | * | | | | | |
| | * | | * | | | * | | * | * | | * | | * | | * | |
| | * | | * | | * | | | * | * | | * | | | | | |
| | | | • | , | | * | | * | * | | * | | * | | * | |
| 10000#GV ALVW=ad | T 6001-8500 /WR; MDV5 justed LVW; -up catalyst catalyst; CTC | HEV=low | 01-14000#0 emission ve | SVWR; EC | S= emiss | ion control | system; S | TD= stan | dard; CE | RT= cer | tification | ; LVW=loa | ded vehic | | | |
| FS=Wide ensor; EC equential liagnostic; | e range/linea GR=exhaust / multiport fu ; DOR=dire ed/liquefied | gas recirc rel injection ct ozone re | continuous ir-fuel ratio ulation; EGI n; DFI=direc educing; HC s; LPG=liqu | n catalyst; \$ /periodic tra sensor; NG RC=EGR ca t fuel inject T=Hydroca efied petro | CR-U or ap oxidize XS= NO coler; AIR ion; TC/S rbon Trap eum gas | SCRC/SC er; DPF = D x sensor; F VAIRE=sec SC= turbo/s b; BCAN=b ; E85="859 | R-N or SO liesel Part DQS=red condary air super char leed carbo %" Ethano | CRC-NH3 iculate Fil luctant qu r injection ger; CAC on caniste I ("15%"g | = selecti lter (activ ality sen (belt driv =charge er; prefix asoline) | ve cataly sor; HO2S sor; NH3 ven)/(ele air coole 2=paralie Fuel; | tic redu S/O2S=I S = Ami ctric driv r; OBD | ction-urea/a neated/oxyg monia sens ven); PAIR= (F)/(P)(B)= iffix=series | ammonia gen sense or; PMS pulsed A full/partia | sorbing TV ; NH3OC= or; WR-HO =particulate NR; SFI/MI al/both on-t | ammon 2S or e matte FI= | |
| AFS=Wide ensor; EC equential liagnostic; compresse | GR=exhaust / multiport fu ; DOR=dire | gas recirc rel injection ct ozone re | continuous ir-fuel ratio ulation; EGI n; DFI=direc educing; HC s; LPG=liqu | h catalyst; \$ /periodic trassensor; NG RC=EGR ci t fuel inject T=Hydroca efied petro 15 MOD | CR-U or ap oxidize XS= NO coler; AIR ion; TC/S rbon Trap eum gas | SCRC/SC or; DPF = D x sensor; F VAIRE=sec SC= turbo/s ; BCAN=b ; | R-N or SO liesel Part DQS=red condary air super char leed carbo %" Ethano | CRC-NH3 iculate Fil luctant qu r injection ger; CAC on caniste I ("15%"g | e selecti lter (activ vality sen (belt driv =charge er; prefix asoline) ELS IN | ve cataly re); HO23 sor; NH3 ven)/(ele air coole 2=paralie Fuel; FORM | tic reduction S/O2S=I S = Amictric driv ctric driv r; OBD el; (2) st ATIOI | ction-urea/a neated/oxyg monia sens ven); PAIR= (F)/(P)(B)= iffix=series | ammonia gen senso or; PMS= pulsed A full/partia ; CNG/L | sorbing TV ; NH3OC= or; WR-HO =particulate NR; SFI/MI al/both on-t | ammon 2S or e matte FI= board | |
| AFS=Wide ensor; EC equential diagnostic; compresse | GR=exhaust / multiport fu ; DOR=dire ed/liquefied | gas recirc rel injection ct ozone re | continuous ir-fuel ratio ulation; EGI s; DFI=direc educing; HC s; LPG=liqu 20 | h catalyst; \$ /periodic trr sensor; NC RC=EGR cd T=Hydroca efied petro 15 MOD | CR-U or ap oxidize XS= NO coler; AIR ion; TC/S rbon Trap eum gas | SCRC/SC pr; DPF = D x sensor; F VAIRE=sec SC= turbo/s ; BCAN=b ; E85="859 AR: VE EVAPO FAI | R-N or SO iesel Part RDQS=rec condary ai uper char leed carbo %" Ethano | CRC-NH3 iculate Fil luctant qu r injection ger; CAC ger; CAC ger; CAC ger; CAC ger; CAC second to caniste t (*15%*g MODE | e selecti lter (activ vality sen (belt driv =charge er; prefix asoline) ELS IN | ve cataly re); HO2: sor; NH3 ven)/(ele air coole 2=paralik Fuel; FORM (GINE SIZE (L) | tic redu \$/02S=1 S = Am ctric driv r; OBD el; (2) su ATIOI VEH T | ction-urea/a neated/oxyg monia sens ven); PAIR= (F)((P)(B)= (ffix=series N N IICLE (PE | ammonia gen senso or; PMS= pulsed A full/partia ; CNG/L SPE FEAT | sorbing TV ; NH3OC= or; WR-HO =particulate NR; SFI/MI al/both on-b NG= | ammon 22 or e matter FI= board OBD | |
| MASSEWIDE ensor; EC equential iagnostic; ompresse MA | GR=exhaust / multiport fu ; DOR=dire ed/liquefied KKE | gas recirc rel injection ct ozone re | continuous ir-fuel ratio ulation; EGI r; DFI=direc educing; HC s; LPG=liqu 20 MOD Freightlin | r catalyst; \$ /periodic trr sensor; NG C=EGR c t fuel inject T=Hydroca efied petro 15 MOD DEL er 2500 | CR-U or ap oxidize XS= NO coler; AIR ion; TC/S rbon Trap eum gas | SCRC/SC r; DPF = D x sensor; F XAIRE=sec SC= turbo/s b; BCAN=b ; E85="859 AR: VE EVAPO FAI | R-N or SC iesel Part 2DQS=red condary ai upper char leed carbo %" Ethano HICLE RATIVE MILY | CRC-NH3 iculate Fil luctant qu r injection ger; CAC on caniste l ("15% g MODE EC: NO | e selecti lter (activ vality sen (belt driv =charge er; prefix asoline) ELS IN | ve cataly e); HO2: sor; NH3 ven)/(ele air coole 2=paralk Fuel; FORM KGINE SIZE (L) 3 | tic redu S/O2S=I S = Am ctric driv r; OBD sI; (2) su ATIOI VEH T | ction-urea/a neated/oxyg monia sens ren); PAIR= (F)/(P)(B)= iffix=series N IICLE (PE DV4 | ammonia jen sens or; PMS= pulsed A full/partia ; CNG/L SPE FEAT | sorbing TV ; NH3OC= or; WR-HO =particulate NR; SFI/MI al/both on-b NG= CIAL URES | ammon 2S or e matte FI= board OBD Parti | |
| AFS=Wide ensor; EC equential. liagnostic; compresse MA FREIGH | GR=exhaust / multiport fu ; DOR=dire ed/liquefied | gas recirc rel injection ct ozone re | continuous ir-fuel ratio ulation; EGI s; DFI=direc educing; HC s; LPG=liqu 20 | r catalyst; \$ /periodic trr sensor; NG C=EGR c t fuel inject T=Hydroca efied petro 15 MOD DEL er 2500 | CR-U or ap oxidize XS= NO coler; AIR ion; TC/S rbon Trap eum gas | SCRC/SC r; DPF = D x sensor; P K2AIRE=sec SC= turbo/s BCAN=b ; BCAN=b ; BCAN= | R-N or SC iesel Part DQS=red condary ai uper char leed carbo %" Ethano HICLE | CRC-NH3 iculate Fil luctant qu r injection ger; CAC ger; CAC ger; CAC ger; CAC ger; CAC second to caniste t (*15%*g MODE | e selecti lter (activ vality sen (belt driv =charge er; prefix asoline) ELS IN | ve cataly re); HO2: sor; NH3 ven)/(ele air coole 2=paralik Fuel; FORM (GINE SIZE (L) | tic redu S/O2S=I S = Am ctric driv r; OBD sI; (2) su ATIOI VEH T | ction-urea/a neated/oxyg monia sens ven); PAIR= (F)((P)(B)= (ffix=series N N IICLE (PE | ammonia jen sens or; PMS= pulsed A full/partia ; CNG/L SPE FEAT | sorbing TV ; NH3OC= br; WR-HQ NR; SFI/MI al/both on-t NG= CIAL URES | ammon 2S or e matte FI= board OBD | |

*

Sprinter 3500 CDI

3

MDV4

1