### **GENERAL MOTORS LLC**

**EXECUTIVE ORDER A-006-1948** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 3

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-02-003:

## IT IS ORDERED AND RESOLVED:

The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| granted.   |                                    |                        |                     |                |                                   |                             |  |  |  |  |
|--|------------------------------------|------------------------|---------------------|----------------|-----------------------------------|-----------------------------|--|--|--|--|
|  |                                    |                        | TEST                | GROUP INFORM   | ATION                             | 50 A -                      |  |  |  |  |
| MODEL<br>YEAR  | TEST GRO                           | OUP VEHIC              | CLE CLASS(ES)       | FUE            | L CATEGORY                        |                             | FUEL TYPE  |  |  |  |
| 2015   | FGMXD06.                           | 0399                   | MDV5                | Flex           | r-Fuel Vehicle                    |                             | Gasoline, 85% Ethanol  |  |  |  |
| . 116-18 - 2-14-14-14-14-14-14-14-14-14-14-14-14-14-   | USEFUL LI                          |                        | 4 1                 | MISSION CATE   | 29-14 Th.                         |                             |  | DIATE IN-USE STD   |  |  |
| EXH/0  | DRVR                               | EVAP                   | FTP                 |                | SFTP                              |                             | FTP  | SFTP   |  |  |
| 150  |                                    | 150,000                | LEV3 LEV630         |                | *                                 |                             | *  | *  |  |  |
| SPECIAL  |                                    | EXHAUST EMISSION       | CONTROL SYSTEMS     |                | OBD STATUS                        | A SECONDARY CONTRACTOR      | and the second s | IE DISPLACEMENT (L)  |  |  |
| 1  | 2                                  | TWC, TWC, 2HO2S(2)     | , SFI               | FULL           | ALL MOD                           | ELS                         |  |  |  |  |
| *  |                                    | *                      |                     | PARTIAL        | -                                 |                             |  | 6.0  |  |  |
| *  |                                    | *                      |                     | PARTIAL WITH   | 1                                 |                             |  |  |  |  |
| to the surface of the | Company Company                    |                        | VAPORATIVE & REFUEL |                |                                   |                             |  |  |  |  |
|  | EVAP / O                           | RVR FAMILY             | EVAPOR              | RATIVE STD CAT | EGORY                             | EVA                         | AP EMISSION ST   | TO VEHICLE CLASS   |  |  |
|  | FGMX                               | R0223842               |                     | LEV 2          |                                   |                             | MD   | V5   |  |  |
|  |                                    | *                      |                     |                |                                   |                             | 1  | t .  |  |  |
|  |                                    | *                      |                     | •              |                                   |                             | 1  | k  |  |  |
| San transfer and region of the state of  | 25.27 (Sept. 18) 18) 18(18) 18(18) |                        | EMISSIO             | N CREDIT INFOR |                                   |                             | A STATE OF THE PROPERTY OF THE | A CONTROL SECTION OF THE CONTROL OF  |  |  |
| BASEL  | NE PZEV                            | ALLOWANCE FOR TEST     | GROUP               |                | G CREDIT FOR<br>ZEV ZERO-EVAP     | NMOG CR                     | EDIT FOR DOR   | OPTIONAL EXH. STD FOR<br>WORK TRUCKS   |  |  |
|  | *                                  | *                      | *                   | 7              | N                                 |                             | N  | N  |  |  |
| install with Paul  | er verten kalender breden.         |                        | NMOG AND FL         | EET AVERAGE I  |                                   | State of Control of Control |  | The state of the s |  |  |
| NMOG RAF   | CH4 RAF                            | FTP NMOG/NMHC<br>RATIO | HCHO/NMHC RATIO     |                | G+NOX FLEET<br>OT (0-3750 LVW) (g |                             |  | EET STD LDT (3751 LVW-<br>VR) + MDPV (g/mi)  |  |  |
| *  | *                                  | 1.10                   | -                   |                | *                                 |                             |  | *  |  |  |
|  |                                    |                        |                     |                |                                   |                             |  |  |  |  |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOX, as applicable, Fleet Average" (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

# BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

## BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles,

**EXECUTIVE ORDER A-006-1948** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 3

amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

### BE IT FURTHER RESOLVED:

Vehicles certified under this Executive Order shall not be introduced into commerce before January 2, 2014.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of December 2013.

Erlk White, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

# **ATTACHMENT**

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

| EXHAUST EMISSION | STANDARDS AND | CERTIFICATION LEVELS | (FTP | , HWFET | , 50 °F | , 20 ° | F) |
|------------------|---------------|----------------------|------|---------|---------|--------|----|
|                  |               |                      |      |         |         |        |    |

|            | FUEL TYPE         | HCHO=formale<br>HC/mi]=runnin<br>Fahrenheit; F1 | H4=methane; NMOG=non-CH4 organic gas; HC=hydrocarbon; NMHC=non-CH4 HC; CO=carbon monoxide; NOx=oxides of nitrogen; CHO=formaldehyde; PM=particulate matter, RAF=reactivity adjustment factor; 2DHS/3DHS [g HC/test]=2/3 days diumal+hot-soak; RL [g C/mi]=running loss; ORVR [g HC/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram; mf=mile; K=1000 miles; F=degrees ahrenheit; FTP=federal test procedure; SFTP=supplemental FTP  NMOG+NOx (g/mi) CO (g/mi) HCHO (mg/mi) PM (g/mi) HWY NMOG+NOx (g/mi) |      |     |      |     |      |      |       |       |  |  |
|------------|-------------------|---|---|------|-----|------|-----|------|------|-------|-------|--|--|
| it will be |                   | CERT  | STD   | CERT | STD | CERT | STD | CERT | STD  | CERT  | STD   |  |  |
| FTP @ UL   | E85-EPA           | 0.126   | 0.630   | 0.8  | 7.3 | 2    | 6   | *    | 0.12 | 0.076 | 0.630 |  |  |
| FTP @ UL   | GASOLINE-LEV3 E10 | 0.147   | 0.630   | 1.5  | 7.3 | *    | 6   | Ŕ    | 0.12 | 0.065 | 0.630 |  |  |
| 20°F @ 50K |                   | *   | ŵ   |      | *   | *    | *   | *    | tr   | w     | *     |  |  |
| 50°F @ 4K  | E85-EPA           | 0.418   | 1.260   | 1.6  | 7.3 | 6    | 80  | •    | ŵ    | W     | *     |  |  |
| 50°F @ 4K  | GASOLINE-LEV3 E10 | 0.214   | 1.260   | 2.0  | 7.3 | w    | 80  | *    | *    | w     | *     |  |  |

### SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

|      |           | US06 / UC (LA92) |              |      |       |       |        | \$C03        |     |      |       | COMPOSITE |         |       |       |       |
|------|-----------|------------------|--------------|------|-------|-------|--------|--------------|-----|------|-------|-----------|---------|-------|-------|-------|
|      | FUEL TYPE |                  | G+NOx<br>mi) | CO ( | g/mi) | PM (m | ng/mi) | NMOG<br>(g/r |     | CO   | g/mi) | NMO       | G+NOx ( | g/mi) | CO (9 | g/mi) |
|      |           | CERT             | STD          | CERT | STD   | CERT  | STD    | CERT         | STD | CERT | STD   | CERT      | STD     | BIN   | CERT  | STD   |
| @ UL | *         | *                | *            | *    | w     | *     | *      | *            | *   | *    | *     | n         | *       | *     | *     | *     |

## WHOLE VEHICLE EVAPORATIVE/ORVR EMISSION STANDARDS AND CERTIFICATION LEVELS

| EVAPORATIVE  |                            | WHOLE VEHICLE EVAPORATIVE TESTING          |      |     |  |      |     | RUNNIN      | GLOSS | ON-BOARD REFUELING                |      |  |
|--------------|----------------------------|--|------|-----|--|------|-----|-------------|-------|-----------------------------------|------|--|
| FAMILY       | FUEL TYPE                  | 3-DAYS DIURNAL + HOT<br>SOAK (g/test) @ UL |      |     | 2-DAYS DIURNAL + HOT<br>SOAK (g/test) @ UL |      |     | (g/mi) @ UL |       | VAPOR RECOVERY<br>(g/gallon) @ UL |      |  |
|              |                            | CERT                                       | STD  | FEL | CERT                                       | STD  | FEL | CERT        | STD   | CERT                              | STD  |  |
| FGMXR0223842 | E10-EPA                    | 0.65                                       | 1.00 | 1   | 0.45                                       | 1.25 | *   | 0.000       | 0.05  | * *                               | *    |  |
| FGMXR0223842 | GASOLINE-TIER2<br>UNLEADED | *  | A    |     |  | *    | ŵ   | *           | *     | 0.03                              | 0.20 |  |
| *            | *                          | *  | W    | -   | *  | W    | *   | *           | rk    | *                                 | *    |  |

### FUEL ONLY & CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

| EVAPORATIVE FAMILY |           |      | FUEL ONLY EVAP          |                          |                         |                         |     |
|--------------------|-----------|------|-------------------------|--------------------------|-------------------------|-------------------------|-----|
|                    | FUEL TYPE |      | AL + HOT SOAK<br>) @ UL | 2-DAYS DIURN/<br>(g/test | AL + HOT SOAK<br>) @ UL | CANISTER BLEED (g/test) |     |
|                    |           | CERT | STD                     | CERT                     | STD                     | CERT                    | STD |
| *                  | *         |      | *                       | *                        | #                       | *                       | *   |
| *                  | *         |      | *                       | *                        | *                       | *                       | *   |

\*=not applicable; #=pounds; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT<6000#GVWR,0-3750#LVW; LDT2=LDT<6000#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4=LDT 6001-8500#GVWR,5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-10000#GVWR; MDV5=MDV 10001-14000#GVWR; MDPV=medium-duty passenger vehicle; ECS=emission control system; CERT=certification; STD=standard; FEL=family emission limit; GVWR=gross vehicle weight rating; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; ZEV=zero-emission vehicle; PZEV=partial ZEV; AT PZEV=advanced technology PZEV; TZEV=transitional ZEV; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; HAC=HC adsorbing catalyst; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3=selective catalytic reduction-urea/ammonia; NH3OC=ammonia oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DFF=diesel particulate filter (active); GFF=PM filter for spark-ignited engine; HO2S/O2S=heated/oxygen sensor; WR-HO2S or AFS=wide range/linear/heated air-fuel ratio sensor; NOXS=NOx sensor; PMS=PM sensor; RDQS=reductant quality sensor; NH3S=ammonia sensor; EGR=exhaust gas recirculation; DFI/IFI=direct/indirect fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; F/P/\$=full/partial/partial with fines on-board diagnostic; DOR=direct ozone reducing; HCT=hydrocarbon trap; BCAN=bleed carbon canister; prefix 2=parallel; (2) suffix=series; CNG/LNG=compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85-CARB: 85% ethanol+15% CA Phase2 gasoline; E85-EPA: 85% ethanol+15% Tier2 unleaded gasoline; E10-CARB: 10% ethanol+90% CA Phase2 gaso

#### 2015 MODEL YEAR: VEHICLE MODELS INFORMATION

| 2010 MODEL TEAK. VEHICLE MODELO IN OKMATION |                   |              |               |               |                    |            |     |              |  |  |  |  |
|---|-------------------|--------------|---------------|---------------|--------------------|------------|-----|--------------|--|--|--|--|
| MAKE  | MODEL             | VEH<br>CLASS | ENGINE<br>(L) | TRANS<br>TYPE | EVAPORATIVE FAMILY | EXH<br>ECS | OBD | PZEV<br>TYPE |  |  |  |  |
| CHEVROLET                                   | C35 SILVERADO 2WD | MDV5         | 6.0           | Α             | FGMXR0223842       | . 1        | F   | *            |  |  |  |  |
| CHEVROLET                                   | K35 SILVERADO 4WD | MDV5         | 6.0           | Α             | FGMXR0223842       | 1          | F   | *            |  |  |  |  |
| GMC   | C35 SIERRA 2WD    | MDV5         | 6.0           | Α             | FGMXR0223842       | 1          | F   | *            |  |  |  |  |
| GMC   | K35 SIERRA 4WD    | MDV5         | 6.0           | Α             | FGMXR0223842       | 1          | F   | *            |  |  |  |  |