EXECUTIVE ORDER A-009-1254

OB Air Resources Board

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LI	FE (miles)	FUEL TYPE Dual Fuel: CNG/Gasoline		
2015	FCRXD05.75VY	MDV: 8501-10000# GVW	"LEV II" Ultra Low Emission	EXH / ORVR	EVAP			
2015			Vehicle (LEV II ULEV)	120K 150K		(Tier 2 Unleaded)		
No.		SPECIAL FEATURES	EVAPORATIVE FAM		DISPLACEMENT (L)			
1	2TWC, 2H	102S(2), SFI, OBD(F)	FCRXR0272		5.7			
*		*	***					
*		*	*	*				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50[°] Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV, amended December 6, 2012).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT, and MDV, amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a largevolume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volumemanufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of August 2014.

unen nnette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

O Air Resources Board

CHRYSLER GROUP LLC

EXECUTIVE ORDER A-009-1254

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	MOG+NOX FLEET NMOG @ F AVERAGE [g/mi] CH4 RAF			NMOG or												
CERT	STD	STD NMOG		14141110	hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure											
		CERT [g/mi]	T CERT	STD [g/mi]	CO [a/mi]		NOx [g/mi]				O [mg/mi]	PM Ic		Hwy NO	NOx [g/ml]	
*	•				CERT		CERT	STE			TD	CERT	STD	CERT	STE	
A State State State	@ 50K	*	*	*	*	*	*	*			*	*	*	*	*	
and the second	QUI	0.007		0.143	0.3	6.4	0.04	0.2	0.	7	16.	*	0.06	0.13	0.4	
THE TEN	@ UL	(0.089)		(0.167)	(0.8)	(6.4)	(0.1)	(0.2) (*) (16.)	(*)	(0.06)	(0.03)	(0.4	
@	50°F & 4K	*	+	* *	+	*	*	*	1		*	*	*	*	*	
CO [g/mi] @ 20°F & 50K				NMHC+NC (compo	0x [g/mi] osite)	CO [g. (compo		NMHC [g/mi]		CO	[g/mi] 506]		IC+NOx] [SC03]	CO	[g/mi] C03]	
				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	ST	
ERT	*	SFTP	@ * miles	*	*	*	*	*	*	*	*	*	*	*	*	
TD	*	SFTP	@* miles	*	*	*	*	*	*	*	*	*	*	*		
Evaporative Family			(gram	urnal + Hot is/test) @ U	L	10	/test) @	UL	(gra	tunning L ams/mile)	@ UL		ecovery (g	Refueling rams/gallo	n) @ UL	
			CERT	ST	D	CERT	S	TD	CER	T	STD		CERT		STD	
FCRXR0272TCY		CY	0.45 (0.40	-		0.46 (0.33)	1.25	(1.25)	0.00 (0	.00) 0	.05 (0.0	5)	* (0.04)	*	(0.20)	
*			*	* *		*	*	*	*		*		*		+	
		*	* *		* *		•	*		*		*		*		
				1										1		
					DT=light-c	* duty truck; L										
DT3=LD1 0000#GV LVW=adj VU=warm xidation c \FS=Wide ensor; EG equential/ iagnostic;	T 6001-8500 /WR; MDV justed LVW -up catalyst catalyst; CT e range/line SR=exhaust / multiport fi ; DOR=dire	#GVWR,3 =MDV 100 ; LEV=low ; NAC=NO OX/PTOX= ar/heated a t gas recirc uel injection ect ozone re	PC=passer 1751-5750#/ 101-14000#(emission ver- x adsorption continuous iir-fuel ratio ulation; EGI n; DFI=direce educing; HC	L ALVW; LDT GVWR; EC shicle; ULE n catalyst; S /periodic tra sensor; NC RC=EGR co t fuel inject T=Hydroca	DT=light- T4=LDT 6 S= emiss V=ultra L SCR-U or ap oxidize DXS= NO poler; AIR ion; TC/S rbon Trai	duty truck; L i001-8500#(ion control : EV; SULEV r SCRC/SCI er; DPF = D x sensor; R X/AIRE=sec SC= turbo/s bc: BCAN=b	SVWR,5 system; s system; s super L R-N or S lesel Par DQS =re ondary a uper cha eed carb	T<6000# 751-8500 STD= sta JLEV; TV CRC-NH ticulate F ductant q ir injectio rger; CA	GVWR,0 #ALVW; ndard; C VC/OC=3 3= selec ilter (acti uality sei n (belt dr C=charge ter: prefix	MDV=m ERT= cer -way/oxid tive cataly ve); HO2 hsor; NH3 iven)/(ele air coold 2=parall	edium-d tification dizing ca tic redu S/O2S= SS = Am ectric driv er: OBD	uty vehicle n; LVW=lo talyst; AD ction-urea heated/ox monia ser ven); PAIF (F)/(P)(B)	6000#GVW e; MDV4=I aded vehic STWC=ad /ammonia ygen sens sor; PMS: R=pulsed A =full/oartia	MDV 8501- cle weight; sorbing TV ; NH3OC= or; WR-HO =particulate AIR; SFI/MI al/both on-t	VC; ammon 2S or e matter	
DT3=LD1 0000#GV LVW=adj /U=warm xidation c FS=Wide ensor; EG equential/ iagnostic; ompresse	T 6001-8500 /WR; MDV 8 /Justed LVW -up catalyst :atalyst; CTr a range/line. GR=exhaust / multiport fi ; DOR=dire ed/liquefied	#GVWR,3 =MDV 100 ; LEV=low ; NAC=NO OX/PTOX= ar/heated a t gas recirc uel injection ect ozone re	PC=passer 1751-5750#/ 101-14000#/ emission ve tx adsorption c continuous adsorption c continuous in-fuel ratio ulation; EGI n; DFI=direc aducing; HC s; LPG=liqu 20	I ger car; LI ALVW; LDT SVWR; EC SVWR; EC chicle; ULE n catalyst; S /periodic tra sensor; NC RC=EGR c tf fuel inject T=Hydroca refied petrol 15 MOD	DT=light-or 4=LDT 6 S= emiss V=ultra L SCR-U or ap oxidize DXS= NO DOS= NO DOS N	duty truck; L 6001-8500#(ision control = EV; SULEV r SCRC/SCI er; DPF = D X sensor; R VAIRE=sec SC= turbo/s p; BCAN=bl ; E85="85% AR: VE	GVWR,5 system; system; sesel Par DQS=recondary a uper cha eed carb " Ethance HICLE	T≤6000# 751-8500 STD= sta JLEV; TV CRC-NH ticulate F ductant q ir injectio rger; CA. on canis ol ("15%"	GVWR,(#ALVW; ndard; C VC/OC=3 3= selec ilter (acti uality sen n (belt dr C=charge ter; prefix gasoline) ELS IN	MDV=m ERT= cel way/oxid tive cataly ve); HO2 hsor; NH3 iven)/(ele air coole c 2=parall Fuel;	edium-d tificatior dizing ca tric redu S/O2S= 2S = Am ectric driver; OBD el; (2) su IATIO	uty vehicle n; LVW=lo talyst; AD ction-urea heated/oxy monia ser ven); PAIF (F)/(P)(B) uffix=serie	sooo#GVV e; MDV4=N aded vehid STWC=ad /ammonia ygen sens: nsor; PMS: R=pulsed A =full/partia s; CNG/L	MDV 8501- cle weight; Isorbing TV sorbing TV sor; WR-HO =particulate MR; SFI/MI al/both on-t NG=	VC; ammon 2S or e matter	
DT3=LD1 0000#GV LVW=adj /U=warm xidation c FS=Wide ensor; EG equential/ agnostic;	T 6001-8500 /WR; MDV 8 /Justed LVW -up catalyst :atalyst; CTr a range/line. GR=exhaust / multiport fi ; DOR=dire ed/liquefied	#GVWR,3 =MDV 100 ; LEV=low ; NAC=NO OX/PTOX= ar/heated a t gas recirc uel injection ect ozone re	PC=passer 751-5750#/ 1001-14000#/ emission ve emission ve continuous con	I ger car; LI ALVW; LDT SVWR; EC SVWR; EC chicle; ULE n catalyst; S /periodic tra sensor; NC RC=EGR c tf fuel inject T=Hydroca refied petrol 15 MOD	DT=light-or 4=LDT 6 S= emiss V=ultra L SCR-U or ap oxidize DXS= NO DOS= NO DOS N	duty truck; L 1001-8500#(1001-8500#(1004-100-100 1004-100	BVWR,5 system; =super L R-N or S iesel Par DQS=re ondary a uper cha eed carb " Ethance HICLE RATIVE	T<6000# 751-8500 STD= sta JLEV; TV CRC-NH ticulate F ductant q ir injectio rger; CA oon canis ol ("15%"	GVWR,(#ALVW; ndard; C VC/OC=3 3= selec ilter (acti uality sei n (belt dr C=charg gasoline) ELS IN	MDV=m ERT= cer -way/oxid tive cataly ve); HO2 nsor; NH2; iven)/(ele air coold 2=parall Fuel; IFORN	edium-d tificatior dizing ca tic redu S/O2S= 2S = Am ectric driv er; OBD el; (2) su IATIO	uty vehicle n; LVW=lo talyst; AD ction-urea heated/ox monia ser ven); PAIF (F)/(P)(B) uffix=serie	S000#GVW e; MDV4=N aded vehid STWC=ad /ammonia ygen sensi ssor; PMS: R=pulsed A =full/partia s; CNG/L SPE	MDV 8501- cle weight; sorbing TV ; NH3OC= or; WR-HO =particulate AIR; SFI/MI al/both on-t	VC; ammon 2S or e matter	