**California Environmental Protection Agency** 

HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0620

OB Air Resources Board

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-14-012;

## IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFUL LI	FE (miles)	FUEL TYPE		
2015	FHNXV02.4DA3	Passenger Car	"LEV II" Ultra Low Emission	EXH / ORVR	EVAP	Gasoline (Tier 2 Unleaded)		
	111111111111111111111111111111111111111	i assenger var	Vehicle (LEV II ULEV)	120K 150K		Gasonne (Ther 2 Onleaded		
No.	ECS & SPI	ECIAL FEATURES	EVAPORATIVE FAM		DISPLACEMENT (L)			
1 .	WU-TWC, TWC, WR	-HO2S, HO2S, SFI, OBD(F)	FHNXR0151	. 10				
*		*	*		.2.4			
*		*	*	Link				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50<sup>°</sup> Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV, amended December 6, 2012).

# BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT, and MDV, amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a largevolume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volumemanufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_\_ day of July 2014.

mones nnette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

**O** Air Resources Board

HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0620

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG+NOx FLEET N AVERAGE [g/mi]		NMOG ( CH4 R	NMOG @ RAF=* CH4 RAF = *		CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/test]=2/3 day diumal+											
CERT	STD	NMOG	NMHC	NMHC STD [g/mi]	mi=mile; H	hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure										
0.078	0.100	CERT	CERT		CO	[g/mi]	NOx [g/mi]	x [g/mi]	H	CHO [mg/	IO [mg/mi]	PM [g/	mi]		Dx [g/mi]	
0.078	0.100		[g/mi] [g/mi]		CERT	STD	CERT				TD	CERT	STD	CERT	ST	
	@ 50K	0.022	*	0.040	0.7	1.7	0.02	0.05			8.	*	*	0.02	0.0	
	@UL	0.035	*	0.055	1.1	2.1	0.04	0.07			1.		0.01	0.03	0.0	
	D 50°F & 4K	*	*	*	*	*	*	*		*	*	*	* *	*	*	
CO [g/mi] @ 20°F & 50K				NMHC+NC (compo		CO [g (comp		NMHC [g/mi] [			[g/mi] 606]		C+NOx [SC03]		[g/mi] 203]	
		-	1	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	ST	
ERT	1.8	SFTP @ 4	000 miles	*	*	*	*	0.08	0.14	0.7	8.0	0.02	0.20	1.0	2.7	
STD	10.0	SFTP	@* miles	*	*	*	*	*	*	*	*	*	*	*	*	
Evaporative Family			urnal + Hot s/test) @ U	I + Hot Soak at) @ UL 2-Days Diurnal + Hot (grams/test) @				Running Loss (grams/mile) @ UL			On-Board Refueling Vapor Recovery (grams/galion) @ UL					
			CERT	ST	D	CERT	S	TD	CER	T	STD		CERT	STD		
FH	NXR0151V	FA	0.25	0.5	50	0.29	0	0.65 0		0.05			0.002		0.20	
	*		*			*		*		* *			*			
*			*			*		*	*		*		*	*		
	. *		*	*		*		*	*	* *		*		*		
DT3=LD 0000#GV ALVW=ac VU=warn oxidation AFS=Wid ensor; Ec equentia	blicable; UL= DT 6001-8500 VWR; MDV8 djusted LVW n-up catalyst catalyst; CT le range/linea GR=exhaust I/ multiport fic; DOR=dire ad/liquéfied	0#GVWR,3 5=MDV 1000 (; LEV=low ( t; NAC=NO) 0X/PTOX= ar/heated ai t gas recircu uel injection	751-5750#/ 01-14000#0 emission ver adsorption continuous r-fuel ratio lation; EGF ; DFI=direc ducing; HC	ALVW; LDT SVWR; EC: catalyst; S /periodic tra sensor; NC RC=EGR co t fuel injecti T=Hydroca	4=LDT 6( S= emissi V=ultra LE CR-U or ap oxidize DXS= NO: Doler; AIR on; TC/S rbon Trap	001-8500# EV; SULEV SCRC/SC r; DPF = D x sensor; R /AIRE=sec C= turbo/s ; BCAN=b	GVWR,57 system; S /=super U R-N or S iesel Part DQS=rec ondary ai uper char leed carb	751-8500; STD= star JLEV; TW CRC-NH: ticulate Fi ductant qu ir injectior rger; CAC on caniste	#ALVW; ndard; C /C/OC=3 3= selec liter (acti uality sen (belt dr c=charge er; prefix	MDV=me ERT= cert 3-way/oxid tive cataly ive); HO25 nsor; NH3 riven)/(elec e air coole c 2=paralle	edium-du tification izing ca tic reduc S/O2S=I S = Amu ctric driv r; OBD	ty vehicle; talyst; LVW=loa talyst; ADS ction-urea/a neated/oxyg monia sens ven); PAIR= (F)/(P)(B)=	MDV4=N ded vehic TWC=ad ammonia; gen sensc or; PMS= =pulsed A full/partia	MDV 8501- cle weight; sorbing TW NH3OC=a pr; WR-HO particulate IR; SFI/MF I/both on-b	VC; immon 2S or matter I=	
					ourrigue,		-	1 1070 9	acentre)	1 0.01,	-					
ompress	AKE			IS MOD	EL YEA	EVAPO	HICLE RATIVE MILY	MODE	s E	NGINE	VEH		SPE		OBD	
ompress M/			201	EL	EL YEA	EVAPO FAN	RATIVE	EC	s E	NGINE	VEH	IICLE		JRES	OBD	