California Environmental Protection Agency

O Air Resources Board

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-14-012;

#### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL			EXHAUST EMISSION STANDARD CATEGORY USEFUL LIFE (mile			FUEL TYPE		
2015	FVGAV02.0VSE	Passenger Car	"LEV II" Super Ultra Low Emission Vehicle (LEV II	EXH / ORVR EVAP   120K 150K		Gasoline (Tier 2 Unleaded)		
2015			SULEV)					
No.		ECIAL FEATURES	EVAPORATIVE FAI		DISPLACEMENT (L)			
1		2S, HO2S(2), DFI, TC, AIR, CAC, OBD(F)	FVGAR0110					
*		*			2			
*		*	•	Can B				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50<sup>°</sup> Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV, amended December 6, 2012).

## **BE IT FURTHER RESOLVED:**

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California 2001 through 2014 Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2009 through 2016 Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT, and MDV, amended December 6, 2012 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a largevolume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volumemanufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 24th day of April 2014.

menes Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

**California Environmental Protection Agency** 

**O** Air Resources Board

VOLKSWAGEN GROUP OF AMERICA, INC.

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG+NOx FLEET NMOG AVERAGE [g/mi] CH4		@ RAF=* AF = *	NMOG or													
CERT	STD	NMOG	NMHC	NMHC STD [g/mi]	hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit; SFTP=supplemental federal test procedure											
0.073	0.400	CERT	RT CERT			[g/mi]	NOx [g/mi]			CHO [mg/mi]		PM [g		Hwy NOx [g/r		
0.073	'3 0.100 [g/mi]				CERT	STD	CERT	STD			TD	CERT	STD	CERT	STE	
	@ 50K	*	*		*	*				*	*	*	*		*	
	@ UL	0.004	*	0.010	. 0.2	1.0	0.01	0.02		*	4.	0.004	0.01	0.003	0.03	
	50°F & 4K	0.007	*	0.020	0.2	1.0	0.01	0.02		*	8.	*	*		*	
CO [g/mi] @ 20°F & 50K				NMHC+NOx [g/mi] (composite)		i] CO [g/mi] (composite)		NMHC+NOx [g/mi] [US06]		CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
				CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
ERT	2.0	SFTP @ 4	S.S. Silve and have been a second	*	*	*	*	0.03	0.14	1.5	8.0	0.03	0.20	0.2	2.7	
STD	10.0	SFTP	@ * miles		*	*	*	*	*	*		*	*	*	*	
Evaporative Family FVGAR0110VAE * * *		nily					-Days Diurnal + Hot Soak (grams/test) @ UL			Running Loss (grams/mile) @ UL		On-Board Refueling N Recovery (grams/gallor				
			CERT	ST	D	CERT	S	TD	CER	RT	STD		CERT		STD	
		AE	0.33	0.	50	0.34	0.6	.65	0.00	0.000			0.01		0.20	
			* *			*		*	*		*		*		*	
			*		•	*		*	*	* *		*		*		
			*	*		* *		*	* *		*		*			
0000#G ALVW=ac VU=warn oxidation AFS=Wid sensor; E sequentia liagnostic	T 6001-8500 VWR; MDVS djusted LVW n-up catalyst; CTu e range/line GR=exhausi // multiport fi c; DOR=dire ed/liquefied	5=MDV 100 (; LEV=low 4 (; NAC=NO: OX/PTOX= ar/heated a t gas recircu uel injection ect ozone re	01-14000#0 emission ve x adsorption continuous ir-fuel ratio ulation; EGI t; DFI=direc ducing; HC	GVWR; EC shicle; ULE n catalyst; S /periodic tra sensor; NC RC=EGR co t fuel injecti T=Hydroca	S= emiss V=ultra L SCR-U or ap oxidize DXS= NO poler; AIR ion; TC/S rbon Tran	ion control EV; SULEV SCRC/SC er; DPF = D x sensor; F VAIRE=sec SC= turbo/s b; BCAN=b	system; s <b>R-N or S</b> Diesel Part <b>RDQS</b> =rec condary as super cha	STD= star JLEV; TM CRC-NH ticulate F ductant q ir injection rger; CAC on canist	ndard; C /C/OC=: 3= select ilter (act uality se n (belt du C=charg er; prefit	ERT= cer 3-way/oxid tive cataly ive); HO23 nsor; NH3 riven)/(ele e air coole x 2=paralle	tification lizing ca tric redu S/O2S= S = Am ctric driv er; OBD	n; LVW=loa ttalyst; ADS ction-urea/ heated/oxy monia sen ven); PAIR (F)/(P)(B);	aded vehic STWC=ad ammonia; gen senso sor; PMS= =pulsed A =full/partia	NH3OC= or; WR-HO particulate IR; SFI/MI	VC; ammon 2S or e matter FI=	
	AKE			15 MOD		AR: VE	HICLE	MODE	ELS IN	Constitution of the local division of the						
VOLKSWAGEN EO			INICE	EL			RATIVE	EC NC	5	SIZE (L)		HICLE YPE	FEAT	URES	OBD	