California Environmental Protection Agency

GENERAL MOTORS LLC. OB Air Resources Board

Executive Order: A-006-1981 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 5

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

VEAR 2016 GGMXT05.3382 LDT3 FLEX-FUEL VEHICLE 85% ETHANCOME EXH/ORVR EVAP FTP SFTP FTP SFTP FTP SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS COMPOSITE TOUR SYSTEMS PARTIAL TOUR TOUR			
USEFUL LIFE (miles)	L TYPE		
EXH/ORVR	85% ETHANOL, GASOLINE		
150000 150000 LEV3 ULEV125 LEV 3 COMPOSITE * N	E IN-USE STD		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS 1 2TWC, TWC, 2H02S(2), DFI *	SFTP		
SYSTEMS	NMOG+NOX		
* * PARTIAL * PARTIAL * PARTIAL WITH FINES EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION EVAP EMISSION STD	DISPLACEMENT		
* * PARTIAL WITH FINES * EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION EVAP EMISSION STD			
* FINES * EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION EVAP EMISSION STD	5.3		
EVAP EMISSION STD			
EVAP EMISSION STD			
EVAP / ORVE FAMILY EVAPORATIVE STD CATEGORY VEHICLE CLASS	SPECIAL FEATURES		
GGMXR0176820 LEV 2 LDT3	*		
GGMXR0223840 LEV 2 LDT3	*		
EMISSION CREDIT INFORMATION			
NMOG CREDIT FOR NMOG CREDIT FOR	OPTIONAL EXH.		
BASELINE PZEV AT PZEV TZEV NON-PZEV ZERO-EVAP DOR	TRUCKS		
* * * N N	N		
NMOG AND FLEET AVERAGE INFORMATION			
NMOG RAF CH4 RAF RATIO (CASOLINE) HCHO/NMHC RATIO PC+LDT (0-3750 LVW) LDT (375	NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		
* * 1.10 * 0.093	0.110		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

California Environmental Protection Agency

OB Air Resources Board

GENERAL MOTORS

Executive Order: A-006-1981

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 5

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

day of May 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

GENERAL MOTORS LLC. Executive Order: A-006-1981

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 5

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/fest]: 2/3 days diumal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	E85-EPA (GASOLINE- LEV3 E10)	0.063 (0.036)	0.125 (0.125)	0.4 (0.4)	2.1 (2.1)	* (*)	* (*)	1 (*)	4 (4)	* (*)	0.01 (0.01)
50°F @4K	*	*	*	*	*	*	*	*	*		

		NMOG+N	Ox (g/mi)	CO (g/mi)		
A E TO W	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	E85-EPA (GASOLINE-LEV3 E10)	0.006 (0.003)	0.125 (0.125)	100	- 1	
20°F @ 50K	E70 (70% ETHANOL + 30% COLD CO REGULAR GASOLINE) (GASOLINE-COLD CO LOW OCTANE)			1.5 (1.8)	12.5 (12.5)	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		-		US06		SC03		COM	POSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
0.414		CERT	*	*	1	*	*	1 2 1 2 1		
@ 4K	@ 4K *	STD	*	*		*	*		1	
		CERT	*	*	*	*	*	0.032	0.4	*
@UL	GASOLINE- LEV3 E10	STD	. *	*	*	*	*	0.110	4.2	*
	THIT'S ELV	BIN					De. II	0.120		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY			WHOLE						
	FUEL TYPE	3DHS (g/test) @ UL			2DI	HS (g/test) (RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
GGMXR0176820	E10-EPA	0.55	0.90	*	0.38	1.15	*	0.00	0.05
GGMXR0176820	GASOLINE - TIER 2 UNLEADED	0.75	*	*	0.48	*	*	0.00	*
GGMXR0223840	E10-EPA	0.71	0.90	*	0.76	1.15	*	0.00	0.05
GGMXR0223840	GASOLINE - TIER 2 UNLEADED	0.71	*	*	0.65	*	*	0.00	*

California Environmental Protection Agency

OD Air Resources Board

GENERAL MOTORS LLC. Executive Order: A-006-1981 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 5

ORVR / FU	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS												
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	(55)) UL	FUEL TYPE	3DHS RIG TEST FUEL TYPE (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
GGMXR0176820	GASOLINE - TIER 2 UNLEADED	0.02	0.20	*	*	*	*	*	*	*			
GGMXR0223840	GASOLINE - TIER 2 UNLEADED	0.03	0.20	*	*	*	*	*	*	*			

": not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for sparkignited engine; HO2S/O2S; heated/oxygen sensor; WR-HO2S or AFS; wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor, RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

GENERAL MOTORS LLC. Executive Order: A-006-1981

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 5 of 5

2016 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
CHEVROLET	C15 SILVERADO 2WD	LDT3	5.3	A6	GGMXR0176820	1	F	*
CHEVROLET	C15 SILVERADO 2WD	LDT3	5.3	A 6	GGMXR0223840	1	F	*
CHEVROLET	C1500 SUBURBAN 2WD	LDT3	5.3	A6	GGMXR0223840	1	F	*
CHEVROLET	C1500 TAHOE 2WD	LDT3	5.3	A6	GGMXR0176820	1	F	*
CHEVROLET	K15 SILVERADO 4WD	LDT3	5.3	A6	GGMXR0176820	1	F	*
CHEVROLET	K15 SILVERADO 4WD	LDT3	5.3	A6	GGMXR0223840	1	F	*
CHEVROLET	K1500 SUBURBAN 4WD	LDT3	5.3	A6	GGMXR0223840	1	F	*
CHEVROLET	K1500 TAHOE 4WD	LDT3	5.3	A6	GGMXR0176820	1	F	*
GMC	C15 SIERRA 2WD	LDT3	5.3	A6	GGMXR0176820	1	F	*
GMC	C15 SIERRA 2WD	LDT3	5.3	A6	GGMXR0223840	1	F	*
GMC	C1500 YUKON 2WD	LDT3	5.3	A6	GGMXR0176820	1	F	*
GMC	C1500 YUKON XL 2WD	LDT3	5.3	A6	GGMXR0223840	1	F	*
GMC	K15 SIERRA 4WD	LDT3	5.3	A6	GGMXR0176820	1	F	*
GMC	K15 SIERRA 4WD	LDT3	5.3	A6	GGMXR0223840	1	F	*
GMC	K1500 YUKON 4WD	LDT3	5.3	A6	GGMXR0176820	1	F	*
GMC	K1500 YUKON XL	LDT3	5.3	A6	GGMXR0223840	1	F	*