## California Environmental Protection Agency

# **OD** Air Resources Board

HYUNDAI MOTOR COMPANY Executive Order: A-254-0312

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GRO	UP INF	ORMATION					
MODEL YEAR					LASS(ES) FUEL CATEGORY			FUEL TYPE			
2016	GHYXV0	1.617	TE.	PC			SINGLE FUEL	GASOLINE			
US	EFUL LIFE	(mile	s) \	EHICLE EMISS	ION CA	TEGORY	INTERIM / INT	ERMEDIA	TE IN-USE STD		
EXH/O	RVR	EV	'AP	FTP		SFTP	FTP		SFTP		
1200	00	150	0000	EV2 ULEV		2 SFTP	*		•		
SPECIA	AL FEATU		EXHAUST EMIS	SION CONTRO	-	OBD S	TATUS	ENGINE	DISPLACEMENT		
1	WU-TWC	, TWC	, HO2S(2), DE	I, TC, CAC		FULL	ALL MODELS				
*	,		*, . "	4		PARTIAL	*	* 1.6			
*			*		P	PARTIAL WITH	*				
			EVAPORATIVE	& REFUELING	(EVAP	ORVR) FAMILY	INFORMATION				
EVAP /	ORVR FA	MILY	EVAPORAT	IVE STD CATE	SORY		SSION STD E CLASS	SPECIA	L FEATURES		
GHY	XR012813	E		LEV 2		PC			*		
				EMISSION C	REDIT II	NFORMATION					
	ALLO	WANC	E FOR TEST GR	OUP		OG CREDIT FO			OPTIONAL EXH STD FOR WORK		
BASELINE PZEV AT PZEV				TZEV	NON	-PZEV ZERO-E	VAP DO	PR	TRUCKS		
	*		*	*		N	. N	r	N		
			NM	OG AND FLEET	AVER	AGE INFORMA	TION				
NMOG R	OG RAF CH4 RAF FTP NMOG/NMHC RATIO HCHO/NMH		HC RAT	TIO PC+LDT	OX FLEET STD (0-3750 LVW) (g/mi)	NMOG+NOX FLEET STE LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)					
*	*		1.04		*		0.093		0.110		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### California Environmental Protection Agency

**On Air Resources Board** 

HYUNDAI MOTOR COMPANY Executive Order: A-254-0312

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 22 ncl day of May 2015.

Michael J. Reffar AH Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

California Environmental Protection Agency

O Air Resources Board

HYUNDAI MOTOR COMPANY Executive Order: A-254-0312

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

ORVR / FU	EL ONLY / CA	NISTER	BLEED	<b>EVAPORATIVE</b>	EMISSION	STANDA	RDS AND	CERTIFICA	ATION LEV	ELS			
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/g	gallon) @	D) UL	FUEL TYPE		IG TEST ) @ UL		IG TEST ) @ UL	BLEED CANISTER TEST (g/test) @ 4K				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
GHYXR01281TE	GASOLINE - TIER 2	0.03	0.20	*	*	*	*	*	*	*			

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: \_DT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger yehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst: CTOX/PTOX; continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for sparkquited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOX sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%" ethanol ("15%"gasoline) fuel; E10; "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

### 2016 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	VEH CLASS ENGINE (L)		EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
HYUNDAI	TUCSON AWD	PC	1.6	AMS7	GHYXR01281TE	1	F	*
HYUNDAI	TUCSON ECO AWD	PC	1.6	AMS7	GHYXR01281TE	1	F	*
HYUNDAI	TUCSON ECO FWD	PC	1.6	AMS7	GHYXR01281TE	1	F	*
HYUNDAI	TUCSON FWD	PC	1.6	AMS7	GHYXR01281TE	1	F	*

HYUNDAI MOTOR COMPANY Executive Order: A-254-0312

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

# **OB** Air Resources Board

# ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS
EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)
CH4: methane: NMOG: non-CH4 organic dae: HC: hydrocarbon: NMHC: non-CH4 HC: CO: cosh

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	GASOLINE - TIER 2 UNLEADED	0.018	0.040	0.2	1.7	0.01	0.05	*	8	*	*
FTP@UL	GASOLINE - TIER 2 UNLEADED	0.024	0.055	0.3	2.1	0.02	0.07		11	*	0.01
50°F @4K	GASOLINE - TIER 2 UNLEADED	0.028	0.080	0.2	1.7	0.01	0.05		16		

1	FUEL TYPE	NOx	(g/mi)	CO (g/mi)		
None and a second	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	GASOLINE - TIER 2 UNLEADED	0.01	0.07			
HWFET @ UL	GASOLINE - TIER 2 UNLEADED	0.01	0.09			
20°F @ 50K	GASOLINE-COLD CO LOW OCTANE			0.5	10.0	

## SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		TOTAL		US06		SC03	3	COMPOSITE			
	FUEL TYPE		NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMHC+NOx (g/mi)	CO (g/mi)	NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
	GASOLINE - TIER 2 UNLEADED	CERT	0.03	3.2		0.02	0.1			7 -	
@ 4K		STD	0.14	8.0		0.20	2.7		V-1		
		CERT	*	*	*	*	*	*	* *	. *	
@UL	*	STD	*	*	*	*	*	*	*	*	
		BIN	Aller San			1.4		*			

## WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE						
EVAPORATIVE	FUEL TYPE	3DH	S (g/test) (	@ UL	2D	HS (g/test) (	RL (g/ml) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
GHYXR01281TE	GASOLINE-CA PHASE 2	0.26	0.50	*	0.17	0.65	*	0.01	0.05