## California Environmental Protection Agency

**OB** Air Resources Board

HONDA MOTOR CO.,

Executive Order: A-023-0653

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP INFO	ORMATION						
MODE	TEST GENOLIE			VEHIC	LE CLASS(E	ES)	FUEL CATEGORY  DEDICATED SINGLE FUEL  VEHICLE			FUEL TYPE  GASOLINE			
2017 HHNXV03.5VH3			3.5VH3		PC ,								
	USEFUL	LIFE	(miles)	VEI	HICLE EMISS	SION CA	TEGORY	IN'	TERIM / INTE	RMEDIA	TE IN-USE STD		
EXH/ORVR EVAP			FTP			SFTP		FTP		SFTP			
150000 150000			LEV3	ULEV125	COMPOSITE	OSITE *			NMOG+NOX				
SPE	CIAL FE	ATUR		IAUST EMISSI TEMS	ON CONTRO	DL	OBD S	STATU	s	ENGINE	DISPLACEMENT (L)		
1	. 2WU-TWC, TWC, 2WR-HO2S, 2HO2S, EGR, DFI FULL *												
*	* PARTIAL ALL MODELS										3.5		
*			* PARTIAL WITH * FINES										
			EV	APORATIVE &	REFUELING	(EVAP	ORVR) FAMIL	Y INF	ORMATION				
EVA	P / ORV	R FAN	NILY :	EVAPORATIV	E STD CATE	GORY	EVAP EM VEHICL			SPECIA	L FEATURES		
Н	IHNXR01	51VF2	4	I	LEV 2			PC			*		
		-			EMISSION C	REDIT II	NFORMATION						
. ALLOWANCE FOR TEST GROUP							NMOG CREDIT FOR NMOG CR			B STD FOR WOR			
BASELINE PZEV AT PZEV					TZEV	TEV LENO-	ZERO-EVAI		TRUCKS				
	*			*	* N			N			N		
				NMO	AND FLEE	T AVERA	GE INFORMA	MOITA					
NMOG RAF	CH4 RAF  RAF  RATIO  FTP  NMOG/NMHC RATIO  HCHO/NMHC RATIO  NMOG+NOX PC+LDT (0 (g/n				3750 LVW) LDT (3751 LVW-85								
*	*		1.10	0.05		0.086		0.101			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of

California Environmental Protection Agency

**⊘** Air Resources Board

HONDA MOTOR CO., LTD.

Executive Order: A-023-0653 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of June 2016.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

UNLEADED

HONDA MOTOR CO., LTD. Executive Order: A-023-0653

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 3 of 4

							A	TTAC	НМ	ENT								
	EXHA	US	TANE	EV	APOR	ATIVE	EMIS	SION	STAN	DARD	SANE	CERT	FIC	ATION	LEVE	S	-	
		EXH	AUST	EMIS	SSION S	TANDA	RDS A	ND CER	TIFICA	TION L	EVELS	(FTP, HW	FET,	50°F, 20	)°F)			
	FUI	FUEL TYPE			oxide; No stment fa R [g HC/	Ox: oxidenctor; 2D gallon d	es of nita HS/3DH lispense	rogen; H HS [g HC d]: on-b	ICHO: c/test]: oard re	formalde 2/3 days fueling	ehyde; P diurnal- vapor rec	bon; NMH M: particu +hot-soak covery; g: ure; SFTF	late r ; RL [ gram	natter; R g HC/mi ; mg: mi	AF: read ]: running lligram; r	tivity g loss	3;	
	- *				NMOG+NOx (g/mi)		(	CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)			PM (g/mi)			
				CE	RT	STD	CERT	ST	D	CERT	STD	CER	Т	STD	CERT		STD	
FTP@5	OK	*		*		*	*	*		*	4	*	V	*	*		*	
CTD/MIII		GASOLINE- LEV3 E10		0.0	656 0	.125	0.13	2.	1	*				4	*	* 0.0		
50°F @	4K	*		16		*	*	*			. *	*		*	1	-	ж.	
				FUEL TYPE							x (g/mi)			CO (g/mi)				
									-	CERT		STD		CER	Т	S	rD	
HWFE	r @ 50K					*						*	_					
HWFE	T@UL			GASOLINE-LEV3 E10						0.0	412	0.125				-		
20°F	@ 50K		GA	SASOLINE-COLD CO LOW OCTANE										0.66		10.0		
				SFTF	EXHAL	JST EM	ISSION	STAND	ARDS	AND C	ERTIFIC	ATION LI	EVEL					
			-		US06					SC03					COMPOSITE			
	FUEL 1	YPE		N	(g/mi		CO (g/mi)		PM g/mi)		s+NOx mi)	CO (g/mi)		g/mi)	(g/m	1	PM mg/mi)	
@ 4K	* s		CER			<b>Y</b>				ŀ	*							
			STD	-	*		*				*	*		-		_		
	CO COT TITM		CER			* *		*	*		*	0.0612		0.6	4	*		
@ UL			STD		*		*		*	,	k	*	0	.103	4.3	2	*	
		BI		N					-					.100				
		WI	HOLE	/EHI	CLE EV	APORA	TIVE E	MISSIO	N STAI	NDARD	S AND C	ERTIFIC	ATIO	N LEVE	LS			
						WI	HOLE V	EHICLE	EVAP	ORATI	/E TEST	ING		_	1 (!!)	011		
	ORATIV MILY	1 -11-1		TYPE 3DHS (g.		/test) @ UL			2DHS (g/test)		@ UL		R	L (g/mi)	g/mi) @ UL			
					CERT S		TD FEL		CE	CERT S		FEI	FEL		RT	STI		
HHNXR0151VF		A	GASOLINE - CA PHASE 2		10 2	24 0	0.50 *		0.2	254	0.65	*	*		00	0.05		
(	DRVR / F	UEL	ONLY	/ CA	NISTER	BLEED	EVAPO	DRATIV	V-4			RDS AND				VEL	S	
EVAPORATIVE FAMILY		E	ORVR (g/gallo						30	HS RIG	2DHS	& CANISTER BLE  2DHS RIG TEST		BLEED CANISTER				
		FUEL TVD		DE	E CERT STD		FUEL TYPE			(g/test) @ UL CERT STD			(g/test) @				/test) @ 4K	
		GA A	GASOLINE TIER 2		0.008					* *		*			*		*	

California Environmental Protection Agency

Air Resources Board

HONDA MOTOR CO., LTD. Executive Order: A-023-0653 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle: HDV; heavy-duty vehicle: ECS; emission control system; CERT; certification; STD; standard; FEL; family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2017 MODEL YEAR: VEHICLE MODELS INFORMATION										
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE		
ACURA	MDX	PC	3.5	SA9	HHNXR0151VFA	1	P	*		