California Environmental Protection Agency

⊘ Air Resources Board

GENERAL MOTORS LLC. Executive Order: A-006-2105

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

-					TEST GR	OUP IN	FORMAT	ION					
MODEL		EST GI	ROUP	VEHIC	CLE CLASS(LE CLASS(ES)			TEGORY	FU	FUEL TYPE		
2018	JG	MXT03	. 6151		LDT3				SINGLE FUEL	G	GASOLINE		
L	JSEFUL	LIFE	(miles)	VE	HICLE EMIS	SION C	ATEGOR	Y	INTERIM / IN	TERMEDIA	TE IN-USE STD		
EXH	ORVR	T	EVAP		FTP			SFTP			SFTP		
150	0000		150000	LEV	3 ULEV70	LEV	3 СОМРО	SITE	NMOG+NOX AN	D PM	PM PM		
SPEC	CIAL FE	ATUR	ES & EXH	AUST EMISS	ION CONTRO	OL		OBD ST	ATUS	ENGINE	DISPLACEMENT (L)		
1	1 DFI, 2TWC(2), 2HO2S(2)							ULL ALL MODELS					
*				*	9/2		PARTIAL *				3.6		
*				*			PARTIAL WITH						
			EV	APORATIVE 8	REFUELIN	G (EVAI	PIORVR)	FAMILY	INFORMATION				
EVAI	P / ORV	R FAN	IILY .	EVAPORATIV	E STD CATE	EGORY		AP EMIS	SION STD CLASS	SPECIA	L FEATURES		
J	GMXR01	46402		LEV 3 OP	TION2 WITH	ON2 WITH FEL LI			DT3		HCT		
					EMISSION	CREDIT	INFORM	ATION					
ALLOWANCE FOR TEST GROUP								EDIT FO		EDIT FOR	OPTIONAL EXH STD FOR WORK		
BASELINE PZEV AT PZEV					TZEV	NO	N-PZEV	ZERO-EV	AP DO	JK	TRUCKS		
	*				*		1	1	1	A	N		
				NMO	G AND FLEE	T AVE	RAGE IN	ORMAT	ION				
NMOG RAF	NMOG/NMHC			HCHO/NMHO RATIO	D(.TI I) 1 (D-			LDT (3	IOG+NOX FLEET STE DT (3751 LVW-8500 VWR) + MDPV (g/mi)		MDV (10,001-14,000 GVWR) (g/mi)		
*	* 1.10 * 0.0						0.092				*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

⊘ Air Resources Board

GENERAL MOTORS LLC. Executive Order: A-006-2105

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

For evaporative family JGMXR014640A, the manufacturer has attested to compliance with the 0.02 inch effective leak diameter standard in 13 CCR Section 1976(b)(1)(G)6 ["Effective Leak Diameter Standard And Procedure"].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

⊘ Air Resources Board

GASOLINE-

TIER3 E10

0.05

0.20

JGMXR014640A

GENERAL MOTORS LLC.

Executive Order: A-006-2105

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

0.009

0.020

ATTACHMENT

			-									_		LEVELS		
	ا	XHA	UST EN	IISSIO	NST	ANDA	RDS A	ND CERT	IFICATIO	N LEVELS	FTP, H	WFET	, 50°F, 20	°F)		
	FUE	TYP	mo adj OR 100	noxide ustmer VR [g	; NO) nt fac HC/g	c: oxide tor; 2D allon d	es of nit HS/3DH ispense	rogen; HO HS [g HC/ ed]: on-bo	CHO: formatest]: 2/3 dard refuelia	aldehyde; ays diurna ng vapor n	PM: partical+hot-soa ecovery;	culate ik; RL g: gran	matter; Ra [g HC/mi]	C; CO: ca AF: reactiv : running lo ligram; mi: Il FTP	ity oss;	
				NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HCH (mg/n			PM (g/mi)	
10.74			C	ERT	S	TD	CERT	STD	CER	T STI	CE	RT	STD	CERT	STD	
FTP@50	K	*		*		*	*	*	*	*				*	*	
FTP@U	TP@UL GASOLINE-			.022	0.	070	0.4	1.7	*	*	1		4	0.001	0.003	
50°F @4	K	*		*		*	*	*	*	*			*			
					FUE	L TYPI	E				Ox (g/m		CER	CO (g/mi)		
William St.									-14	CERT		STD		S. T. Marie Marie Value of the	STD	
HWFET	@ 50K					*				*	*		The state of the s	The second second		
HWFET	T@UL			GASO	LINE	-TIER	3 E10			0.007	0.0	70				
20°F (@ 50K	COI						E (TIER	Bellett	1.4			2.7		12.5	
Tiell along			SF	TP EX	HAUS		ISSION	STANDA	RDS AND	CERTIFI		LEVE		MPOSITE		
	FUEL TY	PE		NMO (g	G+NC /mi))x	CO (g/mi)	Pl (mg/		IOG+NOx (g/mi)	CO (g/mi)	NN	IOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi	
@ 4K	*	* CE		रा *		*			*							
					*	V	* /			* .	*			1. 製物學		
		GASOLINE- SIER3 E10					, *	* 7		*			0.028	0.4	*	
@ UL					*		*	10		*	*		0.097	4.2	*	
			BIN						第一				0.080	多為為		
		WHO	LE VE	HICLE	EVA		-					CATIC	N LEVEL	.S		
EVAPORATIVE FUEL		IEI TVI	TYPE 3DHS (g/test) @ UL										RL (g/mi) @ UL			
		1	UEL TYPE		CERT STD					2DHS (g/test) ERT STD		FEL		T	STD	
JGMXR014640A			SOLIN	LINE- 0 334 0				0.343					0.00 0.05			
0	RVR / FL				ER E	BLEED	EVAP	ORATIVE	EMISSIO	N STAND	ARDS AI	ID CE	RTIFICAT	TION LEVE	LS	
		T											R BLEED			
EVAPORATIVE FAMILY		0	ORVR (g/gallon) @ UL						3DHS I	DHS RIG TEST (g/test) @ UL		2DHS RIG T (g/test) @				
			14414 (8	, gane	, e		FUE	L TYPE								

GASOLINE-

TIER3 E10

GENERAL MOTORS

Executive Order: A-006-2105

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semiautomatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT; other transmission.

2018 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	OBD	PZEV TYPE
BUICK	ENCLAVE	LDT3	3.6	SA9	JGMXR014640A	1	F	*
BUICK	ENCLAVE AWD	LDT3	3.6	SA9	JGMXR014640A	1	F	*
CADILLAC	XT5	LDT3	3.6	SA8	JGMXR014640A	1	F	*
CADILLAC	XT5 AWD	LDT3	3.6	SA8	JGMXR014640A	1	F	*
CHEVROLET	TRAVERSE	LDT3	3.6	SA9	JGMXR014640A	1	F	*
CHEVROLET	TRAVERSE AWD	LDT3	3.6	SA9	JGMXR014640A	1	F	*
GMC	ACADIA AWD	LDT3	3.6	A6	JGMXR014640A	1	F	*
GMC	ACADIA FWD	LDT3	3.6	A6	JGMXR014640A	1	F	*