## California Environmental Protection Agency

# **O** Air Resources Board

FORD MOTOR COMPANY

Executive Order: A-010-2066

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP IN	FORMAT	ION					
MODE	- 1	EST G	ROUP	VEH	HICLE CLASS		FUEL CATEGORY			FUEL TYPE			
2018	18 JFMXT02.72JQ				LDT2			DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
(	JSEFUL	LIFE	(miles)	EHICLE EMIS	ICLE EMISSION CATEGORY			INTERIM / INTE			RMEDIATE IN-USE STD		
EXH	ORVR	EVAP FTP SFTP				FTP			SFTP				
150000 150000			LE	V3 ULEV70	70 LEV 3 COMPOS		SITE		+	*			
SPE	CIAL FE	ATUR		IAUST EMIS	SION CONTRO	OL		OBD ST	TATU	IS	ENGINE	DISPLACEMENT (L)	
1	DFI, 2TWC, 2WR-HO2S, 2HO2S, 2TC, CAC						FULL 2		ALI	MODELS			
*	*						PARTIAL *		+	2.7			
*	* PAI						PARTIAI FINI	*					
			EV	APORATIVE	& REFUELIN	G (EVA	P/ORVR)	FAMILY	INF	ORMATION			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO							EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES		
JFMXR0135NBB					LEV 2	LDT2				*			
					EMISSION (	CREDIT	INFORM	ATION					
ALLOWANCE FOR TEST GROUP							NMOG CREDIT FO					OPTIONAL EXH STD FOR WORK	
BASELINE PZEV AT PZEV					TZEV	NC	NON-PZEV ZERO-E		VAP DOI		TRUCKS		
* *					*	*			N N		N		
				NN	OG AND FLEE	TAVE	RAGE IN	FORMAT	TION				
NMOG RAF	CH4 RAF	NMC	FTP G/NMHC RATIO	HCHO/NMI RATIO	PC+LD1		0 LVW) LDT		OG+NOX FLEET STI DT (3751 LVW-8500 VWR) + MDPV (g/mi)		MDV (10,001-14,000		
*	*		1.10	*		0.079		0.092		*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



FORD MOTOR COMPANY

Executive Order: A-010-2066

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

\_\_ day of September 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

UNLEADED

FORD MOTOR COMPANY

Executive Order: A-010-2066

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 3 of 4

# **ATTACHMENT**

						A	IIAC	LIIVI								
	EXHA	UST	AND E	VAPO	RATIVE	EMIS	SION	STAN	NDAR	DS AND	CERT	FICA	TION	LEVELS		
		EXH	AUST EM	ISSION	STANDA	RDS A	ND CER	TIFIC	MOITA	LEVELS (	FTP, HW	FET, 5	50°F, 20°	°F)		
	FUE	L TY	mor adju OR' 100	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; C monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: n adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: runi ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligrar 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTF:									AF: reactive running leading mit in the reactive running leading mit in the reactive running ru	rity oss;		
				NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCH (mg/			PM (g/mi)		
1111			C	ERT	STD	CERT		D	CERT	STD	CER		STD	CERT	STD	
FTP@50	ok	*	Ł	*	*	*	*		*	*	*		*	*	*	
FTP@U	GAS	OLIN	1 (1	0351	0.070	0.32	1.	7	*	*	*	4		*	0.01	
50°F @4	4K	*		*	*	*	*		*	*	*		*	0-		
11-15-	1			FUEL TYPE				NMOG+NOx		x (g/mi)		CO (g/mi				
					TOLLTITLE			CERT		STD		CERT		STD		
HWFET	T @ 50K				*					*	*			-		
HWFET @ UL				GASOLINE-TIER3 E10					0.0	0.0				- 111		
20°F	@ 50K	CC	OLD CO E	10 REG	ULAR G	GASOLINE (TIER3)							0.48		12.5	
			SFT	P EXHA	UST EM	ISSION	STAND	ARDS	AND C	ERTIFIC	ATION LE	EVELS				
-			6			US06			SC03				COI			
	FUEL T	YPE		NMOG+		CO (g/mi)		M J/mi)		G+NOx /mi)	CO (g/mi)		G+NOx J/mi)	CO (g/mi)	PM (mg/mi)	
@ 4K	*		CERT	*		*	463			*	*			14.	No.	
				D *		*	*		*		*				115	
		GASOLINE- TIER3 E10		RT *		* *		*	*		*	0.0449		0.40	. *	
@ UL				. *		*	*		*		*	0.097		4.2	*	
			BIN					-	1 11				.070	al.		
		WH	IOLE VEH	IICLE E								ATION	LEVEL	S		
EVAPORATIVE FAMILY  JFMXR0135NBB			UEL TYP	F	3DHS (g/test) @ UL				PORATIVE TESTING  2DHS (g/test) @ UL			RL (g/mi) @ UL			UL	
			CERT			STD FEL		CE			FEI	CER		T	STD	
		GASOLINE -		- 0.:		. 65	*		336	0.85	*		0.00		0.05	
(	ORVR / F	UEL	ONLY / C	ANISTE	RBLEED	EVAPO	DRATIVE	EEMI	SSION	STANDA	RDS AND	CER	TIFICAT	ION LEVI	ELS	
		T								NLY EVA						
EVAPORATIVE FAMILY  JEMKR0135NBI		FUEL TYPE		(g/gallon) @ UL		FUEL TYPE			3DHS RIG TEST (g/test) @ UL		2DHS RIG (g/test) (				ED CANISTER (g/test) @ 4K	
								CE	ERT STD		CERT	S	TD	CERT	STD	
			SOLINE TIER 2		0.20		*		*	*	*		*	*	*	

FORD MOTOR COMPANY

Executive Order: A-010-2066

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

**⊘** Air Resources Board

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV; heavy-duty vehicle; ECS; emission control system; CERT; certification; STD; standard; FEL; family emission limit: GVWR: gross vehicle weight rating: LVW: loaded vehicle weight: ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S; heated/oxygen sensor; WR-HO2S or AFS; wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic: DOR; direct ozone reducing: HCT; hydrocarbon trap; BCAN; bleed carbon canister; prefix 2; parallel; (2) suffix; series; CNG/LNG; compressed/liquefied natural gas; LPG; liquefied petroleum gas; E85; "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semiautomatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

### 2018 MODEL YEAR: VEHICLE MODELS INFORMATION

1									
	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
	FORD	EDGE AWD	LDT2	2.7	SA6	JFMXR0135NBB	1	F	*
	LINCOLN	MKX AWD	LDT2	2.7	SA6	JFMXR0135NBB	. 1	F	*
	LINCOLN	MKX FWD	LDT2	2.7	SA6	JFMXR0135NBB	1	F	*