

HONDA MOTOR CO., LTD. Executive Order: A-023-0703 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFORI	MATION					
MODE	_	ST GROUP		VEHIC	HICLE CLASS(ES)			FUEL C	ATEGORY		FUEL TYPE		
2018	JH	NXV02.09K2	KV02.09K2 PC						ELECTRIC HICLE		GASOLINE		
	USEFUL	LIFE (miles)	VEHICLE EMISSION CATEGORY				SORY	INTERIM / IN	TER	RMEDIATE IN-USE STD			
EXH/ORVR EVAP					FTP SFTP			ГР	FTP		SFTP		
15	150000 150000			LEV3	SULEV30 LEV 3 COMPO			MPOSITE	PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							OBD STATUS			ENGINE DISPLACEMENT (L)			
1 TWC, WR-HO2S, HO2S, EGR, EGRC, SFI								FULL	*				
*	* *							ARTIAL	ALL MODELS		2.0		
*	* *							TIAL WITH *					
		ΕV	/APC	DRATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y INFORMATIO	N			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
JHNXR0121VSA LEV					3 OPTION2			PC			*		
				E	EMISSION C	REDI	INFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NO ZERO-EVAP							ZEV	NMOG C	MOG CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS		
	У						И				N		
				NMOG	AND FLEET	T AVE	RAGE	INFORMA	TION				
NMOG RAF	CH4 RAF	NIM()(2/NIM(+)(1) P(1+1)) /(1+3/)				0-375				0	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		0.05	0	.079			0.092		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



HONDA MOTOR CO., LTD. Executive Order. A-023-0703

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

day of March 2018.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

111 Junion

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



GASOLINE-TIER3 E10

0.01

0.20

JHNXR0121VSA

HONDA MOTOR CO., LTD. Executive Order: A-023-0703

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

0.004

0.020

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

		EXHA	AUST EM	ISSION S	STAND	ARDS A	ND CERT	IFICA	TION	LEVELS	(FTP, HW	FET	, 50°F, 2	0°F)		
	FUE	FUEL TYPE		noxide; Nostment fa VR [g HC	Ox: oxid actor; 20 /gallon	des of nitro DHS/3DH dispense	rogen; H(HS [g HC/ ed]: on-bo	CHO: test]: ard re	formal 2/3 da fueling	dehyde; P ys diurnal y vapor re	bon; NMH M: particu +hot-soak covery; g: ure; SFTP	late ; RL gran	matter; F [g HC/m n; mg: m	RAF: read i]: runnin illigram; i	ctivity g loss;	
				NMOG+I (g/mi		(CO g/mi)			NOx g/mi)		HCH mg/i			PM g/mi)	
			CI	ERT	STD	CERT	STE		CERT	STD	CER	T	STD	CERT	STD	
FTP@50	K	*		*	*	*	*		*	*	*		*	*	*	
FTP@U		LIN 3 E1	1 (1)	016	0.030	0.4	1.0		*	*	0.4	4		0.00	0.00	
50°F @4	K	*		*	*	*	*		*	*	*		*	1 350		
				FU	EL TYP)F			NMOG+NOx (g/mi)					(g/mi)		
									С	ERT	STD	CER		RT	STD	
HWFET @ 50K				*						*	* *					
HWFET @ UL			GASOLINE-LEV3 E10					0	.004	0.030		11.11				
20°F (@ 50K	CO	LD CO E	E10 REGULAR GASOLINE (TIER3)									0.	0.5 10.		
			SFT	PEXHA	UST EN	ISSION	STANDA	RDS	AND	CERTIFIC	ATION LE	VEL	S			
						US06			SC03			COMPOSITE				
	FUEL TY						PM (mg/mi)		NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NOx (g/mi)		x CC	7.7	
@ 4K	*	, CE		*		*				*	*					
	S		STD	*		*				*	*					
		GASOLINE- LEV3 E10 BIN		*		*	0.	5		*	*		0.011	0.	4 *	
@ UL				*		*	10	0	*		*	0.097		4.:	*	
												-	0.050			
		WH	OLE VEH	ICLE EV	-						ERTIFIC	ATIC	N LEVE	LS		
					W	HOLE V	EHICLE	EVAP	ORAT	IVE TEST	ING		١.	31. (-l1)		
EVAPORATIVE FAMILY		FUEL TYPE		E :	3DHS (g/test) @ UL				2DF	2DHS (g/test) @ UL				KL (g/mi)	(g/mi) @ UL	
				CERT		STD	FEL	CERT		STD	FEL		CERT		STD	
JHNXR	0121VSA	USA GASOLINE- LEV3 E10 0.202 0.300 * 0.218 0.300 *			0.00 0.05											
0	RVR / FL	IEL (DNLY / C	ANISTER	BLEE	DEVAPO	DRATIVE	-			RDS AND				VELS	
								-	FUEL ONLY EVAP & CANISTER BLEED							
	ORATIVE MILY		ORVR (g/	ORVR (g/gallon) @ UL			FUEL TYPE		DHS RIG TEST (g/test) @ UL			2DHS RIG TES (g/test) @ UL		BLEED CANIS TEST (g/test) (
			EL TYPE											CERT		

GASOLINE-

LEV3 E10



HONDA MOTOR CO., LTD. Executive Order: A-023-0703

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD						
JHNXR0121VSA	JHNXR0121VSA-A00		0.02						

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GWWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven): PAIR: pulsed AIR: SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV; selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2018 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HONDA	ACCORD HYBRID	PC	2.0	CV1	JHNXR0121VSA	1	P