

HYUNDAI MOTOR COMPANY

Executive Order: A-254-0353-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	NFORM	ATION				
MODE		EST GROUP	VEHIC	VEHICLE CLASS(ES)				ATEGORY	FUEL TYPE		
2018	JE	IYXV02.01E3	PC					SINGLE FUEL HICLE	GASOLINE		
	USEFUL	LIFE (miles)	VEH	ICLE EMIS	SION C	ATEGO	ORY	INTERIM / INT	ERMEDIATE IN-USE STD		
EXH	/ORVR	EVAP		FTP SF1			•	FTP	SFTP		
15	0000	150000	LEV3	SULEV30	LEV	LEV 3 COMPOSIT		PM	PM		
SPE	CIAL FE	EATURES & EXI	HAUST EMISSION	ON CONTRO	DL		OBD S	TATUS	ENGINE DISPLACEMENT		
1	¥	WR-HO2S, HO2S	, WU-TWC, TW	C, SFI		FULL		*	•		
*			+			PARTIAL		+	2.0		
*			* .				AL WITH	ALL MODELS			
		EV	APORATIVE &	REFUELING	G (EVA	P/ORVI	R) FAMILY	INFORMATION			
EVA	P / ORV	R FAMILY	EVAPORATIVE	STD CATE	GORY	E		SSION STD E CLASS	SPECIAL FEATURES		
J	HYXR01	1301EG	LEV 3	OPTION2		PC			HCT		
			E	EMISSION C	REDIT	INFOR	MATION				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP						NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		Y		N		N			N .		
			NMOG	AND FLEE	TAVE	RAGE	NFORMA	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+NO PC+LDT			LDT	+NOX FLEET ST((3751 LVW-8500 R) + MDPV (g/mi)	NMOG+NOX FLEET ST MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	*		0.079			0.092	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



HYUNDAI MOTOR COMPANY

Executive Order: A-254-0353-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models has been determined to have seven deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$125 per vehicle for the third through seventh deficiencies for each vehicle in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2018 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

day of September 2018.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. This Executive Order hereby cancels and supersedes Executive Order A-254-0353 dated April 25, 2017.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this //

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



GASOLINE-

TIER3 E10

0.01

0.20

JHYXR01301EG

HYUNDAI MOTOR COMPANY

Executive Order: A-254-0353-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

0.020

0.006

ATTACHMENT

EVHALIST AND	EVADODATIVE	EMICCION CTANDA	DOC AND CE	ERTIFICATION LEVELS
EVUNOS I VIAI	EVAPORATIVE	EMISSION STANDA	KUS AND CE	EKTIFICATION LEVELS

	EXH	AUST	TAND	EVAI	POR	RATIVI	EMIS	SIONS	MATE	IDAR	DS AND	CERT	FIC	ATION	LEVEL	5	
		EXH	AUST E	MISSI	ON S	TANDA	ARDS AN	ND CERT	TIFIC A	TION	LEVELS	(FTP, HW	FET,	50°F, 20	°F)		
	FUI	EL TY	ad OI	onoxid justme RVR [g	e; No ent fa HC/	Ox: oxid octor; 20 /gallon o	es of nite DHS/3DH dispense	rogen; Ho IS [g HC/ d]: on-bo	CHO: /test]: ard re	formale 2/3 day	hydrocar dehyde; P ys diurnal- y vapor rec est proced	M: particu hot-soak covery; g:	late r ; RL [gram	matter; R. g HC/mi] ; mg: mil	AF: reacti : running ligram; m	ivity loss;	
					IMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCI (mg/		_		PM (g/mi)	
				CERT		STD	CERT	STE		CERT	STD	CER	Т	STD	CERT	STD	
FTP@5	950K *		*			*	*	*		*	*	*		*	*	*	
FTP@L	@UL GASOLINE- LEV3 E10		1 (.018	C	.030	0.3	1.0		*	*			4	0.001	0.003	
50°F @	A LC	V3 E	1 (.015	0	.060	0.3	1.0		*	*	*		8			
					FU	EL TYP	E				MOG+NO				CO (g/m		
				TOLETTIC						CERT		STD	STD			STD	
HWFET @ 50K				*					*	*							
HWFE	T@UL			GAS	OLI	NE-LEV	3 E10			0.	800	0.030					
20°F	@ 50K		GAS	OLINE	-co	гр со	TOM OC	TANE						1.4		10.0	
			SF	TP EX	CHAL			STANDA	ARDS	AND (CERTIFIC		VEL				
				US06						SC03			COMPOSITE				
	FUEL 1				NMOG+NOx (g/mi)		CO PN (g/mi) (mg/			NMOG+NOx (g/mi)		CO (g/mi)	NMOG+NOx (g/mi)		(g/mi)	PM (mg/mi	
@ 4K	@4K *		CERT	* *		*	*		*		*						
			STD		*		*			·	*	*					
		CE		* TS		*	* 2		*		*	0.016		1.5	*		
@ UL	UL GASOLI						* 10				0			0.097	4.2	*	
		BII								,			(0.030			
		WH	OLE VE	HICLE	EV						OS AND C		ATIO	N LEVEL	.S	•	
		_		1		W	HOLE VI	EHICLE	EVAP	ORAT	IVE TEST	ING			4-4-1		
	ORATIV MILY	F	FUEL TYPE		3DHS (g/test) @ UL				2DHS (g/test) @ UL				RL (g/mi) @ UL				
				CERT		RT S	STD FEL		CE	RT STD		FEL		CER	Т	STD	
JHYXR01301EG GASOLINE LEV3 E1			0 256 0			.300	300 * 0.:		194 0.300 *			0.03 0.05					
(DRVR / F	UEL	ONLY/	CANIS	TER	BLEEC	EVAPO	RATIVE	EMIS	SION	STANDA	RDS AND	CEF	RTIFICAT	ION LEV	ELS	
											NLY EVA						
	ORATIV MILY		ORVR (FUEL	TYPE		3DHS RIG TEST (g/test) @ UL			2DHS RIG 1 (g/test) @				
		FL	JEL TYP	E CE	RT	RT STD C			CE	RT	STD	CERT		STD	CERT	STD	

GASOLINE-

LEV3 E10



HYUNDAI MOTOR COMPANY

Executive Order: A-254-0353-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

EFFECTIV	E LEAK DIAMETER STANDA	RD AND CERTIFICATION LEV	/EL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
JHYXR01301EG	JHYKR01301EG-AD1	0.00	0.02

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; EÇS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR; pulsed AIR; SFI/MFI; sequential/multiport fuel injection; DFI/IFI; direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister, prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2018 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	ECS	OBD
HYUNDAI	ELANTRA	PC	2.0	SA6	JHYXR01301EG	1	\$
HYUNDAI	ELANTRA SE	PC	2.0	SA6	JHYXR01301EG	1	. \$