California Environmental Protection Agency

OB Air Resources Board

KIA MOTORS CORPORATION Executive Order: A-314-0270-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP II	NFORMAT	ION						
MODE	_	EST GI	ROUP	VEHI	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
2018	JK	. 6DA6		PC	PC DEDICA			CATED SINGLE FUEL VEHICLE			ASOLINE			
l	USEFUL	LIFE	(miles)	· VI	HICLE EMIS	SION	CATEGOR	Υ	IN	TERIM / INT	ERMEDIA	TE IN-USE STD		
EXH	/ORVR		EVAP		FTP		SFTP			FTP		SFTP		
15	0000		150000	LEV	3 ULEV125	LEV	3 COMPO	SITE		*		*		
SPE	CIAL FE	ATUR		IAUST EMISS	SION CONTRO	DL		OBD ST	TATL	JS	ENGINE	DISPLACEMENT (L)		
1	Γ	FI, W	R-HO2S,	HO2S, WU-	TWC, TWC		FUL	L		*				
*		1000,100		*	-		PART	IAL		*		1.6		
*				*			PARTIAI		ALI	L MODELS	DELS			
			EV	APORATIVE	& REFUELING	G (EVA	P/ORVR)	FAMILY	INF	ORMATION				
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GOR	Y EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES			
J	KMXR01	104BG	;	LEV	3 OPTION2		PC					HCT		
J	KMXR01	101AG	,	LEV	3 OPTION2		PC PC					HCT		
J	KMXR01	104AG	;	LEV	3 OPTION2	OPTION2 PC			C		•	HCT		
J	KMXR01	201A	;	LEV	3 OPTION2			P	C			HCT		
J	KMXR01	204B	;	LEV	3 OPTION2	OPTION2			PC			HCT		
					EMISSION C	REDI	TINFORM	ATION						
	A	LLOW	ANCE FO	R TEST GRO	UP		NMOG CREDIT FOR NMOG CI				REDIT FOR STD FOR W			
BASE	ELINE P	ZEV							DO	TRUCKS				
	* * *			*		1	4		N		N			
				NMC	G AND FLEE	TAVE	RAGE IN	FORMA	TION					
NMOG RAF	CH4 RAF	NMO	FTP G/NMHC ATIO	HCHO/NMH RATIO	PC+LD1			LDT (+NOX FLEET STD N (3751 LVW-8500 R) + MDPV (g/mi)		MDV	OG+NOX FLEET ST DV (10,001-14,000 GVWR) (g/mi)		
*	+		1.10	*		0.079			0	. 092		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

California Environmental Protection Agency

⊘ Air Resources Board

KIA MOTORS CORPORATION Executive Order: A-314-0270-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's NMOG+NOx and greenhouse gas Fleet Average (PC or LDT or MDPV) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

For evaporative families JKMXR01101AG, JKMXR01104AG, JKMXR01104BG, JKMXR01201AG, and JKMXR01204BG, the manufacturer has attested to compliance with the 0.02 inch effective leak diameter standard in 13 CCR Section 1976(b)(1)(G)6 ["Effective Leak Diameter Standard And Procedure"].

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models has been determined to have nine deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$175 per vehicle for the third through ninth deficiencies for each vehicle in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2018 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37500 per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby supersedes Executive Order A-314-0270 dated June 30, 2017.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 30 day of August 2017.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

KIA MOTORS CORPORATION

Executive Order: A-314-0270-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

OB Air Resources Board

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

/ = Y		NMOG+NOx (g/mi)				NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)			
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
FTP@50K	*	*	*	*	*	*	*	*	*	*	*		
FTP@UL	GASOLINE- TIER3 E10	0.040	0.125	0.8	2.1	*	*	*	4	*	0.01		
50°F @4K	GASOLINE- TIER3 E10	0.064	0.250	1.2	2.1	*	*	*	16		-		

I see To	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	. *			
HWFET @ UL	GASOLINE-TIER3 E10	0.029	0.125	- 1	1 - 1 - 1 - 1	
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)	1 1 1		1.6	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

I WELL		15	•	US06		SC03	3	COMPOSITE			
T.	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
@ 4K	*	CERT	*	*	3	*	*	4.			
		STD	*	*		*	*	- 1	1		
		CERT	*	*	*	*	*	0.042	1.8	* '	
@ UL	GASOLINE- TIER3 E10	STD	*	*	* .	*	*	0.097	4.2	*	
		BIN		- C	P() - V	778 35 352		0.130	}	7 kg ()	

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE \							
EVAPORATIVE FAMILY	FUEL TYPE	3DHS (g/test) @ UL			2DI	HS (g/test) @	UL	RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD	
JKMXR01101AG	GASOLINE- LEV3 E10	0.215	0.300	*	0.197	0.300	*	0.01	0.05	
JKMXR01104AG	GASOLINE- LEV3 E10	0.250	0.300	*	0.186	0.300	*	0.01	0.05	
JKMXR01104BG	GASOLINE- LEV3 E10	0.215	0.300	*	0.197	0.300	*	0.01	0.05	
JKMXR01201AG	GASOLINE- LEV3 E10	0.215	0.300	*	0.197	0.300	*	0.01	0.05	
JKMXR01204BG	GASOLINE- LEV3 E10	0.215	0.300	*	0.197	0.300	*	0.01	0.05	

KIA MOTORS CORPORATION Executive Order: A-314-0270-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

⊘ Air Resources Board

ORVR / FUI	ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
				FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K					
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD				
JKMXR01101AG	GASOLINE- TIER3 E10	0.02	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.005	0.020				
JKMXR01104AG	GASOLINE- TIER3 E10	0.02	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.002	0.020				
JKMXR01104BG	GASOLINE- TIER3 E10	0.02	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.005	0.020				
JKMXR01201AG	GASOLINE- TIER3 E10	0.02	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.005	0.020				
JKMXR01204BG	GASOLINE- TIER3 E10	0.02	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.005	0.020				

t not applicable: #: pounds: UL; useful life: PC; passenger car: LDT; light-duty truck; LDT1; LDT<6000#GVWR.0-3750#LVW; LDT2; LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; PZEV: partial ZEV; AT PZEV: advanced technology PZEV; TZEV: transitional ZEV: TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor: PMS: PM sensor: RDQS; reductant quality sensor; NH3S; ammonia sensor; EGR; exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol "15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semiautomatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission

2018 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD	PZEV TYPE
HYUNDAI	ACCENT	PC	1.6	M6,SA6	JKMXR01101AG	1	\$	*
HYUNDAI	ACCENT	PC	1.6	M6,SA6	JKMXR01201AG	1	\$	*
KIA	RIO	PC	1.6	M6,SA6	JKMXR01104BG	1	\$	*
KIA	RIO	PC	1.6	M6,SA6	JKMXR01204BG	1	\$	*
KIA	SOUL	PC	1.6	M6,SA6	JKMXR01104AG	1	\$	*