

Executive Order: A-002-0226

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GRO	OUP INFOR	MATION				
MODE		ST GROUP	VEHIC	LE CLASS(E	S)	FUEL C	ATEGORY	FUEL TYPE		
2019	KF	JXJ02.5BUY	L	DT1, PC	DEDICATED SINGLE FUEL GA.			GASOLINE		
1	USEFUL	LIFE (miles)	VEH	ICLE EMISS	ION CATE	GORY	INTERIM / INT	ERMEDIATE IN-USE STD		
EXH	/ORVR	EVAF	4	FTP	SF	TP	FTP	SFTP		
15	0000	15000	0 LEV3	SULEV30	LEV 3 CC	MPOSITE	. *	PM		
SPE	CIAL FE		KHAUST EMISSIONSTEMS	ON CONTRO	L	OBD ST	ATUS	ENGINE DISPLACEMENT		
1	TWC (2), WR-HO2	s, HO2S, DFI,	EGR, EGRC		FULL	ALL MODELS			
*			*		P	ARTIAL	*	2.0		
*			*			TIAL WITH	*			
		E	VAPORATIVE &	REFUELING	(EVAP/OR	VR) FAMILY	INFORMATION			
EVA	P / ORV	R FAMILY	EVAPORATIVE	E STD CATE	GORY	EVAP EMIS		SPECIAL FEATURES		
K	FJXR01	155AD	LEV 3 OPT	ON2 WITH	FEL	P	С	HCT		
K	FJXR01	545GE	LEV 3 OPT	ION2 WITH	FEL	LD	T1	HCT		
				EMISSION C	REDIT INFO	RMATION				
	EDIT FO	X FLEET AVE OR EXTENDED RRANTY	NMOG CH	REDIT FOR N		NMOG CF	REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N		N			N	N		
			NMOC	AND FLEE	T AVERAGE	INFORMAT	TON			
MOG RAF	CH4 RAF	FTP NMOG/NMH RATIO	C HCHO/NMHC RATIO	PC+LDT	X FLEET S (0-3750 LVV g/mi)	V) LDT (NOX FLEET STI 3751 LVW-8500 R) + MDPV (g/mi)	NMOG+NOX FLEET STE MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	0.008		0.072		0.083	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



Executive Order: A-002-0226 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-002-0226 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 3 of 4

ATTACHMENT

EX	HAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS
	FYHALIST EMISSION STANDARDS AND GERTIFICATION

	-XHAUST A	ND EVAP	ORATIV	E EMISS	SION ST	ANDARI	DS AND	CERTIFI	CATION	LEVEL	S
	EXHAU	STEMISSIC	N STAND	ARDS AND	O CERTIF	ICATION L	EVELS	(FTP, HWFE	T, 50°F, 2	0°F)	
FTP@50K FTP@UL	FUEL TYPE	CH4: met monoxide adjustmer ORVR [g	hane; NM(; NOx: oxiont factor; 2 HC/gallon	DG: non-CH des of nitro DHS/3DHS dispensed]	H4 organic gen; HCH [g HC/tes]: on-board	gas; HC: I O: formalde st]: 2/3 days	hydrocar ehyde; P s diurnal-	bon; NMHC: M: particulat +hot-soak; R covery; g: gra ure; SFTP: si	non-CH4 e matter; l L [g HC/m	HC; CO: care RAF: reacti	ivity
			G+NOx mi)		O mi)		Ox mi)		HO J/mi)		PM (mi)
The state of the s		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- LEV3 E10	0.0174	0.030	0.28	1.0	*	*	0.0	4	0.0003	0.003
50°F @4K	GASOLINE- LEV3 E10	0.0329	0.060	0.28	1.0	*	*	0.0	8		
			FUEL TYP	F		NN	IOG+NO	x (g/mi)		CO (g/mi)	A 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
			OLL III	_		CEF		STD	CER		STD
HWFET @	50K		*		10.00	*	1	*	100 37.6		of any the
HWFET @	UL	GASO	LINE-LEV	3 E10		0.00	041	0.030			
20°F @ 5	OK COLD	CO E10 RE	GULAR GA	ASOLINE	(TIER3)		100		0.8	1	10.0
		SFTP EXH	AUST EM	ISSION ST	ANDARD	S AND CE	RTIFICA	TION LEVE	IS		
				J\$06	Contract of		SC03			MPOSITE	4-1

	the state of the state of	SF	TP EXHAUST E	MISSION S	STANDARDS	AND CERTIFIC	ATION L	EVELS		1000
				Section 1	SC03		COMPOSITE			
	FUEL TYPE	224	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT		*		*	*			
		STD	*	*		*	*		СО	
		CERT	*	*	0.7	*	*	0.0176	1.11	*
@ UL	GASOLINE- LEV3 E10	STD	16	*	6	*-,	*	0.090	4.2	*
		BIN		and the second				0.050	314	

EVAPORATIVE FAMILY	WHOLE VEHIC		WHOLE						
	FUEL TYPE	3DHS (g/test) @ UL			2DI	HS (g/test)	RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
KFJXR01155AD	GASOLINE- LEV3 E10	0.2532	0.300	0.300	0.1852	0.300	0.300	0.000	0.05
KFJXR01545GE	GASOLINE- LEV3 E10	0.2412	0.300	0.300	0.2202	0.300	0.300	0.000	0.05



Executive Order: A-002-0226

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

ORVR/FUE	LONLITOA	HOTEK		EVAPORATIVE	FUEL C	NLY EVA	P & CANIS	TER BLEE				
EVAPORATIVE	ORVR (g/g	jallon) @	UL	POS AGA	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CA	ANISTER est) @ 4K		
FAMILY	TVDE	CERT	STD	FUEL TYPE	CERT	THE RESERVE THE PARTY OF THE PA		STD	CERT	STD		
	FUEL TYPE	CERT	310	GASOLINE-	2 1 1 2 2 2 1 1 1 1			*	0.0136	0.020		
KFJXR01545GE	GASOLINE- TIER3 E10	0.005	0.20	LEV3 E10	* * * * * * * * * * * * * * * * * * * *	10 to *. 0 L	1 2 2					
KFJXR01155AD	GASOLINE-	0.009	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.0148	0.020		
	EFFECTIVE	LEAK D	IAMET	ER STANDAF	ED AND CE	ERTIFICA	TION LEV	EL (INC	HE3)	20170		
		TO THE PROPERTY	KFAMII			RT	1 (1) op	A	STD			
EVAPORATIVE FAMILY		1				•			0.02			
KFJXR011	55AD	KFJXR0	1155AD	0-5AD					0.02			
KFJXR015	45GE	KFJXRO	1545GE	-5GE		*		0 . 02 :5000#GVWR.0-3750#LVW; LDT2				

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT; other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	ECS	ОВ
WAKE		E. C. H. SAR STA	2.0	CV1,M6,SCV7	FAMILY ECS KFJXR01545GE 1 KFJXR01155AD 1 KFJXR01155AD 1	1	F
SUBARU	CROSSTREK	LDT1		CV1,M5,SCV7		1	F
SUBARU	IMPREZA 4-DOOR	PC	2.0	CVI,MS,SCV7	The second by the second second second		
SUBARU	IMPREZA 4-DOOR	PC	2.0	M5,SCV7	KFJXR01155AD	1	F
SOBARO	SPORT		2.0	CV1,M5,SCV7	KFJXR01155AD	1 1 1	F
SUBARU	IMPREZA 5-DOOR	PC	2.0	CV1,113/5011			DEEK A
SUBARU	IMPREZA 5-DOOR SPORT	PC	2.0	M5,SCV7	KFJXR01155AD	1	F