

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FOR	MATION					
MODE	- I TP	ST GROUP		VEHIC	VEHICLE CLASS(ES)				ATEGORY		FUEL TYPE		
2019	KG	MXT05.3384		LDT4 DED				SINGLE FUEI HICLE	·	GASOLINE			
USEFUL LIFE (miles) VEHICLE EMIS						E EMISSION CATEGORY			INTERIM / IN	ERIM / INTERMEDIATE IN-USE S			
EXH	/ORVR	EVAP		FTP		SF	ТР	FTP		SFTP			
150000 150000 LEV3 ULEV125					ULEV125	LEV	3 C(OMPOSITE	*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS			ENGINE DISPLACEMENT		
1 DFI, 2TWC, 2H02S(2), TWC								FULL ALL MODELS					
*	*						F	ARTIAL	*		5.3		
*	*						PAF	TIAL WITH	*				
		E	VAP	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y INFORMATIO	N			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	r	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
K	GMXR01	6150 A		LEV 3	OPTION2			L	DT4		HCT		
K	GMXR02	1250B	I	LEV 3 OPTI	ION2 WITH	FEL		LDT4			HCT		
				l	EMISSION C	REDI	T INF	ORMATION					
	EDIT FO	X FLEET AVE R EXTENDED RANTY	· I		EDIT FOR N ZERO-EVAP	_	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N				N	N			
				NMOG	AND FLEE	r ave	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMH RATIO	с но	CHO/NMHC RATIO	NMOG+NO PC+LDT (N) LDT	NMOG+NOX FLEET STD LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		MDV (10,001-14,000		
*	*	1.10		*	0	.072			0.083		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of May 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



FUEL TYPE

GENERAL MOTORS LLC.

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

1															
						CO (g/mi)		-				- 1			
			CERT	STI	D CEF	RT ST	D	CERT	STD	CER	т	STD	CEF	RT	STD
ok	*		*	*	*	*		*	*	*		*	*		*
			0.031	0.1	25 0.	5 2.	1	*	*	*		4	0.002		0.003
4K	*		*	*	*	*		*	*	*		*			
				euer :	TVDE			N	MOG+N	Dx (g/mi)			CO (g	J/mi)	
				FUEL				CI	ERT	STD		CERT	•		STD
HWFET @ 50K				*	·				*	*					
T @ UL			GAS	OLINE-1	TIER3 E1	0		0.	004	0.125	,				
@ 50K	co	DLD CO	E10 1	REGULA	R GASOLI	NE (TIE	R3)					1.5		t	.2.5
		S	FTP E)	HAUST	EMISSIO	N STAND	ARDS	AND C	ERTIFIC	ATION L	EVEL	.S			
	US06						ļ				COMPOSITE				
FUEL TYPE			NMOG+NOx			· · ·		NMOG+NOx		со			1 -	-	PM
			(9	g/mi)	(g/mi) (mg	g/mi)	(g	/mi)	(g/mi)		(g/mi)	(g/	mi)	(mg/mi)
*	* CERT STD			*	*				*	*					
				*	*				*	*					
	CERT			*	*		1		*	*		0.027	0	. 4	*
			* 0		*	*			*	*		0.090	4	. 2	*
											0.120				1
	WH	OLE VI	EHICLE	EVAPO	ORATIVE I	EMISSIO		NDARD	S AND C	ERTIFIC	ATIO	N LEVEL	S		<u> </u>
					WHOLE	VEHICLE	EVAP	ORATI	VE TEST	ING					
	VE FUEL TYPE			3DHS (g/test) @ UL				2DH	2DHS (g/test) @ UL			RL (g/mi) @ UL		UL	
			ľ	CERT	STD	FEL	CE	RT	STD	FEL	_	CERT			STD
0161502	A I			0.383	0.500	*	0.3	376	0.500	*		0.00		(0.05
021250	2 1 -			0.470	0.500	0.525	0.3	354	0.500	0.52	25	0.00)	(0.05
	GAS TIE 4K 7 @ 50K 7 @ UL @ 50K FUEL T * GASOLI TIER3 ORATIVE MILY	GASOLINE- TIER3 E10 FUEL TYPE * GASOLINE- TIER3 E10 WH ORATIVE MILY 016150A G G 021250B G	GASOLINE- TIER3 E10 4K * 7 @ 50K T @ UL @ 50K COLD CO S FUEL TYPE * CERT STD CERT STD CERT STD BIN WHOLE VI ORATIVE MILY FUEL TY FUEL TY E STD BIN WHOLE VI ORATIVE MILY 016150A GASOLIN TIER3 CASOLIN	Image: Cert of the second state of the second sta	(g/mi) CERT STI OK * * * OK TER3 E10 0.031 0.12 4K * * * TIER3 E10 0.031 0.12 4K * * * FUEL FUEL * 7 @ 50K * * T @ UL GASOLINE-1 * @ 50K COLD CO E10 REGULAR * FUEL TYPE NMOG+NOX (g/mi) * FUEL TYPE NMOG+NOX (g/mi) * * CERT * GASOLINE- TIER3 E10 STD * ORATIVE MILY FUEL TYPE 3DH ORATIVE MILY FUEL TYPE 3DH 016150A GASOLINE- TIER3 E10 0.383 021250B GASOLINE- TIER3 E10 0.470	CERT STD CERT OK * * * * GASOLINE- TIER3 E10 0.031 0.125 0.1 4K * * * * FUEL TYPE FUEL TYPE * * 7 @ 0L GASOLINE-TIER3 E1 @ * 0 50K * * * 7 @ UL GASOLINE-TIER3 E1 @ * 0 50K COLD CO E10 REGULAR GASOLINE GASOLINE US06 FUEL TYPE VNOG+NOX CO (g/mi) (g/mi) FUEL TYPE STD * * * GASOLINE- TIER3 E10 STD * * * GASOLINE- TIER3 E10 STD * * * WHOLE VEHICLE EVAPORATIVE FUEL TYPE SDHS (g/test) (g/t	(g/mi) (g/mi) CERT STD CERT ST OK * * * * * IL GASOLINE- TIER3 E10 0.031 0.125 0.5 2. 4K * * * * * * 4K * * * * * * 4K * * * * * * * 7 UL GASOLINE-TIER3 E10 CERT * * * * * FUEL TYPE STD * * * * * * GASOLINE- TIER3 E10 STD * * * * * * <	(g/mi) (g/mi) CERT STD CERT STD OK * * * * * OK * * * * * * OK * * * * * * * OK * * * * * * * * GASOLINE- TIER3 E10 0.031 0.125 0.5 2.1 * * FUEL TYPE FUEL TYPE FUEL TYPE * * * * FUEL TYPE COLD CO E10 REGULAR GASOLINE (TIER3) SFTP EXHAUST EMISSION STANDARDS * * FUEL TYPE NMOG+NOX CO PM (g/mi) (mg/mi) full * CERT * * * * GASOLINE- TIER3 E10 STD * * 6 * * GASOLINE- TIER3 E10 STD * * 6 * * 6	(g/mi) (g/mi) (g/mi) (g DK * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *	(g/mi) (g/mi) (g/mi) OK * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * *	(g/mi) (g/mi)<	(g/mi) (g/mi) (g/mi) (g/mi) (mg/riphi) OK * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * * <t< td=""><td>Image: constraint of the state of</td><td>Image: constraint of the second sec</td><td>Image: constraint of the state of</td></t<>	Image: constraint of the state of	Image: constraint of the second sec	Image: constraint of the state of

AR	CALIF		VIA		MOTORS .C.	1		nger Cars,	der: A-006-2 Light-Duty Medium-Du Pa	Trucks and			
ORVR / FU	EL ONLY / C/	NISTER	BLEED	EVAPORATIVE	EMISSION	STANDA	RDS AND	CERTIFIC	ATION LEV	ELS			
				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTE TEST (g/test) @ 4				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
KGMXR016150A	E10-EPA	0.01	0.20	GASOLINE- TIER3 E10	*	*	*	*	0.007	0.020			
KGMXR021250B	E10-EPA	0.03	0.20	GASOLINE- TIER3 E10	*	*	*	*	0.010	0.020			
I	EFFECTIVE	LEAK D	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INCH	IES)				
EVAPORATIVE FAMILY LEAK FAMIL			Y CERT				STD						
KGMXR016150A KGMXR01615			16150A	-LK1		0.02							
KGMXR0212	50B	KGMXRO	21250B	-LK1 *				0.02					
not applicable; # DT<6000#GVWR 500#ALVW; MDV uty passenger ve mission limit; GW ILEV: ultra LEV; S DSTWC: adsorbi CRC/SCR-N or S ontinuous/periodi eated/oxygen ser DQS: reductant of econdary air inject irect/indirect fuel in nes on-board diag uffix: series; CNG	8,3751-5750#I /: medium-dut hicle; HDV: he WR: gross vel SULEV: super ng TWC; HAC GCRC-NH3: se c trap oxidizer nsor; WR-HO2 quality sensor; tion (belt drive injection; TC/S gnostic; DOR:	LVW; LD y vehicle eavy-duty nicle weig ULEV; Z C: HC ads elective c c; DPF: di S or AFS NH3S: a en)/(elect SC: turbo direct oz	T3: LDT (MDV4: vehicle; ht rating EV: zero orbing ca atalytic re esel part wide ra mmonia ric driver /super ch one redu	5001-8500#GV MDV 8501-1000 ECS: emission ; LVW: loaded v -emission vehicl atalyst; WU: wal eduction-urea/ar iculate filter (act ange/linear/heate sensor; EGR: e a); PAIR: pulsed barger; CAC: cha	VR,3751-579 00#GVWR; M control syste ehicle weigh e; TZEV: tra m-up cataly: nmonia; NH ive); GPF: P ed air-fuel ra xhaust gas r AIR; SFI/MF arge air cool	50#ALVW; MDV5: MD em; CERT: ansitional Z st; NAC: N 30C: amm M filter for tio sensor; recirculatio FI: sequent er; FFH: fu	LDT4: LDT V 10001-14 certification adjusted LV EV; TWC/C Ox adsorpt onia oxidat spark-ignite NOXS: NC n; EGRC: E tial/multipor el fired hea	6001-850 0000#GVW n; STD: sta W; LEV: lo C: 3-way/ ion catalys ion catalys ed engine; X sensor; GR coole t fuel injec tter; F/P(\$:	0#GVWR,5 /R; MDPV: r andard; FEL ow emission oxidizing ca st; SCR-U or st; CTOX/PT HO2S/O2S PMS: PM so r; AIR/AIRE: tion; DFI/IFI full/partial/p	751- medium- .: family vehicle; talyst; TOX: : ensor;			

2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CHEVROLET	C15 SILVERADO LD 2WD	LDT4	5.3	A6	KGMXR016150A	1	F
CHEVROLET	C1500 SUBURBAN 2WD	LDT4	5.3	A6	KGMXR021250B	1	F
CHEVROLET	C1500 TAHOE 2WD	LDT4	5.3	A6	KGMXR016150A	1	F
CHEVROLET	K15 SILVERADO LD 4WD	LDT4	5.3	A6	KGMXR016150A	1	F
CHEVROLET	K1500 SUBURBAN 4WD	LDT4	5.3	A6	KGMXR021250B	1	F
CHEVROLET	K1500 TAHOE 4WD	LDT4	5.3	A6	KGMXR016150A	1	F
GMC	C15 SIERRA LTD 2WD	LDT4	5.3	A6	KGMXR016150A	1	F
GMC	C1500 YUKON 2WD	LDT4	5.3	A6	KGMXR016150A	1	F
GMC	C1500 YUKON XL 2WD	LDT4	5.3	A6	KGMXR021250B	1	F
GMC	K15 SIERRA LTD 4WD	LDT4	5.3	A6	KGMXR016150A	1	F
GMC	K1500 YUKON 4WD	LDT4	5.3	A6	KGMXR016150A	1	F



2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
GMC	K1500 YUKON XL 4WD	LDT4	5.3	A 6	KGMXR021250B	1	F

.