

Executive Order: A-003-0636

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 5

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMAT	TION					
MODE		EST GROUP	CLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
2019	K	MBXD03.0HD2	MI	MDV4, MDV5			DICATED SINGLE FUEL VEHICLE			DIESEL		
	USEFU	L LIFE (miles)	VE	HICLE EMISS	SION C	ATEGOR	RY	INTERIM / INT	ERMI	EDIATE IN-USE STD		
EXH/ORVR EVAP				FTP				FTP		SFTP		
150000 *		LEV3						PM NMHC+NOX AND PM				
SPE	CIAL F	EATURES & EXI	AUST EMISSI	ON CONTRO	DL		OBD S	TATUS	ENG	GINE DISPLACEMENT (L)		
DFI, TC, CAC, EGR, EGRC, OC+DPF, SCRC, NOXS(2), WR-HO2S, PMS, RDQS							FULL +					
*							PARTIAL			3.0		
* *						PARTIAL WITH ALL MODELS						
		. EV	APORATIVE &	REFUELING	G (EVA	P/ORVR)	FAMILY	INFORMATION				
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR					GORY	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	*			*				•		*		
				EMISSION C	REDIT	INFORM	IATION	······································				
CREDITEOR EXTENDED					EDIT FOR NON-PZEV ERO-EVAP			REDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS		
и						N				N		
			NMO	AND FLEE	T AVE	RAGE IN	FORMAT	rion '				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	LDT (3751 L	OX FLE VW-85 PV (g/r	00 GVW)	NMOG- MDV (8	NMOG+NOX FLEET STE MDV (8501-10000 GVWR (g/mi)		MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	*	0.018	0.083			*			#		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-003-0636

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 5

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models have been determined to have eight deficiencies. These vehicle models are approved subject to the manufacturer paying a fine of \$200 per vehicle for the third through eighth deficiencies for vehicles in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2019 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED:

Per Daimler AG's request for conditional OBD II approval and conditional Executive Order (EO) approval (Daimler AG's Request) dated September 12, 2018, the listed vehicle models are certified conditionally on Daimler AG's completion of OBD II and durability testing and submission of test results to CARB no later than December 7, 2018, and final review of Daimler AG's complete and revised AECD document. Failure to submit the required data by the agreed upon dates, or failure of the submitted data to demonstrate compliance with the emission standards and OBD II requirements, shall be cause for the Executive Officer to revoke the conditional EO ab initio; vehicles sold or introduced into commerce under the revoked conditional EO shall be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED:

The fuel-fired heater incorporated in the listed vehicle models must not operate at ambient temperature above 40 °F (13 CCR Section 1961.2(a)(13) [Emission Standard for a Fuel-Fired Heater]).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.



Executive Order: A-003-0636

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 5

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of September 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-003-0636

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 5

							A	TTAC	HI	ENT							
	EXH	AUS	TAND	EVAP	ORA	TIVE	EMIS	SION	STA	NDAR	DS ANI	CERT	IFIC	ATION	LEV	ELS	•
		EXH	AUST E	MISSIO	N STA	NDA	RDS A	ND CER	TIFIC	ATION	LEVELS	(FTP, HV	/FET,	50°F, 2	O°F)		
	FU	FUEL TYPE		onoxide djustmer RVR [g	; NOx: nt facto HC/ga	oxide or; 2D llon di	es of nit HS/3DH ispense	rogen; H HS [g HC ed]: on-be	ICHO [/test] oard r	: formald : 2/3 day refueling	lehyde; P s diurnal vapor re	bon; NMh M: particu +hot-soak covery; g: ure; SFTF	ulate i ; RL gram	matter; fig HC/m i; mg: m	RAF: re i]: runr illigran	eactive ning lon; mi:	vity oss;
,				NMHC+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCH (mg/r				PM (g/mi)		
				CERT STD		D	CERT STD		D	CERT	STD	CERT		STD CE		RT	STD
TP@5	TP@50K			*	*	-	*	*		*		*		*	*		*
FTP@l	_	ESEL-	EPA C	.1506	0.2	30	0.08	4.	2	*	*	0.0		6 0.005		052	0.010
50°F @		*		*	*		*			*	*	**		*			
		T								NMHC+NOx (g/mi)				CO (g/mi)			
					FUEL	TYPE					RT	STD		CER			STD
HWFET @ 50K								-	*		*						
HWFET @ UL				DIESEL-EPA						0.0	0.0227 0.23		,				
20°F @ 50K *						t								*			*
-			SI	FTP EX	AUST	EMI	SSION	STAND	ARDS	AND C	ERTIFIC	ATION LE	VEL	S			
		US06								SC03				COMPOSITE			
	FUEL	UEL TYPE		NMHC+NOx (g/mi)			CO PM (g/mi) (mg/mi)			NMHC+NOx (g/mi)		CO (g/mi)			Ox CO (g/mi)		PM (mg/mi
@ 4K			CERT		*		1.00			*		*	• 7		,		
W 41.		STI			*		*					*		1. 11-			1
		CEF			k		*	*			*	*	* 0.070		0.06		5.0
@ UL	DIESE	ESEL-EPA ST			t		*	1	*		*	* 0.3		.350	4.0		7
			BIN		111				-		1	11 341		•			
		WH	OLE VE	HICLE	EVAP	ORA1	IVE EN	MISSION	STA	NDARD	S AND C	ERTIFIC	ATIO	N LEVE	LS		
						WH	OLE V	EHICLE	EVA	PORATI	VE TEST	ING					
EVAPORATIVE FUEL		UEL TY	PE	3DHS (g/test) @			UL	JL .		2DHS (g/test) @			RL (g/mi)		ıi) @	@ UL	
					CERT STD		TD	FEL C		CERT STD		FEL		CERT		STD	
*		*		* *		*	*		*	*	*		* *			*	
(ORVR/I	FUEL	ONLY /	CANIST	ER BL	EED	EVAPO	PRATIVE	EMI	SSION S	STANDA	RDS AND	CER	RTIFICA	TION	EVE	LS
												P & CANI					
EVAPORATIVE FAMILY		/E	ORVR (g/gallor	ilon) @ UL		FUEL TYPE			3DHS RIG TEST (g/test) @ UL		2DHS RIG (g/test) @				D CANISTER (g/test) @ 4K	
		FUEL T		YPE CERT S		TD				ERT	STD	CERT		STD		T	STD
*			*	*	* *		*			* *		*	*		*		*
		EFF	ECTIV	E LEA	DIA	MET	ER ST	ANDAR	D A	ND CER	TIFICA	TION LE	VEL	(INCH	ES)		
EVAF	PORATI	VE FA	MILY	L	EAK F	AMIL	Υ.Υ			CER	Т				STD		
*				*					*				*				



Executive Order: A-003-0636

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 5 of 5

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer: DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	OBD
FREIGHTLINER	SPRINTER 3500 XD	MDV5	3.0	A7	*	1	\$
FREIGHTLINER	SPRINTER 4500	MDV4	3.0	A7	*	1	\$
FREIGHTLINER	SPRINTER 4500	MDV5	3.0	A7	*	1	\$
MERCEDES-BENZ	SPRINTER 3500 XD	MDV5	3.0	A7	*	1	\$
MERCEDES-BENZ	SPRINTER 4500	MDV5	3.0	A7	*	1	\$