(A)	CALIFORNIA AIR RESOURCES BOARD	
ATT	ALL DESCURCES BOARD	
an iin	AIR RESOURCES BOARD	

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GRO		FOR	NOITAN				
MODE		EST GROUP	VEHIC	LE CLASS(E	S)		FUEL C	ATEGORY	FUEL TYPE		
2019	KF	JXV02.5JHZ		PC DEDICATED SINGLE FUEL GAS							
	USEFUL	LIFE (miles)	VEH	ICLE EMISS	ION C	ATEC	ERMEDIATE IN-USE STD				
EXH	EXH/ORVR EVAP FTP						ГР	FTP	SFTP		
15	150000 150000 LEV3 LEV160 LEV 3 COL							PM	PM		
SPE	CIAL FE		HAUST EMISSIO	ON CONTRO	L		OBD S	TATUS	ENGINE DISPLACEMENT (L)		
1	TWC (2)	, WR-HO2S,	HO2S, TC, CA	C, SFI, AI	IR	10.50	FULL	ALL MODELS	and the second		
*			*			P	PARTIAL *		2.5		
*			*				TIAL WITH FINES	*			
		E	APORATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	INFORMATION	1200		
EVA	P / ORV	R FAMILY	EVAPORATIVE	E STD CATE	GORY	,		SSION STD E CLASS	SPECIAL FEATURES		
F	KFJXR01	303BC	L	EV 2			P	PC S	*		
				EMISSION C	REDIT	INFC	RMATION				
	EDIT FC	X FLEET AVE. OR EXTENDED RANTY		EDIT FOR NZERO-EVAP		ZEV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							N	N		
			NMOC	AND FLEE	T AVE	RAGE	INFORMA	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+NO PC+LDT (			/) LDT	+NOX FLEET ST (3751 LVW-8500 R) + MDPV (g/mi			
*	*	1.10	0.001	C	0.072			0.083	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## **BE IT FURTHER RESOLVED:**

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of April 2018.

TA

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

$\frown$							
A)	~ ^	11	F(		NS	11	Λ
A	JA		1		11	1 1	A
IINA	AIR R	ESC	UR	CES	5 8	OA	RD

STD

\*

SUBARU CORPORATION Executive Order: A-002-0228 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

A	T	Т	Α	С	Н	Ν	Λ	Е	N	Т

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon<br/>monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity<br/>adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss;<br/>ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K:<br/>1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

					s+NOx mi)		CO /mi)	NO: (g/m			HCHO (mg/mi)	P (g/	M mi)
				CERT	STD	CERT	STD	CERT	STD	CER	T STD	CERT	STD
FTP@50	ж	*	100	*	*	*	*	*	*	*	*	*	*
FTP@U	IL LE	SOLIN V3 E: PREM		0.1227	0.160	1.77	4.2	*	*	1.1	. 4	0.0002	0.003
50°F @4	K LE	SOLIN V3 E: PREM		0.1083	0.320	1.24	4.2	*	*	0.0	30		
	a lak	1.000	121	A. R. S. M.	FUEL TYP			NMC	OG+N	Ox (g/mi)		CO (g/mi)	
				1.	FUELIT			CER	Т	STD	CER	г	STD
HWFET	@ 50K	η.			*			*		*			
HWFE	T@UL			GASOLIN	E-LEV3	E10 PREM	1.	0.062	22	0.160	)		
20°F (	@ 50K	cc	DLD CC	E10 PF	EMIUM G	ASOLINE	(TIER3)	dillor Right	1960		4.10	)	10.0
4			S	FTP EXH	AUSTEN	AISSION S	TANDARDS	AND CEP	RTIFIC	ATION L	EVELS		100
		-	75000		- Seathards	US06	and the second second	-	SC03		co	MPOSITE	· ····································
	FUEL 1	YPE	16,0	1	G+NOx mi)	CO (g/mi)	PM (mg/mi)	NMOG+ (g/m		CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*		CERT			*	A for	*	5.7	*			115
0						and the second se							

		CERT	*	*	1	. 3	*	*	0.1126	1.74	*
@ UL	GASOLINI LEV3 E1 PREM		*	*		6	*	*	0.090	4.2	*
		BIN		10 18 300	and Albert	And the second			0.150	1017-1469	
5.4		WHOLE VEH	CLE EVAPO	ORATIVE I	EMISSION	STANDA	RDS AND	CERTIFICA	TION LEVELS	S	
		-		WHOLE	VEHICLE	EVAPORA	TIVE TES	TING			
EVAPORATIVE FAMILY F		FUEL TYP	E 3DH	S (g/test)	@ UL	2D	HS (g/test	t) @ UL	RL	(g/mi) @ L	JL
			CERT	STD	FEL	CERT	STD	FEL	CERT	S	TD
KFJXF	R01303BC	GASOLINE CA PHASE	10 2951	0.50	*	0.292	0.65	*	0.000	0 0	.05

\*

NE UN	SUBARU New Passenger Cars, Light-Duty Medium-D						Medium-Dut Pa	Frucks and by Vehicles lige 4 of 4			
ORVR / FU	JEL ONLY / CA	NISTER	BLEED	EVAPORATIVE	EMISSION	STANDA	RDS AND	CERTIFIC	ATION LEV	ELS	
EVAPORATIVE	ORVR (g/	gallon) (	DL		3DHS R	GTEST		IG TEST	BLEED CANISTE		
FAMILY		CERT	STD	FUEL TYPE	(g/test) CERT	STD	CERT	est) @ UL TEST (g/test) @ STD CERT ST * * * EVEL (INCHES) STD	STD		
KFJXR01303BC	FUEL TYPE GASOLINE - TIER 2 UNLEADED		0.20	*	*	*	*		*	*	
	EFFECTIVE	LEAK D	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INCH	HES)		
EVAPORATIVE	FAMILY	LEA	K FAMIL								
*			*	1000	*			*			
uty passenger v mission limit; GV JLEV: ultra LEV; JDSTWC: adsort CRC/SCR-N or ontinuous/period	ehicle; HDV: h /WR: gross vel SULEV: super bing TWC; HAC SCRC-NH3: se dic trap oxidize ensor; WR-HO2	eavy-duty hicle weig ULEV; Z C: HC ads elective c r; DPF: d 2S or AFS	y vehicle; ght rating EV: zerc sorbing c atalytic r iesel par S: wide r	MDV 8501-1000 ; ECS: emission ; LVW: loaded v eatalyst; WU: war eduction-urea/ar ticulate filter (act ange/linear/heate sensor; EGR: e	control syst ehicle weigł e; TZEV: tra m-up cataly nmonia; NH ive); GPF: F ed air-fuel ra	em, CERT ansitional Z vst; NAC: N I3OC: amm PM filter for atio sensor	adjusted L\ ZEV; TWC/ IOx adsorp nonia oxida spark-ignit; NOXS: No	W; LEV: I CC: 3-way tion cataly tion cataly ed engine Dx sensor;	ow emission /oxidizing ca st; SCR-U o st; CTOX/PT ; HO2S/O2S PMS: PM s	vehicle; atalyst; r	

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
SUBARU	WRX STI	PC	2.5	M6	KFJXR01303BC	1	F