

FCA US LLC.

Executive Order A-009-1413

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2, and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

		•				TEST GRO	UP II	NFOR	MATION						
MOD YEA		TES	ST GROUP	VEHIC	CLE CLASS(ES)			FUEL C	ATEGORY	FUEL TYPE					
201	9 1	KÇRI	XT03:05PV		LDT4 DED				SINGLE FUEI HICLE	٤	DIESĒL				
	USEF	UL L	IFE (miles)	•	VE	IICLE EMISS	LE EMISSION CATEGORY			INTERIM / IN	NTE	RMEDIATE IN-USE STD			
EXH/ORVR EVAP					FTP SF			SF	TP FTP			SFTP			
120000 *					LE	V2 LEV LEV 2 SF STANDAR				*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							L	·	OBD S	TATUS		ENGINE DISPLACEMENT (L)			
CAC, DFI, DPF, EGRC, NOXS(2), OC, PMS, RDQS, SCRC, TC, WR-HO2S, EGR									FÜLL	*					
*	* *								ARTIAL	nk:		3.0			
*	* *								RTIAL WITH ALL MODELS						
			ΕV	APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMILY	/ INFORMATIO	N				
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR										SSION STD E CLASS		SPECIAL FEATURES			
* *						*				*.		*			
			·		·	EMISSION CI	REDIT	INFO	RMATION						
						EDIT FOR NON-PZEV			NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
N N								N.				N			
					NMOG	AND FLEET	AVE	RAGE	INFORMA	TION					
NMOG RAF	RAF NMOGINMHC RATIO PC+LDT (0							/) LDT	+NOX FLEET S (3751 LVW-850 R) + MDPV (g/n	0	D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	-	*		*	0	.072		0.083			*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



FCA US LLC.

Executive Order: A-009-1413

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models have been determined to have twelve (12) deficiencies. These vehicle models are approved subject to the manufacturer paying a fine of \$425 per vehicle for the third through twelfth deficiencies for vehicles in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2019 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

 \searrow

Allen Lyons, Unier

ZEmissions Compliance, Automotive Regulations and Science Division



FCA US LLC.

Executive Order: A-009-1413

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

								Α	TTA	CHM	IENT									
	EXI	HAU	ST A	ND	EVAP	ORA	TIVE	EMIS	SSION	STA	NDAR	S ANI	CER	TIFIC	CATION	LEV	ELS	i		
		E	(HAU	ST E	MISSIC	N ST	ANDA	RDS A	ND CE	RTIFIC	ATION L	EVELS	(FTP, F	WFET	, 50°F, 20	0°F)				
	F	FUEL TYPE		adj OF	CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP															
					NMHC (g/mi)			CO (g/mi)			N (g/		HCH (mg/n			P M (g/mi)				
	66				CERT STD		TD	CER	T S	TD	CERT STD		CE	RT	STD	CE	RT	STD		
FTP@50K DIES		IESEI	SEL-EPA		.0306	0.	075	0.31	L 3	. 4	0.029	0.05	05 *		15			*		
FTP@	JL D	IESEI	SEL-EPA 0		.0439	0.	090	0.44	1 4	.2	0.032	0.07		*	18	0.001		0.01		
50°F @	4K	*	*		*		*	*		*	*	. *	*		*	7/2/2/20		ally terror		
	1500					enei	TVD	-				NOx (g/mi)			CO (g/mi)			
						FUEL TYPE					CE	CERT		D	CER	T		STD		
HWFET @ 50K		K	DIESEL					EPA			0.0	0.007		7			atterned.			
HWFET @ UL		L		DIESEL-EF					PA			010	0.0	9	17.12.5					
20°F @ 50K				*						one eas		erte d'a respectable		*			*			
				SF	TP EX	HAUS	TEM	ISSION	STAN	DARDS	AND C	ERTIFIC	ATION	LEVE	LS					
15.5			18	57			ι	JS06				SC03		T	CC	MPO	SITE			
	FUEL	- TYP	E.	NI		(g/mi)		CO (g/mi)		PM ig/mi)		NMHC+NOx (g/mi)		NN	/IHC+NO> (g/mi)		CO /mi)	PM (mg/mi)		
@ 4K	D 4K DIESE		SEL-EPA CER		T 0.058			0.02			0.0	018	0.03				7.5			
•				STD	0.60			11.8	100	Tay (h	0.	44	4.0			9 8	Y	13-4		
		CEI		ERT		*		*		*		*		(0.0519		*	*		
@ UL	DIES	ESEL-EPA		STD		*		*		*	*		*		0.090		*	*		
			BIN								- Delating Co			3	0.140	104.7		E SZ vi		
		٧	VHOL	E VE	HICLE	EVA	PORA	TIVE E	MISSIC	N STA	NDARD	SANDO	ERTIF	CATIC	N LEVE	_S				
							WH	IOLE V	/EHICL	E EVAI	PORATI	/E TEST	ING			10 10 10				
EVAPORATIVE FAMILY		IVE	VE FUEL T		TYPE 3		3DHS (g/tes		UL		2DHS	(g/test)	@ UL		R	L (g/n	ni) @	UL		
					CERT		s	STD FEL		CE	RT	STD	FEL		CERT		STD			
	*			*	* *			*	*	* ,		*	* .		*	*		*		
(ORVR	FUE	L ON	LY/C	CANIST	ER B	LEED	EVAP	ORATI	/E EMI	SSION S	TANDA	RDS A	ND CE	RTIFICA	TION	LEVE	LS		
-		1411234214													R BLEE					
EVAPORATIVE FAMILY		1023 Vacan	ORVR (g		g/gallon) @ UL		FUEL TYPE				HS RIG TEST g/test) @ UL		S RIG test) @				ANISTER st) @ 4K			
		FUEL		TYP	YPE CERT		STD	301 0.3040/550		5-3	RT STD		CER	Т	STD		RT	STD		
	*			*	*		*		*		*	* *			*	*		*		
		Е	FFEC	CTIVE	LEA	K DIA	MET	ER ST	ANDA	RD AI	ND CER	TIFICA	TION	EVE	_ (INCHE	ES)				
EVA	PORAT	IVE F	AMIL	_Y	L	EAK	FAMIL	_Y			CER	Ī				STD				
*							*			*					*					



FCA.US LLC.

Executive Order: A-009-1413

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

: not applicable; #: pounds; UL; useful life; PC: passenger car; LDT: light-duty truck; LDT1; LDT<6000#GVWR,0-3750#LVW; LDT2; DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV; medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard, FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW, LEV: low emission vehicle; ULEV: ultra LEV: SULEV: super ULEV: ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst: ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer, DPF; diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2; parallel; (2) suffix: series; CNG/LNG; compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT; other transmission; AER; all-electric range; EAER; equivalent AER; PHEV; plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD:
JEEP"	GRAND CHEROKEE 4X4	LDT4	3.0	A8	*	. 1	\$:
RAM	1500 4X2	LDT4	3.0	A8	.*.	1	\$
RAM	1500 4x4	LDT4	3.0	AB	*	1	\$