CALIFORNIA AIR RESOURCES BOARD

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	FOR	MATION					
MOD	I T	EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
201	9 K	CRXT06.45P1			LDT4 DED				SINGLE FUEI HICLE		GASOLINE		
	USEFU	L LIFE (miles)		VEH	ICLE EMISS	ION (ATE	GORY	INTERIM / IN	ITEF	RMEDIATE IN-USE STD		
EX	H/ORVR	EVAP		FTP SF				TP FTP			SFTP		
1	20000	15000	0	LEV	2 LEV	I		SFTP DARD	*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	TATUS	E	ENGINE DISPLACEMENT		
1 2H02S(2), SFI, 2TWC								FULL	*				
*	*							ARTIAL	ALL MODELS 6.		6.4		
*	*							TIAL WITH * FINES *					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR								VAP EMISSION STD VEHICLE CLASS SPECIAL FEATURE				
KCRXR0180RK0 LEV 2								LDT4			*		
	EMISSION CREDIT INFORMATION												
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-F						ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							N N					
NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	IOG CH4 NMOG/NMHC HCHO/NMHC PC4						EET S 0 LVV	V) LDT (3751 LVW-8500 MDV (10,001-			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.072			0.083		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this *L* day of September 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

A	A	2		RESO	OF		A		FCA L	JS LLO) .				Cars, L	ledium-Du	429 Trucks and ty Vehicles age 3 of 4		
								A	ГТАС	НМ	ENT								
	E	KHAL	JST	AND	EVAP	ORAT	IVE	EMIS	SION	STAN	DARD	S AN	DCERT	IFICA	TION	LEVEL	S		
		E	XH/	UST E	MISSIO	N STAN	DA	RDS AN	D CER	TIFIC	TION L	EVELS	(FTP, HW	FET,	50°F, 2	0°F)			
		FUEL	TY	m ac 0 10	onoxide ljustmer RVR [g	; NOx: o nt factor; HC/gallo	2DH on di	es of niti HS/3DH spense	rogen; H IS [g HC d]: on-bo	CHO: /test]: pard re	formalde 2/3 days fueling v	ehyde; F diurnal apor re	M: partice +hot-soal	ulate n ; RL [(gram;	natter; I g HC/m ; mg: m	HC; CO: c RAF: react i]: running illigram; m tal FTP	ivity loss;		
					NMOG (g/mi)			CO (g/mi)		NOx (g/mi)			HCHO (mg/mi)		PM (g/mi)				
				CERT STD			CERT STD		D	CERT STD		CER	CERT STD		CERT	STD			
FTP@50K GASOLI			1 0 0485		0.07	5	1.03	3.	4	0.022	0.05	; *		15	*	*			
FTPMIN		LEV3	GASOLINE- LEV3 E10		.0485	0.09	0	1.03	. 4.:	-	0.022	0.07	-	10		*	0.01		
50°F @4	4K		*		*	*		*	*	_	*	*	*		*				
						FUEL T	YPE				CE	NOx (g/mi) STD		CER	CO (g/m	I) STD		
HWFET @ 50K					GASC	LINE-L	EV3	3 E10		-	005 0.					510			
HWFET @ UL					GASOLINE-LEV3 E10						0.0	05	0.09						
20°F@50K G				GAS	GASOLINE-COLD CO LOW OCTANE									2.4	6	12.5			
2011								_		APDS	AND CE	RTIEIC	ATION L	EVELS					
1			-		II LAI	AUUT	-	S06	OTAND			SC03				OMPOSITI	E		
	FUEL T		TYPE			:+NOx mi)		CO PM (g/mi) (mg/			NMHC (g/r	+NOx	CO (g/mi)		NMOG+NOx (g/mi) (PM		
							1.15			0.0	61	0.86		1					
@ 4K	LEV3 E10		LO	STD	0.	60	-	11.8		-	0.	44	4.0	-					
				CERT		*	-	*	1	•			*	0.	0580	*	*		
@ UL			GASOLINE- LEV3 E10 ST		STD		*		*		ł	*		*	0	.090	*	*	
		BI		BIN										0	.100				
	_		WH	OLE VE	HICLE	EVAPO	RAT	IVE EN	ISSION	STA	DARDS	AND O	CERTIFIC	ATION	LEVE	LS			
-							WH	OLE VI	HICLE	EVAP	ORATIV	E TEST	ING						
EVAPORATIVE FAMILY			UEL TY			(g/1	/test) @ UL			2DHS (g/test) (@UL			RL (g/mi) @	-			
KCRXR0180RK0		GZ		ER 2 0.281 EADED			.90 *		CE		STD	FEI	-	CERT		STD			
		_	NLEAD							549 1.15		*		0.000		0.05			
C	DRVF	R/FU	ELC	DNLY/	CANIST	ER BLE	ED	EVAPO	RATIVE							TION LEV	ELS		
EVAP	ORA		E ORVR (g/gallon) @ UL				F	30			HS RIG TEST		2DHS	2DHS RIG TEST			D BLEED CANISTER TEST (g/test) @ 4K		
FA	MIL		FU	EL TYP	ECEF	T ST	D	FUEL TYPE			g/test) @ UL RT STD		-	(g/test) @ CERT S		CERT	STD		
KCRXR0180RK0		ORKO	GAS	OLINE IER 2	- 0.1						*	*	*		*	*	*		

CALIF AIR RESOU	ORNIA RCES BOARD	FCA US LLC.	Executive Order: A-009-1429 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4
EFFECTIVE	LEAK DIAMETER S	TANDARD AND CER	TIFICATION LEVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
*	*	*	+
			uck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: #ALVW; LDT4: LDT 6001-8500#GVWR,5751-

8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle: TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant guality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS 1	OBD	
DODGE	DURANGO SRT AWD	LDT4	6.4	A8	KCRXR0180RK0		P	
JEEP	GRAND CHEROKEE SRT 4X4	LDT4	6.4	A 8	KCRXR0180RK0		P	