

GENERAL MOTORS LLC. Executive Order: A-006-2171

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMAT	ON				
	MODEL YEAR TEST GROUP			VEHICLE CLASS(ES)			FUEL C	ATEGORY	FUEL TYPE		
2019	KG	MXD02.8360		MDV4 DED				SINGLE FUEL	DIESEL .		
	USEFUL	LIFE (miles)	VEH	IICLE EMISS	SION C	ATEGOR	Y	INTERIM / INT	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP				FTP		SFTP		FTP	SFTP		
150000 *			LEV3	ULEV250 BAG2, SC03 TEST CYC		FTP	*	*			
SPE	CIAL FE	EATURES & EXH SYS	AUST EMISSI	ON CONTRO	DL		OBD ST	TATUS	ENGINE DISPLACEMENT		
1	CAC, TC, DFI, OC(2), DPF, SCRC, EGR, EGRC, NOXS(2), PMS, RDQS										
2	2 CAC, TC, DFI, OC(2), DPF, SCRC, EGR, EGRC, NOXS(2), PMS, RDQS, FFH						PARTIAL *		2.8		
*							L WITH ES	ALL MODELS			
		EV	APORATIVE &	REFUELING	G (EVA	P/ORVR)	FAMILY	INFORMATION			
EVA	P / ORV	R FAMILY	EVAPORATIVI	E STD CATE	GORY			SSION STD CLASS	SPECIAL FEATURES		
	*			*			1		*		
				EMISSION C	REDIT	INFORM	IATION				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NO ZERO-EVAP						ZEV	NMOG CREDIT FOR DOR		OPTIONAL EXH. STD FOR WORK TRUCKS		
N N						N			N.		
			NMOC	AND FLEE	T AVE	RAGE IN	FORMA	TION			
NMOG RAF	OG CH4 NMOG/NMHC HCHO/NMHC DT (3751 LVW-)				LVW-8	500 GVW			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	*	*		*		0.253		0.400		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



GENERAL MOTORS

Executive Order: A-006-2171

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have three deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2019 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

BE IT FURTHER RESOLVED:

The fuel-fired heater incorporated in the listed vehicle models must not operate at ambient temperature above 40 °F (13 CCR Section 1961.2(a)(13) [Emission Standard for a Fuel-Fired Heater]).

2 day of July 2018.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



GENERAL MOTORS

Executive Order: A-006-2171

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 3 of 4

ATTACHMENT

	EXH	AUS	T AND	EV	APOR	ATIV		SSIONS			DS ANI	CERT	FICATIO	N LEV	ELS	
													FET, 50°F,			
	FU	JEL T	a o	H4: r nonox djustr	methan kide; No ment fa	e; NMC Ox: oxic ctor; 2I	G: non- les of ni DHS/3D dispens	-CH4 orga trogen; H HS [g HC ed]: on-bo	anic ga CHO: /test]:	as; HC: formald 2/3 day	hydrocar lehyde; F s diurnal vapor re	bon; NMH M: particu +hot-soak covery; g:	IC: non-CH late matter; ; RL [g HC/i gram; mg: i e: suppleme	4 HC; C RAF: ro mi]: runr milligran	eactivi ning lo n; mi:	ity iss;
				NMHC+NOx (g/mi)		CO (g/mi)			NOx (g/mi)			HCHO (mg/mi)		PM (g/mi)		
				CER	T	STD	CER	T STI	0	CERT	STD	CER	T STD	CE	RT	STD
TP@5	OK	*		*		*	*	*		*	*	*	*	1	,	*
FTP@L	IL DI	ESEL-	EPA	0.09	94 0	.250	0.1	6.	4	*	*	*	6	0.0	002	0.008
50°F @	4K	*		*		*	*	*		*	*	*	*			
		,			FU	EL TYP	E			$\overline{}$	7	Ox (g/mi)			g/mi)	
				FUEL TYPE						CERT		STD	STD CE		T STD	
HWFE	T @ 50H	<				*					*	*				
HWFE	T@UL			DIESEL-EP			PA	A		0.	033	0.250				
20°F	@ 50K			*										*		*
		_	S	FTP	EXHAL	JST EN	IISSION	STAND	ARDS	AND C	ERTIFIC	ATION L	EVELS			
				US06						SC03		COMPOSITE				
	FUEL	TYPE				HC+NOx (g/mi) (CO PM (g/mi) (mg/m		NMHC+NOx (g/mi)		CO (g/mi)	NMHC+N (g/mi)		CO g/mi)	PM (mg/mi
@ 4K		, CE			*	+		*			*	*	ç			
W 4K				-	+		*				*	*				
		CEIESEL-EPA ST			*		*	,	+		*	*	0.096		0.1	2
@ UL	DIESE				*		*		•		*	*	0.550	2	2.0	7
													*			Jahr.
		W	HOLE V	EHIC	LE EV	APOR	ATIVE E	MISSION	STA	NDARE	S AND	CERTIFIC	ATION LEV	/ELS		
						W	HOLE	VEHICLE	EVAF	PORAT	IVE TES	TING				
EVAPORATIVE FAMILY		FUEL TYPE			3DHS (g/test) @ UL					2DHS (g/test) @ UL			RL (g		g/mi) @ UL	
					CEF	CERT STD		FEL	CE	ERT STD		FE	L C	CERT		STD
*			*		*	*		*	,		*		*		*	
(DRVR /	FUEL	ONLY	CAN	ISTER	BLEE	D EVAF	ORATIVI	EEMI	SSION	STANDA	RDS ANI	CERTIFIC	ATION	LEVE	LS
									F	UEL O	NLY EVA	P & CAN	ISTER BLE	ED		
EVAPORATIVE FAMILY		VE	ORVR (g/gallon) @ UL				FUE	FUEL TYPE 3		DHS RIG TEST (g/test) @ UL			2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 48	
		FUEL '		TYPE CERT STD		_		CI	ERT	STD	CERT	STD	CE	RT	STD	
*			*	* * *			*				*	*			*	
		EF	FECTI	VE L	EAK	IAME	TER S	TANDAF	RD AN	ID CE	RTIFICA	TION LE	VEL (INC	HES)		
EVA	PORAT	IVE F	AMILY		LEA	KFAM	ILY			CERT STD						
	1					*				*				*		



GENERAL MOTORS LLC. Executive Order: A-006-2171

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

to not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GWWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV: SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor, NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV; selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2010 MODEL	VEAD.	VEHICL	E MODEL	SINFORMATION
ZUTY MCHIEL	YEAR.	VEHIC.	E MODEL:	SINFURMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	ECS	OBD
CHEVROLET	G2500 EXPRESS 2WD CARGO	MDV4	2.8	A8	*	1	\$
CHEVROLET	G2500 EXPRESS 2WD CARGO	MDV4	2.8	A8	*	2	\$
CHEVROLET	G2500 EXPRESS 2WD PASS	MDV4	2.8	A8	*	1	\$
CHEVROLET	G2500 EXPRESS 2WD PASS	MDV4	2.8	A8	*	2	\$
CHEVROLET	G3500 EXPRESS 2WD CARGO	MDV4	2.8	A8	*	1	\$
CHEVROLET	G3500 EXPRESS 2WD CARGO	MDV4	2.8	A8	*	2	\$
CHEVROLET	G3500 EXPRESS 2WD PASS	MDV4	2.8	A8	*	1	\$
CHEVROLET	G3500 EXPRESS 2WD PASS	MDV4	2.8	A8	*	2	\$
GMC	G2500 SAVANA 2WD CARGO	MDV4	2.8	A8	*	1	\$
GMC	G2500 SAVANA 2WD CARGO	MDV4	2.8	A8	*	2	\$
GMC	G2500 SAVANA 2WD PASS	· MDV4	2.8	A8	*	2	\$
GMC	G2500 SAVANA 2WD PASS	MDV4	2.8	A8	*	1	\$
GMC	G3500 SAVANA 2WD CARGO	MDV4	2.8	A8	*	1	\$
GMC	G3500 SAVANA 2WD CARGO	MDV4	2.8	A8	*	2	\$
GMC	G3500 SAVANA 2WD PASS	MDV4	2.8	A8	*	1	\$
GMC	G3500 SAVANA 2WD PASS	MDV4	2.8	A8	*	2	\$