CALIFORNIA AIR RESOURCES BOARD	
The FIFTHER REPOONDED DOARD	

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMA	TION				
MODE	- I T	EST GROUP	VEHICI	LE CLASS(ES)	FUEL CATEGORY			FUEL TYPE		
2019	KG	MXV01.8050		PC				ELECTRIC	GASOLINE		
I	USEFUL	LIFE (miles)	VEH	ICLE EMIS	SION C	ATEGOR	RY	INTERIM / INT	ERMEDIATE IN-USE STD		
EXH	ORVR	EVAP		FTP SFTP				FTP	SFTP		
15	0000	150000	LEV3	ULEV70	LEV	3 COMP	OSITE	NMOG+NOX	*		
SPE	CIAL FE	ATURES & EXI	AUST EMISSIC	ON CONTR	OL		OBD ST	TATUS	ENGINE DISPLACEMENT		
1		DFI, TWC, HO	02S(2), EGR,	EGRC		FU	LL	ALL MODELS			
*			*			PAR	TIAL	*	1.8		
*			*		-	PARTIA	L WITH				
		EV	APORATIVE &	REFUELIN	G (EVA	P/ORVR)	FAMILY	INFORMATION			
EVA	P / ORV	R FAMILY	EVAPORATIVE	STD CATE	EGORY			SION STD	SPECIAL FEATURES		
K	GMXR01	02815	L	EV 2 PC				с	*		
			8	MISSION	CREDIT	INFORM	ATION				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON ZERO-EVAP						ZEV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
N N						N			N		
	•		NMOG	AND FLEE	T AVE	RAGE IN	FORMAT	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	C HCHO/NMHC RATIO NMOG+NOX FLI PC+LDT (0-375 (g/mi)					3751 LVW-8500	D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	*		0.072			0.083	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this / 16 day of September 2018.

nnette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division

R	¥	23			OR		A	G	ENERA	L MOTO	ORS	ľ		xecutive Or enger Cars	, Ligh	t-Duty Tr ium-Duty		
						•		A	TTAC	HME	ENT							
	E	XHAL	JST	ANDE	VAPO	RATI	VE	EMIS	SION	STAN	DAR	DS ANI	CERT	FICATIC	NL	EVELS		
		E	XH/	UST EM	ISSION	STAN	DAF	RDS AI	ND CER	TIFICA	TION	LEVELS	(FTP, HW	FET, 50°F	, 20°F)		
		FUEL	. TYP	mor adju OR	noxide; istment VR [g F	NOx: o factor, C/gallo	2DF n dis	s of nit IS/3DF spense	rogen; H IS [g HC d]: on-b	CHO: 1 (test]: 2 oard re:	ormale 2/3 day fueling	dehyde; P ys diurnal vapor re	M: particu +hot-soak covery; g:	IC: non-CH ulate matter ; RL [g HC/ gram; mg: 2: suppleme	r; RAF /mi]: r millig	: reactive unning lo ram; mi:	ity oss;	
					NMOG (g/r		1		CO g/mi)			NOx g/mi)		HCHO (mg/mi)		Pi (g/n		
				C	ERT	STD	+	CERT	-	D	CERT	STD	CER			CERT	STD	
FTP@5	OK		*		*	+	_	*	+		*	*	+	+	-	*	+	
	FTP@UL GASOLINE- TIER3 E10			033	0.07	0	0.2	1.	7	*	*	+	4		*	0.01		
50°F @4	4K		*		*	*		+	+		*	*	*	*			-	
					F	UEL T	YPE					MOG+N				O (g/mi)		
									_		CERT		STD	STD CR		RT ST		
HWFET	۳@	50K				*						*	*					
HWFE	т@	UL			GASOL	INE-T	IERS	3 E10			0.	.003	0.070					
20°F	@ 5	OK	co	LD CO E	10 RE	GULAR	GAS	SOLINE (TIER3)			-	Ja		1.3			10.0	
	-			SFT	PEXH	AUST	EMIS	SION	STAND	ARDS	AND	CERTIFIC	ATION L	EVELS		_		
1							U	S06		-		SC03			COM	POSITE		
	FU	EL TY	PE		NMOG (g/r		(CO (g/mi)		PM g/mi)		G+NOx J/mi)	CO (g/mi)	NMOG+N (g/mi)		CO (g/mi)	PM (mg/mi)	
@ 4K	4K * _		* CE		•			*				+	*					
_				STD	*			*	-		_	*	*	-			-	
				CERT	*		-	*	-	*		*	*	0.050		0.2	*	
@ UL	TIER3 E10		STD	•			. *		*		•	*	0.090		4.2	*		
	-	•		BIN									EDTIFIO	0.070			1	
			WH	OLE VER	ICLE			-						ATION LE	VELS			
EVAPORATIVE			F	UEL TYP				HOLE VEHICLE EVAF			2DHS (g/test) @ UL			RL (g/mi) @ U			UL	
FAMILI					CERT		S	STD FEL		CERT		STD	FE		CERT		STD	
KGMKR0102815			ASOLINE TIER 2 JNLEADE	0	0.346 0		50	* 0.		66	0.65	+	0	0.00		0.05		
C	DRV	R/FU	EL C	DNLY / C	ANIST	R BLE	ED	EVAPO	ORATIV	EEMIS	SION	STANDA	RDS ANI	CERTIFIC	CATIC	ON LEVE	LS	
EVAP	ORA	TIVE		ORVR (g	gallon) @ UL	-	F			UEL ONLY EVAP &		2DHS	& CANISTER BLEED			NISTER	
FA	MIL	.Y				-	_	FUEL TY			g/test) @ UL		-	st) @ UL 1		FEST (g/test) @ 4		
*		0015	GAS	EL TYPE	-		+			CE		STD	CERT		-	CERT	STD	
KGMXF	010	2815		TIER 2	0.0	2 0.2	20		*	1		*	*			*	*	

CALIF AIR RESOU	ORNIA RCES BOARD	GENERAL MOTORS LLC.	Executive Order: A-006-2181 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4
EFFECTIVE	LEAK DIAMETER	STANDARD AND CERT	FICATION LEVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
*	*	*	*
duty passenger vehicle; HDV: he emission limit; GVWR: gross vel ULEV: ultra LEV; SULEV: super ADSTWC: adsorbing TWC; HAC SCRC/SCR-N or SCRC-NH3: se continuous/periodic trap oxidized heated/oxygen sensor, WR-HO2 RDQS: reductant quality sensor, secondary air injection (belt drive direct/indirect fuel injection; TC/S fines on-board diagnostic; DOR: suffix: series; CNG/LNG: compre E10: "10%" ethanol ("90%"gasol continuously variable transmissi	eavy-duty vehicle; EC hicle weight rating; L' ULEV; ZEV: zero-er C: HC adsorbing cata elective catalytic redu r; DPF: diesel particu 2S or AFS: wide rang ; NH3S: ammonia se en)/(electric driven); SC: turbo/super charg direct ozone reducir essed/liquefied natur- line) fuel; A: automati ion; SCV: selectable	CS: emission control system; VW: loaded vehicle weight; A nission vehicle; TZEV: transit ilyst; WU: warm-up catalyst; M uction-urea/ammonia; NH3OC late filter (active); GPF: PM fil je/linear/heated air-fuel ratio s nsor; EGR: exhaust gas recir PAIR: pulsed AIR; SFI/MFI: s ger; CAC: charge air cooler; f ng; HCT: hydrocarbon trap; B al gas; LPG: liquefied petrole ic (with lockup); M: manual tra continuously variable transmi	75: MDV 10001-14000#GVWR; MDPV: medium- CERT: certification; STD: standard; FEL: family LVW: adjusted LVW; LEV: low emission vehicle; ional ZEV; TWC/OC: 3-way/oxidizing catalyst; IAC: NOx adsorption catalyst; SCR-U or :: ammonia oxidation catalyst; CTOX/PTOX: Iter for spark-ignited engine; HO2S/O2S: isensor; NOXS: NOx sensor; PMS: PM sensor; culation; EGRC: EGR cooler; AIR/AIRE: equential/multiport fuel injection; DFI/IFI: FH: fuel fired heater; F/P/\$: full/partial/partial with CAN: bleed carbon canister; prefix 2: parallel; (2) um gas; E85: "85%" ethanol ("15%"gasoline) fuel; ansmission; SA: semi-automatic transmission; CV: ssion; AM: automated marual transmission; AMS: tric range; EAER: equivalent AER; PHEV: plug-in

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CHEVROLET	MALIBU	PC	1.8	CV	. KGMXR0102815	1	F