

Executive Order: A-008-0491

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	ROUP II	NFO	RMATION				-		
MODE YEAR		EST GROUP		VEHIC	LE CLASS	(ES)		FUEL	C	ATEGORY		FUEL TYPE		
2019	KB	MXV00.6I3R			PC		PLUG-IN HYBRID ELECTRIC VEHICLE					GASOLINE		
1	USEFUL	. LIFE (miles)		VEH	ICLE EMIS	SSION CATEGORY INTERIM / INT			ΓER	MEDIATE IN-USE STD				
EXH	EXH/ORVR EVAP FTP					S	FTP		FTP		SFTP			
15	0000	150000		LEV3	SULEV30	LEV	3 (	COMPOSITE		*		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD	S1	TATUS	E	NGINE DISPLACEMENT (L)		
1	1 TWC, WR-HO2S, HO2S, SFI							FULL		ALL MODELS	11			
*	*							PARTIAL	7	*	11	0.6		
*	*						PA	RTIAL WITH	1	*				
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	P / ORV	R FAMILY	EVAP	ORATIVE	STD CAT	EGORY	RY EVAP EMISSION STD VEHICLE CLASS				s	SPECIAL FEATURES		
K	BMXR00	3513R		L	EV 2			PC			*			
					MISSION	CREDI	r inf	ORMATION	ı					
ALL	GR	E FOR TEST OUP	A۷	IOG+NOX /E. CRED NDED W/		R NON-PZEV ZERO		V ZERO-		NMOG CREDIT FOR		OPTIONAL EXH. STD FOR WORK TRUCKS		
	ALL M	ODELS		N			ì	Ŋ		N		N		
				NMOG	AND FLEI	ET AVE	RAC	GE INFORM	ΑT	TION				
NMOG RAF	PAE   RAE   NMOG/NMHC   RATIO   PC+LDI (0-3/								D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)					
*	*	1.10		*		0.072				0.083		*		
0 41-	A 44 1	4.5 3.4			41 5	- 1	_				$\overline{}$	entral Systems Phase		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-008-0491

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED: Evaporative family KBMXR0035I3R is certified pursuant to 13 CCR Section 1976(b)(1)(G)3 and deemed to comply with the requirements of 13 CCR Section 1976(b)(1)(G)1 ["LEV III evaporative requirements"].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of October 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-008-0491

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

## **ATTACHMENT**

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

**FUEL TYPE** 

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		P <b>M</b> (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10	0.019	0.030	0.5	1.0	*	*	*	4	0.000	0.003
50°F @4K	GASOLINE- TIER3 E10	0.014	0.060	0.2	1.0	*	*	*	8		

	EUEL TYPE	NMOG+N	lOx (g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-TIER3 E10	0.010	0.030			
20°F @ 50K	COLD CO E10 REGULAR GASOLINE (TIER3)			1.0	10.0	

## SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			US06			SC03	3	COMPOSITE		
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	1	*	*	0.014	1.4	*
@ UL	GASOLINE- TIER3 E10	STD	*	*	6	*	*	0.090	4.2	*
		BIN						0.050		

#### WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	FUEL TYPE		WHOLE \						
EVAPORATIVE FAMILY		3DH	S (g/test) @	) UL	2DI	HS (g/test) (	RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
KBMXR003513R	GASOLINE - CA PHASE 2	0.28	0.35	*	*	0.35	*	0.00	0.05

## ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
KBMXR0035I3R	GASOLINE - TIER 2 UNLEADED	0.12	0.20	GASOLINE - CA PHASE 2	0.0	0.0	*	0.0	*	*			



Executive Order: A-008-0491

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)									
EVAPORATIVE FAMILY LEAK FAMILY CERT STD									
* * * *									

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GWWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALWW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor: NH3S: ammonia sensor: EGR: exhaust gas recirculation: EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV; selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2019 MODEL	YEAR: VE	HICLE	MODELS	INFORMATION
ZUIS NIUDEL	I EAR. VE		MODELS	HAL OLIMA HOLA

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	BMW	I3 (120AH) WITH RANGE EXTENDER	PC	0.6	SA1	KBMXR0035I3R	1	F
2	BMW	I3S (120AH) WITH RANGE EXTENDER	PC	0.6	SA1	KBMXR0035I3R	1	F

# **ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION**

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHWAY (MILES)		ZEV	
NUMBER	PHEVITE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE	
1	TZEV	186.55	187.37	23.97	166.51	174.33	2.37	
2	TZEV	186.55	187.37	23.97	166.51	174.33	2.37	