

Executive Order: A-009-1430

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	IFORI	MATION					
MOD		TEST GROUP	VEHICLE CLASS(ES			S)	S) F		ATEGORY		FUEL TYPE		
201	9 K	CRXV06.45P0			PC		DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
	USEFL	JL LIFE (miles)	VEHICLE EMISSION CATEGORY				SORY	INTERIM / IN	ITER	RMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP S			SF	SFTP FTP			SFTP		
120000 150000)	LEV	V2 LEV LEV 2 SI STANDAI				*		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	OBD STATUS		ENGINE DISPLACEMENT		
1	2HO2S(2), SFI, 2TWC							FULL	*				
*		*						ARTIAL	ALL MODELS		6.4		
*	*						1	TIAL WITH FINES	*				
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMATIO	N			
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO						,		SSION STD E CLASS		SPECIAL FEATURES		
	KCRXR0141PK0 LEV 2 PC *					#							
		*		E	EMISSION C	REDIT	INFO	RMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR N ZERO-EVAF						ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N								N		N		
	NMOG AND FLEET AVERAGE INFORMATION												
NMO(RAF					0-375	50 LVW) L		NMOG+NOX FLEET ST LDT (3751 LVW-8500 GVWR) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	.072			0.083		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-009-1430

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of August 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-009-1430

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

						AIIA	CHI	MENI							
E	XHAU	ST AN	D EV	APORA	TIVE EN	MISSIOI	N STA	NDARD	S AN	D CERT	IFICA	TION	LEVELS	3	
	EX	HAUST	EMIS	SION STA	NDARDS	AND CE	ERTIFIC	CATION L	EVELS	(FTP, HW	/FET,	50°F, 20	°F)		
	FUEL 1	TYPE	monox adjusti ORVR	ride; NOx: ment facto [g HC/gal	oxides of r; 2DHS/3 lon disper	nitrogen BDHS [g l nsed]: on	; HCHO HC/test -board	D: formalde t]: 2/3 days refueling v	ehyde; F s diurnal vapor re	PM: particu +hot-soak covery; g:	ulate m ; RL [g gram;	natter; R. g HC/mi] mg: mill	AF: reaction in the second in	vity oss;	
				NMOG (g/mi)		CO (g/mi)								PM (g/mi)	
			CER	T ST	D CE	RT S	STD	CERT	STD	CER	T	STD	CERT	STD	
ж	GASOLINE- LEV3 E10 PREM		0.04	72 0.0	75 0.	63	3.4	0.022	0.05	*		15	*	*	
IL	LEV3	E10	0.04	72 0.0	90 0.	63	4.2	0.022	0.07	*		18	* .	0.01	
ŧΚ	*		*	. *	1	*	*	*	*	*		*		15	
				FILE	TVPF				NOx (g/mi)			CO (g/mi)	
				TOLL	111.			CE	RT	STD		CERT	Г	STD	
@	50K		GASC	ASOLINE-LEV3 E10 PREM				0.0	003	0.07					
Т@	UL		GASC	LINE-LE	V3 E10	PREM		0.0	003	0.09			,		
@ 50	ok	G	ASOLI	NE-COLD	CO LOW	OCTANE		(#1		NI -		1.16	;	10.0	
			SFTP	EXHAUST	EMISSIC	ON STAN	IDARD	S AND CI	ERTIFIC	ATION L	EVELS	3			
				US06					SC03			COMPOSITE			
FU	EL TYP	E N		MHC+NOx (g/mi)						CO (g/mi)	NMOG+NOx (g/mi)			PM (mg/mi	
	V3 E10	E10 CERI		0.050	0.6	57		0.0	050	0.39					
	_		0	0.14	8.0	0		0.	20	2.7					
	CI		₹T	*		* *		1	*		0.	0571	*	*	
			D *		*			,	•	*		0.090		*	
			V V			7					0	.100			
	٧	VHOLE	VEHIC	LE EVAP	ORATIVE	EMISSI	ON ST	ANDARD	SAND	CERTIFIC	ATION	LEVEL	.s		
					WHOLE	VEHIC	LE EVA	APORATIN	/E TES	TING					
EVAPORATIVE FUEL		FUEL	TYPE	3DH	IS (g/test)	/test) @ UL		2DHS	2DHS (g/test)			RL (g/mi) @ UL		UL	
			CERT		STD	FEL	. 0	ERT	RT STD		L	CERT		STD	
.014	1PKO	TIE	R 2	NE - 0.454		*	0	.383	0.65	*		0.000		0.05	
	FU GA. LE	FUEL TYP GASOLINE LEV3 E10 GASOLINE LEV3 E10 PREM GASOLINE LEV3 E10 PREM V ORATIVE	FUEL TYPE GASOLINE- LEV3 E10 PREM GASOLINE- LEV3 E10 PREM GASOLINE- LEV3 E10 PREM GASOLINE- LEV3 E10 PREM STI GASOLINE- LEV3 E10 PREM STI GASOLINE- LEV3 E10 PREM STI GASOLINE- LEV3 E10 PREM GASOLINE- LEV3 E10 PREM STI GASOLINE- LEV3 E10 PREM GASOLINE- LEV3 E10 PREM STI GASOLINE- LEV3 E10 PREM GASOLINE- LEV3 E10 PREM STI GASOLINE- LEV3 E10 PREM GASOL	FUEL TYPE CH4: r monox adjusts ORVR 1000 r CER GASOLINE- LEV3 E10 0.04 PREM GASOLINE- LEV3 E10 GASOLITE FUEL TYPE FUEL TYPE GASOLINE- LEV3 E10 PREM STD CERT GASOLINE- LEV3 E10 PREM STD GASOLINE- CERT GASOLINE- CERT GASOLINE- CERT GASOLINE- CERT GASOLINE- CORATIVE GASOLINE- CERT CORATIVE CERT CERT	FUEL TYPE FUEL TYPE	EXHAUST AND EVAPORATIVE EN EXHAUST EMISSION STANDARDS CH4: methane; NMOG: no monoxide; NOx: oxides of adjustment factor; 2DHS/3 ORVR [g HC/gallon dispersion of the factor) on the factor of the fac	EXHAUST AND EVAPORATIVE EMISSION EXHAUST EMISSION STANDARDS AND CE CH4: methane; NMOG: non-CH4 of monoxide; NOx: oxides of nitrogen adjustment factor, 2DHS/3DHS [g] ORVR [g] HC/gallon dispensed]: on 1000 miles; F: degrees Fahrenheit; NMOG (g/mi) (g/mi) CERT STD STD STANDARD STA	EXHAUST AND EVAPORATIVE EMISSION STA EXHAUST EMISSION STANDARDS AND CERTIFIC CH4: methane; NMOG: non-CH4 organic monoxide; NOx: oxides of nitrogen; HCH0 adjustment factor; 2DHS/3DHS [g HC/test ORVR [g HC/gallon dispensed]: on-board 1000 miles; F: degrees Fahrenheit; FTP: 1 NMOG	CH4: methane; NMOG: non-CH4 organic gas; HC: monoxide; NOx: oxides of nitrogen; HCHO: formald adjustment factor; 2DHS/3DHS [g HC/feest]: 2/3 days ORVR [g HC/gallon dispensed]: on-board refueling 1000 miles; F: degrees Fahrenheit; FTP: federal tes NMOG	EXHAUST AND EVAPORATIVE EMISSION STANDARDS AN EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocal monoxide; NOx: oxides of nitrogen; HCH0: formaldehyde; F adjustment factor; 2DHS/3DHS [g HC/Rest]: 2/3 days diurnal ORVR [g HC/gallon dispensed]: on-board refueling wapor 1000 miles; F: degrees Fahrenheit; FTP: federal test proced [g/mi]	EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERT EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HW CH4: methane; NMGG: non-CH4 organic gas; HC: hydrocarbon; NMH monoxide; NOx: oxides of nitrogen; HCH0: formaldehyde; PM: partic adjustment factor; 2DHS/3DHS [g HC/test); 2/3 days diurnal+hot-soals ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g; 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTF (g/mi) (g/mi) (g/mi) CERT STD STD STD STD STD STD STD STD STD ST	EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICA EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, INC. 10 CENT. 1	EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20 CH4: methane; NMOG; non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 is monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter, Radjustment factor; 2DHS/3DHS [g HC/selt]; 22d ads; diumal-ind-casek; R.L. [g HC/gallon dispensed]: on-board refueling vapor recovery; g; gram; mg; mill 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplements (g/ml) (g/ml) (g/ml) (g/ml) (mg/ml) (mg/ml) (mg/ml) (mg/ml) (g/ml) (g/ml) (g/ml) (g/ml) (g/ml) (g/ml) (mg/ml) (g/ml) (g/	EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 crganic gas; HC: hydrocarbon; NMHC: non-CH4 HC: CO: do non-oxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PMI: particulate matter, RAF: reactive adjustment factor; 2D15/3D145 [g HC/nest]; 2/3 days diurnal+hot-scake, RL [g Hc/mi]; nunning I (ORVR Ig Hc/galion dispensed): on-board refueling vapor recovery; g: gram; mg; milligram; milligr	



Executive Order: A-009-1430

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

ORVR / FU	EL ONLY / CA	NISTER	BLEED	EVAPORA	TIVE	EMISSION	STANDA	RDS AN	D CERTIFIC	ATION LEV	ELS	
		FUEL ONLY EVAP & CANISTER BLEED										
EVAPORATIVE FAMILY	ORVR (g/	FUEL TYPE		3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K				
	FUEL TYPE	CERT	STD			CERT	STD	CERT STD		CERT	STD	
KCRXR0141PK0	GASOLINE - TIER 2 UNLEADED	0.090	0.20	*		*	*	*	*	*	*	
	EFFECTIVE	LEAK D	IAMET	ER STAN	DAR	D AND CE	RTIFICA	TION L	EVEL (INCH	IES)		
EVAPORATIVE	FAMILY	LEAK FAMILY			CERT				STD			
*		*			*				*			

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW; LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor, WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor, NOXS: NOx sensor, PMS: PM sensor, RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2019 MODEL YEAR: VEHICLE MODELS INFORMATION													
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	OBD						
DODGE	CHALLENGER	PC	6.4	М6	KCRXR0141PK0	1	P						
DODGE	CHALLENGER	PC	6.4	A8	KCRXR0141PK0	1	P						
DODGE	CHARGER	PC	6.4	A8	KCRXR0141PK0	1	P						