

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GROUP	INFOR	ATION				
MODE		EST GROUP	LE CLASS(ES)		FUEL C	ATEGORY	FUEL TYPE			
2019	K	MXT03.53E8		LDT3 DED:			SINGLE FUEL HICLE	GASOLINE		
l	JSEFUL	LIFE (miles)	VEH	ICLE EMISSION	CATE	ORY	INTERIM / INT	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP				FTP	SF	ГР	FTP	SFTP		
12	0000	150000	LEV	2 ULEV	ULEV LEV 2 SFT STANDARD		*	*		
SPE	CIAL FI	EATURES & EXI	HAUST EMISSIC	ON CONTROL		OBD ST	TATUS	ENGINE DISPLACEMENT		
1		2TWC, 2WR-	HO2S, 2HO2S,	SFI		FULL	*			
*			*		P	ARTIAL	ALL MODELS	3.5		
*			*			PARTIAL WITH *				
-		EV	APORATIVE &	REFUELING (E	VAP/OR	VR) FAMILY	INFORMATION			
EVA	P / ORV	R FAMILY	EVAPORATIVE	E STD CATEGO	RY		SSION STD E CLASS	SPECIAL FEATURES		
K	FMXRO	145GBC	L	EV 2		LD	T3	*		
			E	EMISSION CRE		RMATION				
	EDIT FO	OX FLEET AVE. OR EXTENDED RRANTY		EDIT FOR NON ZERO-EVAP	-PZEV	NMOG CI	REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N		N			N	N		
			NMOG	AND FLEET A	VERAGE	INFORMA	TION			
NMOG RAF	CH4 RAF			750 LVV	V) LDT	+NOX FLEET ST (3751 LVW-8500 R) + MDPV (g/mi)	D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.04	*	0.0	72		0.083	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of September 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

R	F	2		RESO	FOI	R N I s boa	A	FORD COM	MOTO		N				ht-Duty T dium-Dut	164 Trucks and Y Vehicles ge 3 of 4	
							A	TTAC	HM	ENT							
	E	XHA	UST	AND	EVAF	PORAT	IVE EMI	SSION	STAN	DARD	S AND	CERT	FIC	ATION	EVELS	5	
			EXHA	USTE	MISSIC	ON STAP	NDARDS /	ND CER	TIFICA	TION L	EVELS	(FTP, HW	FET,	50°F, 20	°F)		
		FUEL TYPE			CH4: methane; NMOG: non-CH4 organ monoxide; NOx: oxides of nitrogen; HC adjustment factor; 2DHS/3DHS [g HC/to ORVR [g HC/gallon dispensed]: on-boa 1000 miles; F: degrees Fahrenheit; FTF					formalde 2/3 days	ehyde; P diurnal- apor rec	M: particu +hot-soak covery; g:	ilate i ; RL gram	matter; R/ [g HC/mi]: n; mg: mill	AF: reacti running igram; mi	vity loss;	
						MOG g/mi)		CO (g/mi)		NOx (g/mi)			HCHC (mg/m		-	PM (g/mi) °	
					CERT	ST	CER	T ST	D	CERT	STD	CER	т	STD	CERT	STD	
TP@50	GASOLINE 50K TIER 2 UNLEADE		ER 2		0.032	0.04	10 1.3	4 1.	7	0.02	0.05	0.05 *		8	*	*	
FTP@U	TP@UL GASOL TIE UNLE		ER 2		0.041	0.05	5 1.6	2 2.	1	0.04	0.07	*		11	* 1	0.01	
50°F @4	4K		*		*	*	*	*		*	*	*		*	nt farm		
						FUEL 1	TYPE				NOx (-		CO (g/mi		
									CERT STD 0.015 0.07		-	CERT		STD			
IWFET	r @	50K	_	GA	SOLINI	E - TIR	R 2 UNL	EADED				0.07					
HWFE	Т@	UL		GA	SOLINI	E - TIR	R 2 UNL	EADED		0.0	034	0.09					
20°F (@ 5	OK		GA	BOLINE	-COLD	CO LOW C	CTANE			-		-	3.42		12.5	
				S	FTP E)	HAUST	EMISSIO	N STAND	ARDS	AND C			EVEL				
		US06									SC03				MPOSITE		
	FU	JEL T	TYPE NMHC+NOx CO PM (g/mi) (g/mi) (mg/m			NMHC+NOx (g/mi)		CO NMOG+N (g/mi) (g/mi)		OG+NOx (g/mi)	CO (g/mi)	PM (mg/m					
1		SOLINE - C TIER 2 NLEADED		CERT	ERT 0.042		2.65	2.65		0.089		2.51		7		-	
0				STD	0	0.40	10.5			0.	31 .	3.5					
				CERT		*	*		*	*		*		0.103	*	*	
@ UL	UL GASOLI UL TIER UNLEA		2 STD					*		•		*	0.090		*		
		E		BIN										0.130			
			WH	OLE V	EHICL	EEVAPO	DRATIVE						ATIC	N LEVEL	S		
				WHOLE VEHICLE EVAN					ORATIVE TESTING								
EVAPORATIVE FAMILY			I FUEL		EL TYPE 3DHS (g/te		S (g/test)	est) @ UL		2DHS (g/test		t) @ UL		R	- (y/mi) (ı/mi) @ UL	
						CERT	STD	FEL	FEL CE		RT STD		L	CER	Т	STD	
KFMXR0145GB			ASOLII	LINE -		0.90	*	0.3	349 1.15				0.000		0.05		

A					RD MOTOR				der: A-010-2 Light-Duty Medium-Du Pa	Trucks and	
ORVR / FU	EL ONLY / CA	NISTER	BLEED	EVAPORA						ELS	
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TY	3DHS	RIG TEST	2DHS RIG TEST (g/test) @ UL		BLEED CANISTE TEST (g/test) @ 4		
	FUEL TYPE CERT STD		STD		CERT		CERT	STD	CERT	STD	
KFMXR0145GBC	GASOLINE - TIER 2 UNLEADED	2 0.021 0.20		* -	*	*	*	*	*	*	
	EFFECTIVE	LEAK D	AMET	ER STAND	ARDAND	CERTIFICA	TION LE	EL (INCI	HES)		
EVAPORATIVE	FAMILY	LEA	K FAMIL	Y	(CERT			STD		
*	* *					*		*			
*: not applicable; # LDT<6000#GVWF 8500#ALVW; MDV duty passenger ve emission limit; GV ULEV: ultra LEV; \$ ADSTWC: adsorbi SCRC/SCR-N or \$ continuous/periodi heated/oxygen sei RDQS: reductant of secondary air inject direct/indirect fuel fines on-board dia suffix: series; CNO E10: "10%" ethano continuously varia automated manua hybrid electric veh	R,3751-5750#L /: medium-duty hicle; HDV: he WR: gross veh SULEV: super ng TWC; HAC SCRC-NH3: se c trap oxidizer hsor; WR-HO2 quality sensor; ction (belt drive injection; TC/S gnostic; DOR: S/LNG: compre- bl ("90%" gasoli ble transmissio l-selectable tra	VW; LD y vehicle avy-duty nicle weig ULEV; Z : HC ads elective c ; DPF: di S or AFS NH3S: a en)/(elect SC: turbo direct oz essed/liqu ine) fuel; on; SCV:	T3: LDT (MDV4: vehicle; pht rating EV: zero orbing ca atalytic re esel part s: wide ra mmonia ric driver /super ch one redu uefied na A: autom selectab	5001-8500# MDV 8501-1 ECS: emiss ; LVW: loade -emission ve atalyst; WU: eduction-ure iculate filter ange/linear/h sensor; EG b); PAIR: pul harger; CAC ucing; HCT: I tural gas; LF hatic (with lo le continuou	GVWR,3751- 10000#GVWF sion control sy ed vehicle we ehicle; TZEV: warm-up cat a/armmonia; I (active); GPF teated air-fue R: exhaust ga sed AIR; SFI charge air c hydrocarbon PG: liquefied ckup); M: ma asly variable t	5750#ALVW R; MDV5: MI vstem; CERT ight; ALVW: transitional alyst; NAC: I NH3OC: ami PM filter fo I ratio senso as recirculatio /MFI: sequer poler; FFH: I trap; BCAN: petroleum ga nual transmi ransmission;	/; LDT4: LD DV 10001-14 F: certification adjusted LV ZEV; TWC// NOx adsorp monia oxida rr spark-ignif r; NOXS: No on; EGRC: I ntial/multipo fuel fired hea bleed carbo as; E85: "85 ssion; SA: s ; AM: autom	T 6001-850 4000#GVV on; STD: st VW; LEV: I OC: 3-way tion cataly ted engine Ox sensor; EGR coole rt fuel injec ater; F/P/\$ on canister %" ethanol semi-autom	00#GVWR,5 VR; MDPV: I andard; FEL ow emission /oxidizing ca st; SCR-U o st; CTOX/P1 ; HO2S/O2S PMS: PM s r; AIR/AIRE tion; DFI/IFI : full/partial/p ; prefix 2: pa l (*15%*gaso natic transmiss	751- medium- .: family vehicle; talyst; r TOX: : ensor; : : partial with rallel; (2) pline) fuel; ssion; CV: sion; AMS:	

2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
FORD	EXPLORER AWD	LDT3	3.5	SA6	KFMXR0145GBC	1	P
FORD	EXPLORER FWD	LDT3	3.5	SA6	KFMXR0145GBC	1	P