

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MODE		EST GROUP	VEHIC	LE CLASS(E	S)		FUEL C	24	ATEGORY		FUEL TYPE			
2019	19 KTYXT02.5N4H								ATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFU	LLIFE (miles)		VEF	ICLE EMISS	ION C	ATE	GORY	Τ	INTERIM / INT	ERM	EDIATE IN-USE STD		
EXI	I/ORVR	EVAP			FTP		SF	TP	FTP			SFTP		
1!	50000	150000	)	LEV3	ULEV50	LEV	3 CC	MPOSITE	Ī	NMOG+NOX ANI	D PM	PM PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD S	Т	ATUS	EN	GINE DISPLACEMENT (L)		
1	DFI, SFI, EGR, EGRC, WR-HO2S(2), TWC(2)							FULL	Γ	ALL MODELS				
*	*							ARTIAL	t	*		2.5		
*				1	TIAL WITH		*							
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	P / OR	E STD CATE	GORY	,	EVAP EMI	-								
1	KTYXR01	L30P82		LEV 3	OPTION2			LD	נכ	r1	HCT			
				1	EMISSION CI	REDIT	INFC	ORMATION						
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON- ZERO-EVAP						ZEV				PTIONAL EXH. STD OR WORK TRUCKS			
		N			N				N N					
				NMOG	AND FLEET	T AVE	RAG		Т	ION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO HCHO/NMHC RATIO (g/mi)				0-375		V) LDT	LDT (3751 LVW-8500 MDV			MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	0	0.009	0	. 072				0.083		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



# ATTACHMENT

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

## EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

ÍF	÷U	FL	T)	<b>γ</b> Ρ	E

					OG+NOx g/mi)		CO (g/mi)		•	lOx J/mi)		HCH mg/n	-		PM (g/n	•		
				CERT	ST	D CEF	T ST	D	CERT	STD	CER	г	STD	CE	RT	STD		
FTP@5	ок	*		*	*	*	*	,	*	*	*		*	*	,	*		
FTP@L		GASOLINE- TIER3 E10		0.021	2 0.0	50 0.1	9 1.	7	*	*	*		4	0.0	003	0.003		
50°F @	4K	*		*	*	*	*		*	*	*		*					
									N	MOG+NO	x (g/mi)			CO (	g/mi)			
					FUEL	ITPE			CI	ERT	STD		CER	Г		STD		
HWFET @ 50K					*					*	*							
HWFET @ UL			GAS	OLINE-1	IER3 E1	0		0.0	0125	0.050								
20°F	20°F@50K COLD CO			O E10	REGULAR	GASOLI	NE (TIE	R3)					1.31	1.31 10.0		.0.0		
			5	SFTP E	XHAUST	EMISSIO	N STAND	ARDS	AND C	ERTIFIC/	ATION LE	VEL	.S					
						US06				SC03			COMPOSITE					
	FUEL T	UEL TYPE		UEL TYPE NM		NMOG+NOx		F	PM		G+NOx			NMOG+NOx		со	PM	
				(	g/mi)	(g/mi	) (m <u></u>	g/mi)	(g	/mi)	(g/mi)	(	(g/mi)	(g	ı/mi)	(mg/mi)		
@ 4K	*	* CERI		г	*	*				*	*							
0					*	*				*	*							
			CER	r	*	*	0	. 8		*	*	0	0.0340 (		.34	*		
@ UL				GASOLINE- TIER3 E10			*	*		6		*	*	(	0.090	4	1.2	*
			BIN									(	0.060					
		WH	OLE \	/EHICL	E EVAPO	RATIVE I	EMISSIO		NDARD	S AND C	ERTIFIC	ATIO	N LEVEL	S				
						WHOLE	VEHICLE	EVAP	ORAT	IVE TEST	ING							
		E F	UEL TYPE 3DHS (g/test) @ UL 2DHS (g/test) @ UL						RI	L (g/n	ni) @	UL						
					CERT	STD	FEL	CE	RT	STD	FEL	•	CER	Т		STD		
KTYXR0130P8		2 1	ASOL:		0.1788	0.300	*	*	,	0.300	*		0.00	)5		0.05		

#### ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS FUEL ONLY EVAD & OANUOTED DI FED

				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS R (g/test	IG TEST )@UL	2DHS R (g/test		BLEED CANISTER TEST (g/test) @ 4K				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
KTYXR0130P82	GASOLINE- TIER3 E10	0.002	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.0125	0.020			

CALIFORNIA AIR RESOURCES BOARD			OYOTA MOTOR CORPORATION	M. F. B.								
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY			CERT	г	STD							
KTYXR0130P82	KTYXR0130P82-001		*		0.02							
LDT<6000#GVWR,3751-5756 8500#ALVW; MDV: medium- duty passenger vehicle; HDV: emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidi. heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt d direct/indirect fuel injection; T fines on-board diagnostic; DC suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"ga: continuously variable transmis	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: ME : heavy-duty vehicle; E0 vehicle weight rating; L' per ULEV; ZEV: zero-en IAC: HC adsorbing cata : selective catalytic redu zer; DPF: diesel particu IO2S or AFS: wide rang or; NH3S: ammonia se riven)/(electric driven); I C/SC: turbo/super charg OR: direct ozone reducir pressed/liquefied natur soline) fuel; A: automati ssion; SCV: selectable of	01-850 0V 850 CS: en VW: lo nission late fil pe/linea nsor; l PAIR: ger; C, ng; HC al gas ic (with contine	0#GVWR,3751-5750 01-10000#GVWR; ME nission control system baded vehicle weight; n vehicle; TZEV: trans VU: warm-up catalyst urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas rea pulsed AIR; SFI/MFI: AC: charge air cooler iT: hydrocarbon trap; ; LPG: liquefied petro n lockup); M: manual uously variable transr	#ALVW; LDT4: DV5: MDV 1000 n; CERT: certific ALVW: adjusted sitional ZEV; TW ; NAC: NOX ads DC: ammonia ox filter for spark-it o sensor; NOXS circulation; EGR sequential/mult ; FFH: fuel fired BCAN: bleed ca leum gas; E85: ' transmission; S/ nission; AM: aut	tidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; C: EGR cooler; AIR/AIRE:							
2019	MODEL YEAR	: VE		ELS INFO	RMATION							

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	RAV4	LDT1	2.5	SA8	KTYXR0130P82	1	F
TOYOTA	RAV4	LDT2	2.5	SA8	KTYXR0130P82	1	F
TOYOTA	RAV4 AWD	LDT2	2.5	SA8	KTYXR0130P82	1	F