

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMA	TION			
MODE	- I T	EST GROUP	LE CLASS(I	CLASS(ES)		FUEL C	ATEGORY	FUEL TYPE		
2019	KI	YXV01.5P34	PC				ELECTRIC	GASOLINE		
I	USEFUI	LIFE (miles)	VEH	ICLE EMIS	SION C	ATEGO	RY	INTERIM / INT	ERMEDIATE IN-USE STD	
EXH	ORVR	EVAP		FTP SFTP			FTP		SFTP	
15	0000	150000	LEV3	SULEV30	LEV 3 COMPO		OSITE	*	PM	
SPE		EATURES & EXI	HAUST EMISSIO	ON CONTRO	DL		OBD ST	TATUS	ENGINE DISPLACEMENT	
1 SFI, EGR, EGRC, WR-HO2S, TWC(2), HO2S						FU		ALL MODELS		
* *						PAR	PARTIAL *		1.5	
*			*				PARTIAL WITH *			
	-	EV	APORATIVE &	REFUELING	G (EVA	P/ORVR) FAMILY	INFORMATION		
EVA	P / ORV	R FAMILY	EVAPORATIVE	STD CATE	GORY	E		SSION STD	SPECIAL FEATURES	
K	TYXRO	95P12	EV 2 PC				c	HCT		
			1	EMISSION C	REDIT	INFORM	MATION			
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR ZERO-EVA						ZEV NMOG CREDIT FOR DO		REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS	
N N						N			N	
			NMOG	AND FLEE	TAVE	RAGE IN	FORMA	TION		
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO				LDT	+NOX FLEET ST (3751 LVW-8500 R) + MDPV (g/mi)	D NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10	0.002		0.072			0.083	*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)

CALIFORNIA AIR RESOURCES BOARD

TOYOTA MOTOR CORPORATION

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 6 day of August 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

R	A								A MOTOR		٩			Cars, Li	edium-Du	005 Trucks and ty Vehicles age 3 of 4	
							A	TTAC	HME	NT							
	EXH	HAL	IST	ANDE	VAPO	RATIV	EEMIS	SSION	STAND	ARE	S AND	CERT	FIC	ATION	LEVEL	S	
		-	-	USTEMI						-							
	F	FUEL TYPE		mon adju ORV 1000	oxide; N stment f 'R [g HC	Ox: oxid actor; 21 C/gallon	des of nit DHS/3DI dispense	trogen; H HS [g HC ed]: on-b	ICHO: for C/test]: 2/3 oard refu	malde 3 days eling v	ehyde; P s diurnal vapor ree	M: particu +hot-soak	gram	natter; R g HC/mi ; mg: mi	HC; CO: c RAF: react]: running Iligram; m al FTP	ivity loss;	
				NMOG- (g/m				CO (g/mi)		NOx (g/mi)		HCH (mg/r		-		PM /mi)	
				CE	RT			CERT ST		RT	STD	CERT		STD	CERT	STD	
FTP@50	OK	1	*		*	*	+	+		*	+	+		*	+	*	
FTP@U	G	IER		100	060	0.030	0.05	5 1.	0	*	+	*	* 4		0.0001	0.003	
50°F @4	4K		+		+	*	+	+		*	+	*		*			
					FL	JEL TYP	F			N	NOG+NO	Ox (g/mi)			CO (g/m	i)	
										CERT		STD		CER	T	STD	
HWFET	T@ 50	K				*				*		*	*				
HWFE	T@U	L		(GASOLI	NE-TIE	R3 E10		-	0.0040		0.030	0.030				
20°F @ 50K COLD CO E10 REGULAR GASO					ASOLIN	E (TIE	R3)					1.1	6	10.0			
		-		SFT	EXHA	USTEN	ISSION	STAND	ARDS A	ND CI	ERTIFIC	ATION L	EVEL	S			
							US06				SC03			CC	MPOSIT	E	
	FUEL	LTY	PE	1	MOG+ (g/mi		CO (g/mi)		PM N g/mi)		6+NOx mi)	CO (g/mi)		DG+NO g/mi)	K CO (g/mi	PM (mg/mi	
-		*		CERT	RT +		*			1		*					
@4K				STD	*		*	+				+			+		
				CERT			* 0.		.4 *			+		.0060	0.12	+	
@ UL	UL GASOLINE TIER3 E1		- 1	STD			*	* 6		,		*	0.090		4.2	+	
				BIN									0	.020			
			WHO	OLE VEH	ICLE E								ATIO	N LEVE	LS		
EVAPORATIVE			UEL TYPE					1	2DHS (g/test) @ UL			_	RL (g/mi) @ UL				
FAMILY										FEL		CERT		CTD.			
KTYXR0095P12		GA	ASOLINE -			STD	FEL +	0.267		STD 0.65	+	-	0.0		STD 0.05		
	_			INLEADED	_						_					_	
C	DRVR	/ FUI	EL C	ONLY / CA	NISTER	RBLEE	DEVAP	ORATIV								ELS	
EVAPORATIVE			(ORVR (g/gallon) @ UL			-	3DH			HS RIG TEST		2DHS RIG TES (g/test) @ UL				
FA	MILY		FU	EL TYPE	CERT	STD	FUE	FUEL TYPE		(g/test) @		CERT	-	STD	CERT	STD	
KTYXR0095P12			-	OLINE -		1	1				STD	1	+				

CALI AIR RESO	FORNIA URCES BOARD	TOYOTA MOTOR CORPORATION	Executive Order: A-014-1005 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4			
EFFECTIV	'E LEAK DIAMETER	STANDARD AND CER	TIFICATION LEVEL (IN	CHES)		
EVAPORATIVE FAMILY	LEAK FAMILY	CERT		STD		
*	*	*		*		
B500#ALVW; MDV: medium-c duty passenger vehicle; HDV: emission limit; GVWR: gross v ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidia heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt dr direct/indirect fuel injection; TC ines on-board diagnostic; DO suffix: series; CNG/LNG: comp E10: "10%" ethanol ("90%"gas continuously variable transmis automated manual-selectable hybrid electric vehicle	heavy-duty vehicle; EC vehicle weight rating; LV per ULEV; ZEV: zero-en AC: HC adsorbing cata selective catalytic redu zer; DPF: diesel particu (O2S or AFS: wide rang or, NH3S: ammonia sel riven)/(electric driven); f C/SC: turbo/super charg R: direct ozone reducin pressed/liquefied natura soline) fuel; A: automati ssion; SCV: selectable of	CS: emission control system VW: loaded vehicle weight; nission vehicle; TZEV: trans lyst; WU: warm-up catalyst; action-urea/ammonia; NH3C late filter (active); GPF: PM e/linear/heated air-fuel ration nsor; EGR: exhaust gas reac PAIR: pulsed AIR; SFI/MFI: ger; CAC: charge air cooler ng; HCT: hydrocarbon trap; al gas; LPG: liquefied petron c (with lockup); M: manual continuously variable transr	a; CERT: certification; STD: ALVW: adjusted LVW; LEV sitional ZEV; TWC/OC: 3-wa NAC: NOx adsorption cata OC: ammonia oxidation cata filter for spark-ignited engir o sensor; NOXS: NOx sense circulation; EGRC: EGR coo sequential/multiport fuel inj ; FFH: fuel fired heater; F/P BCAN: bleed carbon canist leum gas; E85: "85%" ethar transmission; SA: semi-auto nission; AM: automated ma	standard; FEL: family : low emission vehicle; ay/oxidizing catalyst; lyst; SCR-U or lyst; CTOX/PTOX: he; HO2S/O2S: br; PMS: PM sensor; bler; AIR/AIRE: ection; DFI/IFI: /\$: full/partial/partial with er; prefix 2: parallel; (2) hol (*15%"gasoline) fuel; bratic transmission; CV: ruual transmission; AMS:		

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
TOYOTA	PRIUS C	PC	1.5	CV1	KTYXR0095P12	1	F