

TOYOTA MOTOR CORPORATION

Executive Order: A-014-0999

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

| | | | | TEST GR | OUP INFO | RMATION | | | | |
|---|----------------|--------------|-------------|---------------------------------------|-----------|--|----------------------|--------------------------------------|--|--|
| MODE | _ | EST GROUP | | VEHICLE CLASS(| ES) | FUEL C | ATEGORY | FUEL TYPE | | |
| 2019 | 9 KTYXV05.0M5A | | | PC | 3 22 | | SINGLE FUEL | GASOLINE | | |
| | USEFUL | LIFE (miles) | | VEHICLE EMIS | SION CAT | EGORY | INTERIM / INT | ERMEDIATE IN-USE STD | | |
| EXH/ORVR EVAP | | | | FTP | S | SFTP FTP | | SFTP | | |
| 150000 150000 | | 0 | LEV3 ULEV70 | ULEV70 LEV 3 COM | | PM | PM | | | |
| SPE | CIAL FE | | CHAUST E | MISSION CONTRO | OL | OBD S | TATUS | ENGINE DISPLACEMENT | | |
| 1 | DF | I, SFI, 2WR | -HO2S, 2 | TWC(2), 2HO2S | | FULL | * | | | |
| * | | | * | | | PARTIAL | ALL MODELS | 5.0 | | |
| * | | | * | , , , , , , , , , , , , , , , , , , , | PA | RTIAL WITH | * | | | |
| | | E | VAPORA | TIVE & REFUELING | G (EVAP/O | RVR) FAMILY | INFORMATION | | | |
| EVA | P / ORV | R FAMILY | EVAPO | RATIVE STD CATE | GORY | | SSION STD E CLASS | SPECIAL FEATURES | | |
| KTYXR0165P12 | | | | LEV 2 | | F | PC | HCT | | |
| | | | | EMISSION O | CREDIT IN | FORMATION | | | | |
| NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON ZERO-EVAP | | | | | | NMOG C | REDIT FOR DOR | OPTIONAL EXH. STD FOR WORK TRUCKS | | |
| N N | | | | | | | N | N | | |
| | | | | NMOG AND FLEE | T AVERA | GE INFORMA | TION | | | |
| NMOG CH4 RAF NMOG/NMHC RATIO | | | PC+LDT | OX FLEET (0-3750 L\ (g/mi) | (W) LDT | +NOX FLEET ST (3751 LVW-8500 R) + MDPV (g/mi | | | | |
| * | * | 1.10 | 0.0 | 06 | 0.072 | | 0.083 | * | | |

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



TOYOTA MOTOR CORPORATION

Executive Order: A-014-0999

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

day of April 2018.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

1 c 11/10/1

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



KTYXR0165P12

TIER 2

UNLEADED

0.257

0.50

TOYOTA MOTOR CORPORATION

Executive Order: A-014-0999 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

| 7/2 - | EXH | AUS | TAN | D EVA | PORA | TIVE | EMIS | SION | STAN | IDARI | DS AN | D CED | TIEIC | ATION | LEVEL | | |
|-------------------------|----------------|-----------------------|-----------|---|---------------------|----------|--------------|------------|--------------------|---------------|--------|---------|-----------------|-----------------|--------------|-------------|--|
| | . 6-14 | EXI | HAUST | EMISS | ION ST | ANDAR | DS AN | ID CER | RTIFICA | TION | EVEL S | (FTP H | WEET | FO°E 20 | LEVEL | 5 | |
| | FU | FUEL TYPE | | T EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP | | | | | | | | | | | | | |
| | | | | NMOG+NOx (g/mi) | | | CO (g/mi) | | | NOx (g/mi) | | | HCHO (mg/mi) | | PM (g/mi) | | |
| | | | | CERT | ST | D | CERT | ST | D | CERT | STE | CEF | RT | STD | CERT | STD | |
| FTP@5 | | * | | * | , | | * | * | | * | * | * | | * | * | * | |
| FTP@UL LEV3 E10 PREM | | 10 | 0.0323 | 0.0 | 70 | 0.08 | 1. | 7 | * | * | * | | 4 | * | 0.003 | | |
| 50°F @4 | 4K | * | | * | * | W | * | * | | * | * | * | | * | 70 - a. m.a. | | |
| | | | | FUEL TYPE | | | | | NMOG+NOx (g/mi) | | | | CO (g/mi) | | | | |
| | | | TOEL TIPE | | | | | CERT STD | | | | | STD | | | | |
| HWFET @ 50K | | | | * | | | | | | * | | * | | | | | |
| HWFET @ UL | | | | GASOLINE-LEV3 E10 PREM | | | | | | 0.00 | 041 | 0.07 | 0 | 3 7 7 7 7 | 50.00 | | |
| 20°F (| @ 50K | C | OLD C | O E10 I | PREMIU | M GASO | DLINE | (TIER | (3) | 7 | | Arast 1 | (42) | 0.59 | | 10.0 | |
| | | 714. | | SFTP EX | HAUST | EMISS | SION S | TANDA | ARDS | AND CE | RTIFIC | ATION L | EVEL | S | | | |
| Control of | | 5.0 | | | US06 | | | | | SC03 | | | 100 | COMPOSITE | | | |
| | FUEL 1 | JEL TYPE | | 200 | G+NOx J/mi) | | CO /mi) | PI (mg/ | | NMOG- (g/n | | Ox CO N | | OG+NOx g/mi) | CO (g/mi) | PM (mg/m | |
| @ 4K | * | * C | | CERT | | | | * | | | * | | * | | | | |
| | | | | | * | | * | 1,5 | · · · · · | * | * * | | | 5.6 | | | |
| | | SOLINE- EV3 E10 ST | | Г | * | The same | * | * | | * | | * | 0 | .0213 | 0.10 | * | |
| @ UL | LEV3 | | | | * | | * | | | * | | * | 0 | .090 | 4.2 | * | |
| | | | BIN | | | | | | | | | | | .080 | | | |
| | | WH | OLE V | EHICLE | EVAPO | | | | | | | | ATIO | LEVELS | | | |
| | | | | | WHOLE VEHICLE EVAPO | | | | | | | | | | | | |
| | RATIVE VILY | LIILI TVBE | | _ | 3DHS (g/test) @ UL | | | | 2DHS (g/test) @ UL | | | | RL (g/mi) @ UL | | | | |
| | | - | | | CERT | STD | F | EL | CER | T STD | | FEL | | CERT | | STD | |
| KTVXD0165D12 | | | ASOLI | NE - | | | | | | | | | | | | | |

0.65

0.005

0.05



TOYOTA MOTOR CORPORATION

Executive Order: A-014-0999

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

| | | | | FUEL ONLY EVAP & CANISTER BLEED | | | | | | | | |
|---------------------------------------|----------------------|------------|-------|---------------------------------|-------------------|-------------------|---|----------|--------------------------------------|-----|--|--|
| EVAPORATIVE FAMILY | ORVR (g/gallon) @ UL | | | FUEL TYPE | 3DHS R (g/test | IG TEST) @ UL | 2DHS RI (g/test | | BLEED CANISTER TEST (g/test) @ 4K | | | |
| I AMIL I | FUEL TYPE | CERT | STD | VILLEY OF THE | CERT | STD | CERT | STD | CERT | STD | | |
| GASOLINE KTYXR0165P12 TIER 2 UNLEADED | | 0.014 | 0.20 | | * | * | 20 10 20 10 10 10 10 10 10 10 10 10 10 10 10 10 | * | * | • | | |
| , , , , , , , | EFFECTIVE | LEAK D | IAMET | ER STANDAR | D AND CE | RTIFICA | TION LEV | EL (INCI | HES) | | | |
| EVAPORATIVE FAMILY | | LEAK FAMIL | | Y CERT | | | | STD | | | | |
| * | | * | | ALA SI | 1 | | | | * | | | |

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVVR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI; sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

| | 2019 MODEL | YEAR: VE | HICLE M | ODELS INF | ORMATION | | |
|-------|------------|-----------|------------|------------|--------------------|-----|-----|
| MAKE | MODEL | VEH CLASS | ENGINE (L) | TRANS TYPE | EVAPORATIVE FAMILY | EXH | OBD |
| LEXUS | GS F | PC | 5.0 | SA8 | KTYXR0165P12 | 1 | P |
| LEXUS | RC F | PC | 5.0 | SA8 | KTYXR0165P12 | 1 | P |