

NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0809

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP INF	ORMAT	ION					
	MODEL YEAR TEST GROUP			VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2019	019 KNSXT03.5N7B			LDT2				DEDICATED SINGLE FUEL VEHICLE			GASOLINE		
- (JSEFUL	LIFE (miles)		VEH	ICLE EMIS	SION CA	TEGOR	RY	INTERIM / IN	TEF	RMEDIATE IN-USE STD		
EXH/ORVR EVAP			5,173	FTP			SFTP FTP			Ų,	SFTP		
150000 150000			0	LEV3	ULEV125	LEV125 LEV 3 COM		SITE *			in made order the		
SPE	CIAL FE	ATURES & EX	(HA		ON CONTRO	DL	12.5	OBD S1	TATUS	E	ENGINE DISPLACEMENT		
1	2TWC, 2WR-HO2S, 2HO2S, TWC, DFI						FULL ALL MODELS				A STATE OF S		
*	*							PARTIAL *					
*									AL WITH *				
		E	VAF	ORATIVE &	REFUELING	G (EVAP	ORVR)	FAMILY	INFORMATION	١			
EVA	P / ORV	R FAMILY	E١	/APORATIVE	STD CATE	GORY		AP EMIS	SSION STD CLASS		SPECIAL FEATURES		
KNSKR0120PBC				Li	LEV 2			LDT2			*		
	1			E	MISSION C	REDIT II	NFORM	IATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY					REDIT FOR NON-PZEV ZERO-EVAP			NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
N N							N				N		
				NMOG	AND FLEE	T AVER	AGE IN	FORMAT	TION				
NMOG CH4 RAF NMOG/NMHC RATIO			CHO/NMHC RATIO	C NMOG+NOX FLEET S PC+LDT (0-3750 LV (g/mi))	MDV (10,001-14,000			
*	*	1.10	1.10. * 0.072					0.083 *					

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0809 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

day of April 2018.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



UNLEADED

NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0809

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	EXH	SHARE CHARLES	STATISTICS OF THE PARTY OF THE	-	-	Maria de la Companione				_		CERT				S		
1		EXH										(FTP, HW						
	FUI	EL TY	r	nonoxi adjustm DRVR	ide; No nent fa [g HC	Ox: oxid actor; 20 /gallon (les of nit DHS/3DH dispense	rogen; H HS [g HC d]: on-bo	CHO: /test]: pard re	formal 2/3 da fueling	dehyde; F ys diurnal g vapor re	bon; NMF M: particu +hot-soak covery; g: ure; SFTF	ilate ; RL gran	matter; R [g HC/mi] n; mg: mil	AF: reacti : running ligram; m	vity loss:		
					OG+N (g/mi)		(CO g/mi)			NOx g/mi)		HCH mg/r			M mi)		
		y 5		CERT	Т	STD	CERT	ST	D	CERT	STD	CER	T	STD	CERT	STD		
FTP@5	0K	*		*		*	*	*		*	*	*		* (1)	*	*		
FTP@L	11 1	OLIN V3 E		0.03	2 (0.125	0.4	2.	1	*	*	*		4 *		0.01		
50°F @	4K	*		*		*	*	*		*	*	*		*		Anton Pri		
			2 1	FUEL TYPE						NMOG+NOx (g/mi)				CO (g/mi))		
										CERT		STD	STD		CERT			
HWFE	Г @ 50K			*						* Section 1								
HWFET @ UL				GASOLINE-LEV3 E10					9 3 - 1	0.013 0.1		0.125	5					
20°F @ 50K COLD CO E10 REGULAR GA					ASOLINE	C (TIEF	3)					1.2		12.5				
			5	FTP E	XHAU			STAND	ARDS	AND	CERTIFIC	ATION L	VEL		y			
		in Alberta					US06			SC03					MPOSITE			
	FUEL T	UEL TYPE		TYPE		NMOG+N (g/mi)							G+NOx g/mi)	CO (g/mi)	NMOG+NOx (g/mi)		CO (g/mi)	PM (mg/mi
@ 4K		CEF		16	*		*				*	*						
			STD		*		*	A. P. Park			*	*						
		ASOLINE- LEV3 E10 B			*		*	,	k		*	*	(0.030	0.7	*		
@ UL					*		*	,	k		*	*	- (0.090	4.2	*		
														0.110				
		WH	HOLE V	EHICL	E EV							ERTIFIC	ATIO	N LEVEL	.S			
EVA D	OD 4 TIV	_				W	HOLE VI	EHICLE	EVAP	ORAT	IVE TEST	ING			((i) - 6			
	ORATIVI MILY	FUEL TYPE		YPE	3DHS (g/test) @ UL					2DHS (g/test) @ l		@ UL	UL		RL (g/mi) @ UL			
					CEF	RT S	STD	FEL	CE	RT	STD	FEL		CER	Т	STD		
KMCADUIJUDBU		ASOLI A PHA		0.4	6 0	. 65	*	0.	44	0.85	*		0.00	0	0.05			
C	RVR / F	UEL	ONLY	CANI	STER	BLEED	EVAPO	RATIVE	EMIS	SSION	STANDA	RDS AND	CE	RTIFICAT	ION LEV	ELS		
														ER BLEED				
EVAPORATIVE FAMILY		E ORVR (g/gal			Ion) @	g UL	FUEL TYPE			3DHS RIG TEST (g/test) @ UL		2DHS RIG (g/test) @				CANISTER (g/test) @ 4K		
		FL	JEL TY	PE C	ERT	STD			CE	RT	STD	CERT		STD	CERT	STD		
KNSXR	0120PB	c	SOLINI TIER :	2 0	.13	0.20		*		*	*	*		*	*	*		



NISSAN MOTOR COMPANY, LTD.

Executive Order: A-015-0809

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE	LEAK DIAMETER STAN	DARD AND CERTIFICATION L	EVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
* ************************************	77.00.100		Control of the second s

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor, PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH; fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA; semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

	2019 MODEL Y	EAR: VE	HICLE M	ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
NISSAN	PATHFINDER 4WD	LDT2	3.5	CV1	KNSXR0120PBC	1	F