CALIFORNIA AIR RESOURCES BOARD
AIR RESOURCES BOARD

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	OUP IN	FOR	MATION					
MODE	I TI	EST GROUP		VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE			
2019	) KH	NXT03.5RX4		LDT2, LDT3				DICATED SINGLE FUEL VEHICLE			GASOLINE		
	USEFUL	LIFE (miles)		VEHICLE EMISSION CATEGORY				GORY	INTERIM / INTERMEDIATE IN-USE ST				
EX	I/ORVR	EVAP			FTP		SF	ТР	FT	P	SFTP		
1!	50000	150000	)	LEV3	ULEV125	LEV	3 C(	MPOSITE	*			*	
SPE	ECIAL FE	ATURES & EX	HAUS		ON CONTRO	L		OBD S	OBD STATUS		ENGINE DISPLACEMEN (L)		
1	2WU-I	WC, TWC, 2W	R-HO2	S, 2HO2S	S, EGR, DF	I		FULL	+				
*					F	ARTIAL	ALL MODE	LS		3.5			
*					PAF	TIAL WITH	*						
		E	VAPO	RATIVE &	REFUELING	G (EVA	P/OR	VR) FAMIL	INFORMA	TION			
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
:	KHNXR01	461FA		L	LEV 2 LDT2					*			
		· · · · · · · · · · · · · · · · · · ·		l	EMISSION C	REDI							
	REDIT FO	X FLEET AVE. OR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP		ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							N N				N	
				NMOG	AND FLEE	T AVE	RAG		TION				
					NMOG+NO PC+LDT (			V) LDT	+NOX FLEE (3751 LVW-1 R) + MDPV (	8500		MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.10		0.05	. 0	0.072			0.083			*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



HONDA MOTOR CO., LTD.

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-023-0704 dated February 28, 2018.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of May 2018.

FCR Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

R	A	C	ALI RESC	FO	RNI. s boar	A	IONDA M	IOTOR OTD.	CO.,	,	E New Pass		rs, Lig	dium-Duty	rucks and	
						A	TTAC	HME	NT							
	EXH	AUS		DEVAR	ORAT	VE EMI	SSION	STAN	DAR	DS ANI	CERT	IFICAT	IONL	EVELS	1	
		EXH	AUST	EMISSIC	ON STAN	IDARDS	ND CER	TIFICA	TION	EVELS	(FTP, HW	/FET, 50	°F, 20°	F)		
collected for	FU	EL TY		monoxide adjustme ORVR [g	e; NOx: o nt factor; HC/gallo	MOG: non xides of n 2DHS/3D on dispens grees Fah	itrogen; H HS [g HC ed]: on-bo	CHO: fo /test]: 2 pard ref	/3 day ueling	lehyde; F s diurnal vapor re	M: particu +hot-soak covery; g:	ulate mat ; RL [g H gram; m	ter; RA C/mi]: g: millig	F: reactiv running k gram; mi:	ity oss;	
			ł		G+NOx /mi)		CO (g/mi)		-	lOx /mi)	1	HCHO (mg/mi)		Pl (g/r		
				CERT	STD	CER	T ST	DC	ERT	STD	CER	TS	D	CERT	STD	
FTP@50	ж	*		*	*	*	*		*	*	*			*	*	
FTP@U	L	SOLIN V3 E		0.0614				_	*	*	0.7		1	*	0.01	
50°F @4	ŧΚ	*		*	*	*	*		*	*	*					
	*				FUEL T	YPE		ł	NMOG+NOx (g/mi)			CERT	CO (g/mi)			
HWFET @ 50K *							*			310			-	510		
	-	-		<b>63.6</b>						0364	0.12	-	-	1.15		
	T@UL					EV3 E10			0.0	304	0.12:					
20°F (	@ 50K					O LOW O							0.71		12.5	
	SFTP EXHAU					UST EMISSION STANDARDS				AND CERTIFICATION LEVE			COMPOSITE			
1		TYPE		NMOG+NOx		US06	CO PM		NMOG+NOx		со	NMOG+NOx		CO	PM	
	TOLL				/mi)	(g/mi)		j/mi)	(g/mi)		(g/mi)	(g/mi)		(g/mi)	(mg/mi	
@ 4K	*	+		т	*	*		1-1-		*	*				-	
			STD		*	*	•			*	*				1	
	UL GASOLII		CER	Т	*	*	-	* .		*	*	0.05	596	0.34	*	
@ UL			STD		+ .	*		*		*	*	0.0	90	4.2	+	
			BIN					11				0.1	00			
		W	HOLE	VEHICLE	EVAPO	RATIVE						ATION L	EVELS	S		
-		_		-		WHOLE	VEHICLE	EVAPO	ORATI	VE TEST	ring		DI	(m/mi)		
	ORATIV		FUEL 1	YPE	3DHS	(g/test)	/test) @ UL		2DHS (g/test) @		@ UL		KE (9/		mi) @ UL	
		_			CERT	STD	FEL	CER	RT STD		FE	L	CERT		STD	
KHNXR01461FA		A	A PHA	HASE 2		0.65	*			0.85						
C	RVR / I	UEL	ONLY	/ CANIS	TER BLE	ED EVAR	ORATIV							ON LEVE	ELS	
	ORATIV	E	ORVR (g/gallon) @ UL				3D					RIG TES	T E		ED CANISTER	
FA	MILY	F	JEL. T	PECF	RT ST		-		g/test) @ UL RT STD		CERT	st) @ UL			(g/test) @ 4K	
KHNXR01461FA		GA	SOLIN TIER	E -	008 0.1		+	*		*	. *	t Std +		*	*	

CALIF AIR RESOU	ORNIA IRCES BOARD	HONDA MOTOR CO., LTD.		Executive Order: A-023-0704-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4		
EFFECTIVE	LEAK DIAMETER	R STANDARD AN	ID CERTIF	FICATION LEVEL (INCHES)		
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	STD		
*	*		*	•		
emission limit; GVWR: gross ve ULEV: ultra LEV; SULEV: supe ADSTWC: adsorbing TWC; HA SCRC/SCR-N or SCRC-NH3: s continuous/periodic trap oxidize heated/oxygen sensor; WR-HO RDQS: reductant quality sensor secondary air injection (belt driv direct/indirect fuel injection; TC/ fines on-board diagnostic; DOR suffix: series; CNG/LNG: compr E10: "10%" ethanol ("90%"gaso continuously variable transmiss	ahicle weight rating; L ar ULEV; ZEV: zero-er C: HC adsorbing cata selective catalytic redu- er; DPF: diesel particu- 22 or AFS: wide rang r; NH3S: ammonia se ven)/(electric driven); /SC: turbo/super char R: direct ozone reducir ressed/liquefied natur pline) fuel; A: automat sion; SCV: selectable	W: loaded vehicle mission vehicle; TZ alyst; WU: warm-up uction-urea/ammon ulate filter (active); C ge/linear/heated air- ensor; EGR: exhaus PAIR: pulsed AIR; ger; CAC: charge a ng; HCT: hydrocarb ral gas; LPG: liquefi ic (with lockup); M: continuously variab	weight; ALN EV: transitio catalyst; NA ia; NH3OC: SPF: PM filte fuel ratio se t gas recircu SFI/MFI: sec ir cooler; FF on trap; BC/ ed petroleur manual tran le transmiss	ERT: certification; STD: standard; FEL: family VW: adjusted LVW; LEV: low emission vehicle; onal ZEV; TWC/OC: 3-way/oxidizing catalyst; AC: NOx adsorption catalyst; SCR-U or ammonia oxidation catalyst; CTOX/PTOX: er for spark-ignited engine; HO2S/O2S: ensor; NOXS: NOx sensor; PMS: PM sensor; ulation; EGRC: EGR cooler; AIR/AIRE: quential/multiport fuel injection; DFI/IFI: FH: fuel fired heater; F/P/\$: full/partial/partial with AN: bleed carbon canister; prefix 2: parallel; (2) m gas; E85: "85%" ethanol ("15%"gasoline) fuel; nsmission; SA: semi-automatic transmission; CV: sion; AM: automated manual transmission; AMS: ic range; EAER: equivalent AER; PHEV: plug-in		

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
HONDA	RIDGELINE AWD	LDT3	3.5	A6	KHNXR01461FA	1	P
HONDA	RIDGELINE AWD (ADAPTIVE CRUISE CONTROL)	LDT3	3.5	A6	KHNXR01461FA	1	P
HONDA	RIDGELINE FWD	LDT2	3.5	A6	KHNXR01461FA	1	P

1.1.