

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FOR	NOITAN				
MODE		EST GROUP	VEHI	VEHICLE CLASS(ES)			FUEL C	ATEGORY	FUEL TYPE		
2019	KI	NSXV01.6N4A		PC				SINGLE FUEL HICLE	GASOLINE		
	USEFUI	L LIFE (miles)		HICLE EMIS	SION	ATEG	ORY	INTERIM / INT	ERMEDIATE IN-USE STD		
	ORVR			FTP			ГР	FTP	SFTP		
15	0000	15000	0 LEV	3 ULEV125	LEV	3 CO	MPOSITE	*	*		
SPE	CIAL FI		HAUST EMISS	SION CONTRO	DL		OBD S	TATUS	ENGINE DISPLACEMENT (L)		
1	1 TWC(2), HO2S, WR-HO2S, SFI						FULL	*			
*	• •						ARTIAL	ALL MODELS	1.6		
*			*	5			TIAL WITH				
		E	VAPORATIVE	& REFUELING	G (EVA	P/OR	R) FAMILY	INFORMATION			
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGORY						EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
K	NSXR00	87PCA	TION2 WITH	N2 WITH FEL PC				*			
		d.		EMISSION C	REDIT	T INFO	RMATION				
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY								REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
N N								N	N		
			NMO	G AND FLEE	TAVE	RAGE	INFORMAT	TION			
MOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO	RATIO RATIO NMOG+NOX FLE PC+LDT (0-375 (g/mi)) LDT (NOX FLEET STI 3751 LVW-8500 ₹) + MDPV (g/mi)	NMOG+NOX FLEET STC MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	*		0.072			0.083	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 3019 day of July 2018.

Emissions Compliance, Automotive Regulations and Science Division

CALIFORNIA AIR RESOURCES BOARD							NISSAN MOTOR COMPANY, LTD.			D. Medium-Duty Vehic							
NIC	117	AIF	RES	OURC	ES B	OARC									F	age 3 of 4	
							A	ТАС	CHME	ENT		•					
	EXH	IAUS	TAN	DEVA	POP	RATIV	E EMIS	SION	STAN	DAR	DS AN	D CERT	IFIC	ATION	LEVEL	.S	
		EXI	HAUST									(FTP, HV					
	Fl	FUEL TYPE		CH4: methane; NMOG: non-CH4 organi monoxide; NOx: oxides of nitrogen; HCF adjustment factor; 2DHS/3DHS [g HC/te ORVR [g HC/gallon dispensed]: on-boan 1000 miles; F: degrees Fahrenheit; FTP:						ormal 2/3 da fueling	dehyde; l ys diurna y vapor re	PM: partic I+hot-soal covery; g	ulate k; RL gran	matter; F [g HC/mi n; mg: mi	RAF: read]: running Iligram; n	tivity loss;	
				NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HCHO (mg/mi				PM (g/mi)	
				CERT	r	STD	CERT	ST	DO	CERT	STE	CER	т	STD	CERT	STD	
TP@5		*		*		*	*	*		*	*	* *		*	*	*	
FTP@L		ASOLI EV3 I		0.01	8	0.125	0.6	2.	1	*	*	* *		4	*	0.01	
0°F @4	ŧK	*		*		*	*	*		*	*			*			
					FU	EL TYP	Έ			MOG+NOx (g/mi)			CO (g/mi)				
									CER *		STD	_	CER	T	STD		
HWFET @ 50K * .						•	1						-				
HWFET @ UL GASOLINE-:						3 610		0.	.007	0.12	5						
20°F @ 50K COLD CO E10 REGULAR GASOI												1.1		. 10.0			
-		_	-	SFTP E	XHAI		US06	STAND	ARDS /	AND	SC03	ATION L	EVEL		MPOSIT	e	
	FUEL	UEL TYPE						CO PM		M	NMOG+NOx				OG+NO		PM
					(g/mi)		(g/mi)		g/mi)		/mi)	(g/mi)	1	g/mi)	(g/mi		
@ 4K		* CEI		т	*		*	*		*		*					
					*		*		_		*	*				-	
	GASOL THE		CER	Т	*		*		*		*	*	0	.014	1.1	*	
			STD		*		*		*		*	*	0	.090	4.2	*	
		BI											0	.110			
		W	HOLE	/EHICL	E EV							ERTIFIC	ATIO	N LEVEL	.s		
		/=			_	W	HOLE VE	HICLE	EVAPO	RAT	VE TEST	TING		D	(almi)	8 I II	
EVAPORATIVE FAMILY KNSXR0087PCA			GASOLINE- LEV3 E10		3DHS (g/test) @		JL 2		2DHS (g/test) @		@ UL	@ UL		L (g/mi) (UC .		
					CER	RT S	STD	FEL	CER	Т	STD	FEL		CERT		STD	
		CA			0.2	54 0	. 300 0	0.300	0.266		0.300	0.300		0.000		0.05	
0	RVR / I	FUEL	ONLY	CANIS	STER	BLEED	EVAPO	RATIVE				RDS AND	_			ELS	
EVAPORATIVE		/E	ORVR (g/gallon) @ UL					3D			TEST	2DHS			BLEED CANISTER		
				FUEL TYPE CE				FUEL TYPE		g/test) @ UL RT STD					- L - 2 I - UU/	(g/test) @ 4K RT STD	
	MILY	FI	JEL TY	PEC	ERT	STD	FUEL		CER	1		CERT	1	STD	CERT	1	

CALI AIR RESO	FORNIA URCES BOARD	NISSAN MOTOR COMPANY, LTD.	Executive Order: A-015-0821 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4			
EFFECTIV	E LEAK DIAMETER	STANDARD AND CER	RTIFICATION LEV	/EL (INCHES)		
EVAPORATIVE FAMILY	LEAK FAMILY	CER	т	STD		
KNSXR0087PCA	KNSXR0087PCA-02	2E *		0.02		
duty passenger vehicle; HDV: emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidii heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt d direct/indirect fuel injection; Tr fines on-board diagnostic; DC suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"ga continuously variable transmis	heavy-duty vehicle; EC vehicle weight rating; LV per ULEV; ZEV: zero-em AC: HC adsorbing catal selective catalytic redu zer; DPF: diesel particul IO2S or AFS: wide range or; NH3S: ammonia ser riven)/(electric driven); F C/SC: turbo/super chargo R: direct ozone reducin pressed/liquefied natura soline) fuel; A: automati ssion; SCV: selectable of	CS: emission control syste W: loaded vehicle weight hission vehicle; TZEV: tran lyst; WU: warm-up catalys ction-urea/ammonia; NH3 late filter (active); GPF: PI e/linear/heated air-fuel rat nsor; EGR: exhaust gas re PAIR: pulsed AIR; SFI/MF ger; CAC: charge air coole g; HCT: hydrocarbon trap al gas; LPG: liquefied petr c (with lockup); M: manua continuously variable trans	m; CERT: certification ; ALVW: adjusted LV sitional ZEV; TWC/0 it; NAC: NOx adsorp OC: ammonia oxida M filter for spark-ignit io sensor; NOXS: NO ecirculation; EGRC: I I: sequential/multipo er; FFH: fuel fired hea ; BCAN: bleed carbo oleum gas; E85: "85 I transmission; SA: s smission; AM: autom	tion catalyst; SCR-U or tion catalyst; CTOX/PTOX: ted engine; HO2S/O2S: Ox sensor; PMS: PM sensor; EGR cooler; AIR/AIRE:		

2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
NISSAN	VERSA	PC	1.6	CV1 , M5	KNSXR0087PCA	1	P