

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP INF	ORM	ATION					
MOD YEA	1 1	EST GROUP		VEHICI	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE		
201	19 KNSXV02.5RPA PC						DI		SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles) VEHICLE EMIS							TEGO	ORY	INTERIM / IN	TERM	EDIATE IN-USE STD		
EXH/ORVR EVAP				FTP SF			SFT	FTP FTP			SFTP		
150000 150000				LEV3	SULEV30 LEV 3 COM			POSITE NMOG+NOX AND			PM PM		
SP	SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							OBD S	EN	ENGINE DISPLACEMENT (L)			
1	TWC(2), WR-HO2S, HO2S, EGR, EGRC, DFI						F	ULL	*				
*	*						PA	PARTIAL ALL MODELS 2.5					
*	* * PARTIAL FINE								*				
		ε	VAPO	RATIVE &	REFUELING	(EVAP	ORV	R) FAMIL	INFORMATIO	N			
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGO						ORY EVAP EMISSION STD VEHICLE CLASS			SP	SPECIAL FEATURES		
	KNSXR0	114PCB	V 3 OPTION2 WITH FEL				PC			*			
				E	EMISSION C	REDIT I	NFOF	RMATION					
						REDIT FOR NON-PZEV ZERO-EVAP					OPTIONAL EXH. STD FOR WORK TRUCKS		
	NN							N					
NMOG AND FLEET AVERAGE INFORMATION													
	- INMOGINIMISCO I PC+CDL0-3750				0-3750					MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	C	.072			0.083		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of August 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

CALIFORNIA AIR RESOURCES BOARD								NISSAN MOTOR COMPANY, LTD.			Executive Order: A-015-0825 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4								
								A	ТАС	НМ	ENT								
	E	XHA	UST	AN	DEV	APOF	VITAS	EEMIS	SION	STAN	DARC	S AN	CERTI	FIC	ATION	LEVE	ELS		
		E	EXHA										(FTP, HW						
		FUEI	_ TY		CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: ca monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactiv adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running k ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP							activi ng lo	ty ss;						
				ľ	N	MOG+N		1	со		NOx			нсн			PI		
			ł		(g/mi)			(g/mi)		(g/mi)			ng/n		0.55	(g/mi)			
FTP@50			*		CEF		STD *	CERT	STI		CERT	STD	CERT		STD	CER		STD *	
FTP@U	+	GASC		1	0.0	18 (0.030	0.3	1.	0	*	*	·		4	0.001		0.003	
50°F @4	ŧК	GASC		E-	0.0	18 (0.060	0.2	1.	0	*	*	*		8				
					FUEL TYPE						NMOG+NOx (g/mi)				CO (g/m				
											CE	CERT STD			CERT			STD	
HWFET					. *							* *							
HWFE	Т@	UL			GASOLINE-LEV3 E10					0.0	005	0.030							
20°F (@ 5	0K	co	LD C	0 E1	0 REGU	JLAR G	ASOLINE (TIER3)						0.4	0.4 10.0		.0.0		
				;	SFTP	EXHAU			STAND	ARDS	AND C		ATION LE	VEL					
	FUEL TY					US0 NMOG+NOX C			CO PM			SC03	СО	NIRA	CC OG+NO	OMPOS		PM	
						(g/mi)		(g/mi)			NMOG+NO> (g/mi)				(g/mi)		mi)	(mg/mi)	
@ 4K		*		CER	ERT +		*				*	*							
				STD		*		*				*	*			_			
		BASOLINE- LEV3 E10 BI				* *		2			*		* 0.018		0	. 7	*		
@ UL							* 6		6		*	*	0.090		4.2		*		
				BIN											0.040				
			WH	OLE	VEHIC									TIO	N LEVE	LS			
EVAP	ORA							HOLEVE		EVAP					R	L (g/m	i) @	UL	
	MIL				TYPE 3DHS (g/			/test) @ UL		2DHS (g/test)									
			(350)		CERT		रा	STD	STD FEL		RT	STD	STD FEL		_ CEF		r st		
	KNSXR0114PCB GASOLINE- LEV3 E10 0.146							236	6 0.300 0.300 SION STANDARDS AND C			0.000		0.05					
C	RV	R / FU		DNLY	/ CAN	NISTER	BLEE		RATIVE	-			RDS AND				EVE	LS	
EVAP				ORVF	R (g/gallon) @ UL			EUE	3		DEL ONLT EVAP DHS RIG TEST g/test) @ UL				EST BLEED				
	. AUL		FU	ELT	YPE	CERT	STD				ERT	STD	CERT	1	STD	CER		STD	
KNSXR	011	4PCB		SOLI ER3		0.03	0.20		GASOLINE- LEV3 E10		*	*			*	0.01	1	0.020	

CALIFORNIA AIR RESOURCES BOARD	NISSAN MOTOR COMPANY, LTD.	Executive Order: A-015-0825 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4						
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								

EFFECTIV	EFFECTIVE LEAR DIAMETER STANDARD AND CERTIFICATION LEVEL (INCILLS)									
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD							
KNSXR0114PCB	KNSXR0114PCB-09E	*	0.02							

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection: TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater, F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2019 MODEL YEAR: VEHICLE MODELS INFORMATION										
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD			
NISSAN	ALTIMA	PC	2.5	CV1	KNSXR0114PCB	1	P			
NISSAN	ALTIMA SR/PLATINUM	PC	2.5	CV1	KNSXR0114PCB	1	P			