

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GROU	UP INFOR	MATION				
MODE		EST GROUP	VEHIC	LE CLASS(ES	5)	FUEL C	ATEGORY	FUEL TYPE GASOLINE		
2019	KIN	ISXV02.0PVA	11.00	PC			SINGLE FUEL HICLE			
1	USEFUL	LIFE (miles)	VE	HICLE EMISSI	ON CATE	GORY	INTERIM / INTE	RMEDIATE IN-USE STD		
EXH/ORVR EVAP			FTP			FTP	SFTP			
15	150000 150000) LEV3	ULEV70	EV70 LEV 3 COMP		NMOG+NOX AND	PM PM		
SPE	CIAL FE		HAUST EMISSI	ON CONTROL	-	OBD S	TATUS	ENGINE DISPLACEMENT (L)		
1	TWC (2), HO2S, WR-	HO2S, SFI, D	OFI, CAC, TO	-	FULL	*			
*			*		P	ARTIAL	2.0			
*			*			TIAL WITH	ALL MODELS			
		E	VAPORATIVE &	REFUELING	(EVAP/OR	VR) FAMILY	INFORMATION			
EVA	P / ORV	RFAMILY	EVAPORATIV	E STD CATEG	ORY		SSION STD	SPECIAL FEATURES		
K	NSXR01	19PCA	LEV 3 OPT	ION2 WITH F	EL	P	c	*		
				EMISSION CR	EDIT INFO	ORMATION				
	EDIT FO	X FLEET AVE. DR EXTENDED RRANTY	NMOG CI	REDIT FOR NO	ON-PZEV	NMOG C	REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N		N			N	N		
			NMO	G AND FLEET	AVERAG	E INFORMA	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		PC+LDI (U		N) LDT	+NOX FLEET STD (3751 LVW-8500 R) + MDPV (g/mi)	NMOG+NOX FLEET ST MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	*	0.	.072		0.083	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the listed vehicle models produced on or before November 27, 2016 have been determined to have three deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of \$25 per vehicle for the third deficiency for vehicles in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2019 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _____ day of August 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division

A	R		RESO	O				NISSAN COMPA	I MOTOI					er Cars, L	ledium-D	0826 Trucks and uty Vehicles age 3 of 4	
							A	TTAC	HME	NT							
	EXHA	USI	AND	EVA	POR	VITAS	EEMIS	SION	STANE	DAR	DS AN	D CERT	IFIC	ATION	LEVEL	S	
		EXH	AUST E	MISSI	ON S	TAND	ARDS A	ND CER	TIFICAT	ION	EVELS	(FTP, HI	VFET	, 50°F, 2	0°F)		
	FUE	m ac O		monoxide; NOx: oxi adjustment factor; 2 ORVR [g HC/gallon 1000 miles; F: degre				DG: non-CH4 organic ga des of nitrogen; HCHO: f DHS/3DHS [g HC/test]: dispensed]: on-board re ses Fahrenheit; FTP: fed			ehyde; f s diurna vapor re	PM: partic I+hot-soa covery; g	ulate k; RL : grar	matter; f [g HC/m n; mg: m	RAF: read i]: running illigram; r	tivity loss;	
				NMOG+NOx (g/mi)			CO (g/mi)			NOx (g/mi)		HCł (mg/				PM g/mi)	
				CERT		STD	CERT	T ST	DC	ERT	STD	CE	रा	STD	CERT	STD	
FTP@50	<	*		*		*	*	*		*	*			*	*	.*	
FTP@UL	LEV	3 E	10	. 027	0	0.070	0.1	1.	7	*	*.	*		4	0.001	0.003	
50°F @4k		OLIN 3 EI		. 030	0	.140	0.2	1.	7	*	*			16			
	1									N	MOG+N	Ox (g/mi)		CO (g/n	ni)	
-					FU	EL TYF	'E			CE	RT	STD	1	CER	RT .	STD	
HWFET @ 50K *								•		*	*						
HWFET	@ UL			GAS	SOLI	NE-LEV	73 E10			0.007		0.07	0.070				
20°F @	50K	CC	DLD CO	E10	REGU	LAR G	ASOLIN	E (TIEF	23)	1				0.1	8	10.0	
		_	SF	TP E	XHAL		ISSION	STAND	ARDS A	ND C	ERTIFIC		EVE	LS			
							US06				SCOS		T		MPOSIT	E	
F	FUEL T	UEL TYPE		E NMOG+NOx (g/mi)					M i /mi)		G+NOx J/mi)	CO (g/mi)	NN	IOG+NO (g/mi)	x CO (g/m	PM i) (mg/mi	
@ 4K	*		CERT *				*				*	*					
			STD		*		*	-			*	*	-				
	GASOLI	CERT	-	*		*	-	4		*	*		0.025	. 0.2			
		LEV3 E10 ST		1	*		*		6		*	*		0.090	4.2	*	
			BIN							-				0.090			
		WH	OLE VE	HICL	EEV							CERTIFIC	ATIC	DN LEVE	LS		
EVAPO								EHICLE						-	L (g/mi)	രല	
FAN								CER	2DHS (g/test) @ U RT STD			FEL CEF					
KNSXR0	119PCA	CA GASOL		LINE-		.300 0.300		0.23	-	0.300		0.300		00	0.05		
OF	RVR / FL	JEL (ONLY / C	ANIS	TER	BLEED	EVAP	ORATIVE	EEMISS	ION S	TANDA	RDS AN	DCE	RTIFICA	TION LE	VELS	
									FUE	LON	ILY EVA	P& CAN	IISTE	R BLEE	D		
EVAPO			ORVR (R (g/gallon) @ UL			FUEL TYPE			IS RIG TEST /test) @ UL		2DHS RIG (g/test) @				CANISTER (test) @ 4K	
		FUEL 1						CER	T	STD	CERT		STD	CERT	STD		
			SOLINE	-		310		LINE-			310	CER	-	510	UERI	010	

CALI AIR RESO	FORNIA DURCES BOARD	NISSAN MOTOR New Pa COMPANY, LTD.		Executive Order: A-015-0826 Issenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4		
EFFECTIV	E LEAK DIAMETER	STANDARD AND CEP	RTIFICATION	EVEL (INCHES)		
EVAPORATIVE FAMILY	LEAK FAMILY	CER	т	STD		
KNSXR0119PCA	KNSXR0119PCA-13	E *		0.02		
emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidi. heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt d direct/indirect fuel injection; T fines on-board diagnostic; DC suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"ga: continuously variable transmis	vehicle weight rating; LV ber ULEV; ZEV: zero-em IAC: HC adsorbing cataly : selective catalytic reduc zer; DPF: diesel particula IO2S or AFS: wide range sor; NH3S: ammonia sen Iriven)/(electric driven); P C/SC: turbo/super charg DR: direct ozone reducing pressed/liquefied natura soline) fuel; A: automatic ssion; SCV: selectable c	W: loaded vehicle weight hission vehicle; TZEV: trar yst; WU: warm-up catalys ction-urea/ammonia; NH3 ate filter (active); GPF: PM e/linear/heated air-fuel rat hsor; EGR: exhaust gas re PAIR: pulsed AIR; SFI/MF ger; CAC: charge air coole g; HCT: hydrocarbon trap al gas; LPG: liquefied petro c (with lockup); M: manual continuously variable trans	; ALVW: adjusted hsitional ZEV; TV t; NAC: NOx ads OC: ammonia ox d filter for spark- io sensor; NOXS ecirculation; EGR I: sequential/mult r; FFH: fuel fired ; BCAN: bleed ca oleum gas; E85: I transmission; SM: au	kidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: ; NOx sensor; PMS: PM sensor; C: EGR cooler; AIR/AIRE:		
2019	MODEL YEAR:	VEHICLE MOD	ELS INFO	RMATION		

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	0
NISSAN	ALTIMA SR/PLATINUM	PC	2.0	CV1	KNSXR0119PCA	1	

,

.