

HONDA MOTOR CO., LTD.

Executive Order: A-023-0715

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	NID IN	JEOP	MATION					
1405			η		1E31 GRC		TOR	TIA I I O I		Т			
YEA	DEL TEST GROUP			VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
201	9 KI	iNXV01.8EJ3			PC				SINGLE FUEL HICLE		GASOLINE		
USEFUL LIFE (miles)				VEHICLE EMISSION CATEGOR				GORY	INTERIM / IN	TERM	ERMEDIATE IN-USE STD		
EXH/ORVR EVAP					FTP			TP	FTP		SFTP		
1	150000 150000		)	LEV3	ULEV70	LEV 3 COM		MPOSITE	NMOG+NOX A	ID PN	4 PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS					L		OBD S	TATUS	E	ENGINE DISPLACEMENT			
1	WU-TWC, TWC, WR-HO2S, HO2S, EGR, SFI							FULL	*				
*	*						Р	ARTIAL	L ALL MODELS		1.8		
*	*							TIAL WITH	W				
		E	VAP	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y INFORMATIO	N			
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR					GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
KHNXR0106VFB				LEV 2				PC			*		
					EMISSION C	REDI	ΓINF	ORMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY					REDIT FOR NON-PZEV ZERO-EVAP			NMOG CREDIT FOR DOR		R	OPTIONAL EXH. STD FOR WORK TRUCKS		
N				N			И			И			
				NMOG	AND FLEE	Γ AVE	RAGI	E INFORMA	TION				
NMO0 RAF	CH4 RAF	NMOG/NIMORC     PC+  D   /U-3/5				V) LDT	NOX FLEET STD 3751 LVW-8500 R) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	1.10	T	0.05	0.072				0.083		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



HONDA MOTOR CO., LTD. Executive Order: A-023-0715

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

## BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

## BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of June 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



**FUEL TYPE** 

GASOLINE-

TIER3 E10

KHNXR0106VFB

CERT

0.01

STD

0.20

HONDA MOTOR CO.,

Executive Order: A-023-0715

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

## **ATTACHMENT**

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F) CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP **FUEL TYPE** NMOG+NOx CO NOx **HCHO** PM (g/mi) (g/mi) (g/mi) (mg/mi) (g/mi) CERT STD CERT STD CERT CERT STD STD CERT STD FTP@50K GASOLINE-0.070 0.026 FTP@UL 0.4 1.7 0 4 0.001 0.003 LEV3 E10 50°F @4K NMOG+NOx (g/mi) CO (g/mi) **FUEL TYPE** CERT CERT STD STD HWFET @ 50K GASOLINE-LEV3 E10 0.015 0.070 HWFET @ UL 20°F @ 50K COLD CO E10 REGULAR GASOLINE (TIER3) 0.4 10.0 SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS **US06** COMPOSITE SC03 NMOG+NO<sub>X</sub> **FUEL TYPE** NMOG+NOx CO PM CO NMOG+NO<sub>x</sub> PM CO (g/mi) (g/mi) (g/mi) (g/mi) (mg/mi) (g/mi) (g/mi) (mg/mi) CERT \* @ 4K STD \* \* \* CERT \* \* \* \* 0.021 2 0.9 \* GASOLINE-STD + 6 \* + 0.090 4.2 @ UL LEV3 E10 0.080 BIN WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS WHOLE VEHICLE EVAPORATIVE TESTING **EVAPORATIVE** RL (g/mi) @ UL **FUEL TYPE** 3DHS (g/test) @ UL 2DHS (g/test) @ UL **FAMILY** CERT STD FEL CERT CERT STD FEL STD GASOLINE-KHNXR0106VFB 0.37 0.50 0.37 0.65 0.00 0.05 LEV3 E10 ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS **FUEL ONLY EVAP & CANISTER BLEED** ORVR (g/gallon) @ UL 3DHS RIG TEST 2DHS RIG TEST **BLEED CANISTER EVAPORATIVE** (g/test) @ UL (g/test) @ UL TEST (g/test) @ 4K FAMILY **FUEL TYPE** 

CERT

STD

CERT

STD

CERT

STD



HONDA MOTOR CO.,

Executive Order: A-023-0715

New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)							
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD				
* .	*		*				

\*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR; gross vehicle weight rating; LVW; loaded vehicle weight; ALVW; adjusted LVW; LEV; low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV; transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS; wide range/linear/heated air-fuel ratio sensor; NOXS; NOx sensor; PMS; PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

## 2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	ECS	OBD
HONDA	HR-V AWD	PC	1.8	CV1,SCV7	KHNXR0106VFB	1	P
HONDA	HR-V FWD	PC	1.8	CV1,SCV7	KHNXR0106VFB	1	P