

HONDA MOTOR CO., LTD. Executive Order: A-023-0734

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
	ODEL TEST GROUP VEHICLE CLASS						S)		FUEL C	ATEGORY		FUEL TYPE		
201	2019 KHNXV02.0BL2 PC							HYBRID ELECTRIC VEHICLE				GASOLINE		
	USEFU	LIFE (miles)		\top	VEHICLE EMISSION CATEGOR					INTERIM / IN	RMEDIATE IN-USE STD			
EXH/ORVR EVAP					FTP			SF	SFTP FTP			SFTP		
150000 150000					LEV3	EV3 SULEV30 LEV 3 CO			MPOSITE	PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							L	OBD STATUS				ENGINE DISPLACEMENT (L)		
1 TWC, WR-HO2S, HO2S, EGR, EGRC, SFI									FULL *		71			
*	* *							Р	ARTIAL	RTIAL ALL MODELS		2.0		
*									TIAL WITH *					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION													
EV	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						GORY	′	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
KHNXR0121VSA LEV 3 OPTION2								PC			*			
					E	MISSION C	REDI	TINFO	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-I ZERO-EVAP						ON-P	ZEV NMOG CREDIT FOR DOP			R	OPTIONAL EXH. STD FOR WORK TRUCKS			
Y N										N		И		
NMOG AND FLEET AVERAGE INFORMATION														
NMO0 RAF	NMOG/NMEC 1					0-375		LVW) LDT (3751 LVW-8500 MD			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)			
*	* * 1.10 0.05 0.072						.072			0.083		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



HONDA MOTOR CO., LTD. Executive Order: A-023-0734

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of October 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



KHNXR0121VSA

FUEL TYPE | CERT

0.01

GASOLINE-

TIER3 E10

HONDA MOTOR CO., LTD.

Executive Order: A-023-0734 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

STD

CERT

STD

0.020

CERT

0.004

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFIC	ATION LEVELS
---	--------------

-	EXHA	UST	AND	EVA	PORAT	IVE	EMIS	SION S	TAN	NDAR	DS AND	CERT	IFIC	ATION	LEVELS				
		EXH	AUST	EMISS	ON STAN	NDA	RDS A	ND CERT	IFIC/	ATION	LEVELS	(FTP, HW	/FET,	50°F, 20°	°F)				
	FUE	L TY	r á	nonoxio adjustm DRVR [de; NOx: o	xide ; 2D on d	es of nit HS/3DI ispense	rogen; H0 HS [g HC/ ed]: on-bo	CHO: test]: ard re	formald 2/3 day efueling	lehyde; P s diurnal vapor re	M: particu +hot-soak covery; g:	late i ; RL gram	matter; R/ [g HC/mi]: i; mg: mill	C; CO: ca AF: reactive running le igram; mi: I FTP	vity oss;			
						N		NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)				
				CERT	STE		CERT	STE		CERT	STD	CER	T	STD	CERT	STD			
FTP@5	TP@50K			*	*		*	*		*	*	*		*	*	*			
FTD@III		ASOLINE- LEV3 E10		0.016	0.030	10	0.4	1.0	0	*	*	0.4		4	0.001	0.003			
50°F @	4K	*	*		*		*	*		*	*	*		*	100	24.			
	-			FUEL TYPE						NMOG+NOx (g/mi)				CO (g/mi)					
									CERT S			STD CE		T STD					
HWFE'	T @ 50K			*							* *								
HWFET @ UL				GA	SOLINE-	LEV	3 E10			0.004 0.030) .							
20°F	@ 50K	CC	OLD CO	E10	REGULAR	GA	SOLIN	E (TIER	3)				-	0.5		10.0			
				FTP E	XHAUST			STANDA	RDS	AND C			EVEL		UD COLTE				
				NIBR	US06					SC03			AIRA	COMPOSITE MOG+NOx CO PM					
	FUEL	UEL TYPE			g/mi)		CO (g/mi)	(mg/			/mi)	(g/mi)	1	(g/mi)	(g/mi)	(mg/mi			
@ 4K	*			RT +		*			*		*.			-					
			STD		*		*		*		*	*							
				Г	*		*	0.	5		*	*	0.011		0.4	*			
@ UL		GASOLINE- LEV3 E10		1 6111		. *		*	6			*	*		0.090	4.2	*		
	В		BIN	1										0.050					
		WH	OLE \	EHICL	E EVAPO	RA	TIVE E	MISSION	STA	NDARD	S AND	ERTIFIC	ATIO	N LEVEL	S				
						W	HOLE V	EHICLE	EVAF	PORATI	VE TEST	TING							
EVAPORATIV FAMILY				TYPE 3DHS (gr		/test) @ UL			2DHS (g/test) (@ UL	@ UL		RL (g/mi) @ UL					
				CERT S		STD FEL		CE	RT	STD	FEL		CER	T	STD				
KHNXR0121VS		GASOLINE- LEV3 E10			0.202	0.202 0.		300 *		218	0.300			0.00		0.05			
(DRVR / F	JEL (ONLY	CANIS	STER BLI	EED	EVAP	ORATIVE	_						ION LEVI	ELS			
			001/0	1-1										R BLEED					
	ORATIVE			R (g/gallon) @ UL			FUEL TYPE			3DHS RIG TEST (g/test) @ UL		•	2DHS RIG TES (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K				
I AMIL I		EI	IEL TY	DE C	EPT ST	rn.	. 02	, oct i i i		EDT STD		CEPT			CEPT				

GASOLINE-

LEV3 E10

CERT

STD

STD

0.20



HONDA MOTOR CO., LTD. Executive Order: A-023-0734

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
KHNXR0121VSA	KHNXR0121VSA-A00	*	0.02					

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2	2019 MODEL YEAR: VEHICLE MODELS INFORMATION										
MAKE	MAKE MODEL		ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD				
HONDA	ACCORD HYBRID	PC	2.0	CV1	KHNXR0121VSA	1	P				