

HYUNDAI MOTOR COMPANY

Executive Order: A-254-0377

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

							1505						
					TEST GRO	OUP II	NFOR	MATION					
MODE YEAF	_	EST GROUP	VEHIC	ICLE CLASS(ES)			FUEL C	ATEGORY		FUEL TYPE			
2019	KH	YXV05.0HM5			PC	PC			SINGLE FUEI HICLE	·	GASOLINE		
	USEFUL	LIFE (miles)	VEH	IICLE EMISSION CATEGOR			GORY	INTERIM / IN	ITER	RMEDIATE IN-USE STD			
EXH	I/ORVR	EVAP		FTP SF			TP	FTP		SFTP			
150000 150000				LEV3	3 ULEV70 LEV 3 COMP			OMPOSITE	NMOG+NO	X	*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD STATUS			ENGINE DISPLACEMENT (L)		
1	1 DFI, 2WR-HO2S, 2HO2S, 2WU-TWC, 2TWC							FULL	*	7			
*	* *							ARTIAL	ALL MODELS		5.0		
*			+			PAF	TIAL WITH	*					
	EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION												
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR							EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
KHYXR0140HME					EV 2				PC		*		
				E	MISSION C	REDI	T INF	RMATION					
NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NO ZERO-EVAP						ON-P	PZEV NMOG CREDIT FOR DOR			R	OPTIONAL EXH. STD FOR WORK TRUCKS		
	N N							n n					
	NMOG AND FLEET AVERAGE INFORMATION												
NMOG RAF	CH4 RAF	NMOG/NMHC PC+LDL(0)-37				0-375		.VW) LDT (3751 LVW-8500 MD			NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.072			0.083		*		
										<u> </u>			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



HYUNDAI MOTOR -COMPANY

Executive Order: A-254-0377

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this day of March 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



TIER 2 UNLEADED HYUNDAI MOTOR COMPANY

Executive Order: A-254-0377 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

										_		CERTI					
	FUE		Ch mo ad Of 10	H4: me onoxid justme	ethande; NO ent fa	e; NMOO 0x: oxide ctor; 2D gallon d	G: non-Ces of nitr HS/3DH ispense	CH4 orga rogen; H IS [g HC d]: on-bo	anic ga CHO: /test]: pard re	as; HC: formale 2/3 day	hydrocar dehyde; P ys diumal vapor rec	ton; NMH M: particu +hot-soak covery; g: ure; SFTP	C: non-C late matte ; RL [g H0 gram; mg	H4 H0 er; RA C/mi]: : milli	C; CO: ca F: reactive running le gram; mi:	vity oss;	
)G+N g/mi)	Ox		CO g/mi)		-	NOx g/mi)		HCHO mg/mi)			M mi)	
				CERT		STD	CERT	STI	D	CERT	STD	CER	T ST	D	CERT	STD	
FTP@5	_	*		*		*	*	*		*	*	*	*		*	*	
FTP@L	GASO TIE			0.040	0	.070	0.4	1.	7	*	*	*	4		*	0.01	
EU E COVICI		OLINE- R3 E10		.044	0	.140	0.5	1.	7	*	*	*	16				
					C	T TVD	E			NMOG+NOx		Ox (g/mi)		(CO (g/mi)		
				FUEL TYPE						CERT STD			CERT		STD		
HWFET @ 50K			*							*	*						
HWFE	T@UL			GAS	OLIN	E-TIER	3 E10			0.	.017	0.070					
20°F	@ 50K	CC	DLD CO	E10	REGU	LAR GA	SOLINE	(TIEF	(83)		-		16	1.6		10.0	
			SF	TP EX	KHAL	IST EMI	SSION	STAND	ARDS	AND (ERTIFIC	ATION LE	VELS				
0.000					US06					SC03				COMPOSITE			
	FUEL TY	YPE		NMOG+NOx (g/mi)					M /mi)	ni) NMOG+NOx		CO (g/mi)	NMOG+NO (g/mi)		CO (g/mi)	PM (mg/mi	
@ 4K	*	CERT		RT *			*				*	*					
W 411			STD		*		*				*	*					
		CE		*		* *		+	*		*	0.037		0.4	*		
@ UL	TIER3 E10		STD		*		*	,	A		*	*	0.09	0	4.2	*	
			BIN									*	0.07	0			
		WH	OLE VE	HICLI	E EV	APORA	TIVE EN	MISSION	STAI	NDAR	S AND	ERTIFIC	ATION LE	VEL	S		
						WH	IOLE V	EHICLE	EVAP	ORAT	IVE TEST	ING					
EVAPORATIVE FAMILY KHYXR0140EME		FUEL TYPE		PE 3DHS (g/test) @ UL						2DHS (g/test) @ UL			R		RL (g/mi) @ UL		
				CERT		RT S	TD	FEL	CE	RT	STD	FEL	L CE			STD	
		-	ASOLINE -		0.29 0.		.50 *		0.	38	0.65	*		0.02		0.05	
(RVR / FL	JEL (ONLY/	CANIS	TER	BLEED	EVAPO	PRATIVE	EMIS	SSION	STANDA	RDS AND	CERTIF	ICAT	ON LEVI	ELS	
									_	-		P & CAN					
EVAPORATIVE FAMILY		ORVR (g/ga			gallon) @ UL		FUEL TYPE			DHS RIG TEST (g/test) @ UL			RIG TES st) @ UL				
				E CE	ERT	STD				RT	STD	CERT	STD		CERT	STD	
KHYKR0140HME		1	SOLINE TIER 2	0	.04	0.20		*		* *		*			*	*	



HYUNDAI MOTOR COMPANY

Executive Order: A-254-0377

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE	LEAK DIAMETER STAND	ARD AND CERTIFICATION L	EVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
*			

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: .DT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4; MDV 8501-10000#GVWR; MDV5; MDV 10001-14000#GVWR; MDPV; mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GWWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	OBD
HYUNDAI	G80 AWD	PC	5.0	SA8	KHYXR0140HME	1	P
HYUNDAI	G80 RWD	PC	5.0	SA8	KHYXR0140HME	1	P