

Executive Order: A-254-0396

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GR	OUP II	NFOI	RMATION				***************************************		
MODE		EST GROUP		VEHICLE CLASS(ES)			FUEL	FUEL CATEGORY			FUEL TYPE			
2019	K	HYXV02.0E2T		PC I				PLUG-IN HYBRID ELECTRIC VEHICLE			GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSI							ATE	ATEGORY INTERIM / INTERMEDIATE IN-USE						
EXH	I/ORVR	EVAP			FTP		S	FTP		FTP		SFTP		
15	0000	150000		LEV3	SULEV30	LEV	3 0	OMPOSITE		PM		PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD	S	TATUS	EN	ENGINE DISPLACEMENT		
1	DFI, WR-HO2S, HO2S, WU-TWC, TWC, EGR, EGRC							FULL		*				
*	*							PARTIAL		ALL MODELS	2.0			
*	*						PA	RTIAL WIT	*					
EVAPORATIVE & REFUELING (EVAP/ORVR) FAMILY INFORMATION														
EVA	P / ORV	R FAMILY	EVAP	ORATIVE	STD CATE	GORY				SSION STD E CLASS	SI	PECIAL FEATURES		
R	CHYXR01	25E2G		LEV 3	OPTION2	PION2 PC					HCT			
				ı	MISSION C	REDIT	INF	ORMATIO	N					
ALLOWANCE FOR TEST GROUP  TZEV  NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRAN						T FOR NON-PZEV ZERO						OPTIONAL EXH. STD FOR WORK TRUCKS		
	ALL M	MODELS		N			N		N			N		
	NMOG AND FLEET AVERAGE INFORMATION													
NMOG RAF	RAF NMOG/NMHC RATIO PC+LDT (0-				(0-3750 LVW) LDT (3		MOG+NOX FLEET STD N LDT (3751 LVW-8500 VWR) + MDPV (g/mi)		-	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	1.10		*		0.072			0.083			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-254-0396

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

day of August 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-254-0396

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

# **ATTACHMENT**

								IIAC	,1 11VII	-111										
	EXHA	UST	ANI	EVA	PORAT	IVI	EEMIS	SION	STAN	IDAR	DS AN	D CERT	IFICA	TION	LEVELS	}				
		EXH	AUST	EMISS	ION STA	ND/	ARDS A	ND CER	TIFICA	TION	LEVELS	(FTP, HV	VFET,	50°F, 20	°F)					
	FUE	L TY		monoxi adjustn ORVR	de; NOx:	oxid r; 20 on c	es of nit DHS/3DH dispense	rogen; F IS [g HC ed]: on-b	ICHO: c/test]: oard re	formald 2/3 day fueling	lehyde; F s diurnal vapor re	PM: partic +hot-soal covery; g	ulate m c; RL [g gram;	atter; R. HC/mi] mg: mil	IC; CO: ca AF: reactiv : running l ilgram; mi: Il FTP	vity oss;				
								NMOG+N				CO (g/mi)		NOx (g/mi)			HCHC (mg/m			M mi)
				CER	STI	0	CERT	ST	D	CERT	STD	CER	T	STD	CERT	STD				
FTP@50H	(	*		*	*		*	*		*	*	*		*	*	*				
FTP@UL	GASC TIEF			0.02	0 0.03	30	0.3	1.	0	*		*		4	0.000	0.003				
50°F @4K	GASC			0.03	9 0.00	60	0.4	1.	0	*	*	*		8						
0	-	•			FUEL 1	ГҮР	E					Ox (g/mi)			CO (g/mi)					
										CE	RT	STD		CERT		STD				
HWFET @ 50K					*						*	*								
HWFET @ UL				GA:	SOLINE-1	IE	R3 E10			0.	800	0.030		Ing						
20°F @	50K	CO	LD C	E10	REGULAR	G.	ASOLINE	(TIE	R3)					0.8		10.0				
		-		FTP E	XHAUST	EM	ISSION	STAND	ARDS	AND C	ERTIFIC	ATION L	EVELS	1						
				T		ı	JS06				SC03			CO	MPOSITE					
F	UEL TY	PE	Ŧ	NMOG+NOx (g/mi)		CO (g/mi)			NMOG+NOx (g/mi)		CO (g/mi)		G+NOx /mi)	CO (g/mi)	PM (mg/m					
@ 4K	*	* CEI		RT *		. *	*				*	*								
					*	1	*				*	*								
			CERT	₹T *			*	4		*		*	0.	016	0.2	*				
600 I II I	GASOLIN TIER3 E				*		* 6		6	*		* (		090	4.2	*				
			BIN										0.030							
		WH	OLE V	EHICL	EEVAPO	RA	TIVE EN	MISSION	STAN	DARD	SANDO	ERTIFIC	ATION	LEVEL	S					
EVAPORATIVE			UEL T	WHOLE VEHICLE EVAP						PORATIVE TESTING  2DHS (g/test) @ UL				RL (g/mi) @ UL						
FAMILY							STD FEL		CEF			FEL		CER		STD				
KHYXRO:	125E2G	1	ASOLI LEV3		0.223		300	*					* 0.0			0.05				
OR	VR / FU	-			STER BLI	ED	EVAPO	RATIVI	EMIS	SION S	STANDA	RDS AND	CERT	TIFICAT	ION LEVE	LS				
												P & CAN								
EVAPORATIVE ORV			ORVR	(g/gal	lon) @ UL		EUE:	TVDE		HS RIG	TEST	2DHS	RIG TI		BLEED CA					

				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS R (g/test	IG TEST ) @ UL	2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
KHYKR0125E2G	GASOLINE- TIER3 E10	0.04	0.20	*	*	*	* '	*	*	*			



Executive Order: A-254-0396

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)								
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD					
KHYKR0125E2G	KHYXR0125E2G-LP1	0.00	0.02					

t not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV: SULEV: super ULEV: ZEV: zero-emission vehicle: TZEV: transitional ZEV: TWC/OC: 3-way/oxidizing catalyst: ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

## 2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	HYUNDAI	SONATA PLUG-IN HYBRID	PC	2.0	AM6	KHYXR0125E2G	1	P

# ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL	PHEV TYPE	UDDS AER	UDDS EAER	US06 AER	HIGHWA	ZEV	
NUMBER	PHEV ITPE	(MILES)	(MILES)	(MILES)	AER	EAER	ALLOWANCE
1	TZEV	38.6	39.6	*	41.1	41	0.70