

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

		and share a state of the state											
					TEST GRO		NFOR	MATION			10 Harrison - 19		
MODE	- I T	EST GROUP		VEHIC	LE CLASS(E	S)		FUEL (	CATEGORY		FUEL TYPE		
2019	KA	SXV04.0AES			PC				SINGLE FUEL		GASOLINE		
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION (	CATE	GORY	INTERIM / IN	TERM	MEDIATE IN-USE STD		
EXH	I/ORVR	EVA	>		FTP		SF	TP	FTP		SFTP		
15	150000 150000		0	CERTI LEV	LEV OPTION FYING TO LEV 2 '3 ULEV STAND OG+NOX				* 1		*		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ENGINE DISPLACEMENT (L)		
1	2WU-TWC, 2TWC, 2WR-H02S, 2H02S, DFI, 2TC, 2CAC							FULL	ALL MODELS				
*	*							ARTIAL *			4.0		
*	* *							TIAL WITH	*				
		E	VAP	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y INFORMATIO	N			
EVA	P / ORV	R FAMILY	EV	APORATIVE	E STD CATE	GOR	(	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
1	KASXR01	.60P1Y		L	EV 2			1	PC		*		
				l	EMISSION CI	REDI		RMATION					
		X FLEET AVE OR EXTENDED RRANTY			EDIT FOR N ZERO-EVAP	ON-P	ZEV				OPTIONAL EXH. STD FOR WORK TRUCKS		
-		N			N				N		N		
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMH RATIO	c H	CHO/NMHC RATIO	NMOG+NO PC+LDT ( (g			N) LDT (3751 LVW-8500 MDV (10,001			IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.04		*	0	.125			0.125		*		
		A			·								

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



#### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

This Executive Order hereby supersedes Executive Order A-098-0058 dated March 8, 2018.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_ day of May 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division



BIN

FUEL TYPE

GASOLINE -

TIER 2

UNLEADED

**EVAPORATIVE** 

FAMILY

KASXR0160P1Y

ASTON MARTIN LAGONDA LIMITED Executive Order: A-098-0058-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

0.090

CERT

0.00

FEL

\*

RL (g/mi) @ UL

STD

0.05

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental F**T**P

1	FL	JEL	TY	PF

				NMOG (g/		-	CO /mi)		Ox mi)		HC⊦ mg/			PN (g/m	-	
			-	CERT	STD	CERT	STD	CERT	STD			STD	CER		STD	
FTP@50	ж	*		*	*	*	*	*	*	*	· †	*	*	<u> </u>	*	
FTP@U	GAS	ASOLINE - TIER 2 UNLEADED		0.0642	0.125	0.43	2.1	*	*	* *		11			0.01	
50°F @4	к т	OLINE IER 2 LEADE	2	0.0724	0.250	0.12	2.1	*	*	*		16				
						(DE		N	IOG+N	Ox (g/mi)		(	CO (g/	mi)		
	FUEL TYPE							CE	RT	STD		CERT		;	STD	
HWFET @ 50K				*					r	*	*					
HWFET @ UL			GA	GASOLINE - TIER 2 UNLEADED					153	0.125	0.125					
20°F@50K			GA	GASOLINE - TIER 2 UNLEADED								0.27		1	.0.0	
			S	FTP EXH	AUST E	MISSION S	TANDARD	S AND C	ERTIFIC		EVE	LS				
				Τ	US06				SC03	3		COMPOSITE				
	FUEL 1	FUEL TYPE		NMHC	+NOx	CO	PM	NMHC	+NOx	CO	NN	OG+NOx	C	С	PM	
				(g/	mi)	(g/mi)	(mg/mi)	(g/	mi)	(g/mi)		(g/mi)	(g/r	ni)	(mg/mi)	
GASOLINE - TIER 2 @ 4K UNLEADED		CERT	0.0	368	0.19		0.0	029	0.7					,		
C				0.	14	8.0		0.	20	2.7						
			CERT	·	ł	*	*	,	ł	*	(	0.0525	*		*	
@ UL	GASOLI TIEF UNLEA	2	STD			*	*		k	*	0.090		*		*	

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS WHOLE VEHICLE EVAPORATIVE TESTING

CERT

0.49

FEL

\*

2DHS (g/test) @ UL

STD

0.65

3DHS (g/test) @ UL

STD

0.50

CERT

0.39

AAL!	CALIF	ASTON LAGONDA	M	Executive Order: A-098-0058-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4									
ORVR / FU	EL ONLY / CA	NISTER	BLEED	EVAPORATIVE	EMISSION	STANDA	RDS AND	CERTIFIC	ATION LEV	ELS			
	ORVR (g/gallon) @ UL						P & CANISTER BLEED						
EVAPORATIVE FAMILY				FUEL TYPE	3DHS RIG TEST (g/test) @ UL			IG TEST	BLEED CANISTER TEST (g/test) @ 4				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
KASXR0160P1Y	GASOLINE - TIER 2 UNLEADED	0.01	0.20	*	*	*	+	÷	*	*			
	EFFECTIVE	LEAK	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INCH	HES)				
EVAPORATIVE	FAMILY	LEA	K FAMIL	Y CERT				STD					
*			*		*			*					
LDT<6000#GVWI 3500#ALVW; MD duty passenger ve emission limit; GV JLEV: ultra LEV; ADSTWC: adsorb	V: medium-duty shicle; HDV: he WR: gross veh SULEV: super ing TWC; HAC SCRC-NH3: se	vehicle avy-duty iicle weig ULEV; Z : HC ads lective c	; MDV4: vehicle; ht rating; EV: zero sorbing ca	MDV 8501-1000 ECS: emission of LVW: loaded ve -emission vehicle atalyst; WU: war	0#GVWR; M control syste ehicle weigh e; TZEV: tra m-up cataly:	MDV5: MD em; CERT: t; ALVW: a nsitional Z st; NAC: N	V 10001-14 certification djusted LV EV; TWC/0	000#GVV n; STD: st W; LEV: lo DC: 3-way/	VR; MDPV: n andard; FEL ow emission oxidizing ca	nedium- : family			

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
ASTON MARTIN	DB11 V8	PC	4.0	SA8	KASXR0160P1Y	1	F
ASTON MARTIN	VANTAGE V8	PC	4.0	SA8	KASXR0160P1Y	1	F