

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO		FOR	MATION							
MODE	I T	EST GROUP	ROUP VEHICLE CLASS(ES)					FUEL CATEGORY				FUEL TYPE			
201	9 K.B	MXT02.4HH3	LD	T1, LDT2	DEDICATED SINGLE FUEL VEHICLE			GASOLINE							
	USEFUL	LIFE (miles)		VEF	ICLE EMISS	LE EMISSION CATEGORY INTERIM / INT						ERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP			SFTP FTP			SFTP					
150000 150000				LEV3	SULEV30 LEV 3 C			COMPOSITE *			*				
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	STATUS		ENGINE DISPLACEMENT				
1 WR-HO2S, HO2S, WU-TWC, TWC, DFI								FULL	L *						
*			*				Р	ARTIAL	ALL MODE	ELS		2.4			
* *								TIAL WITH	*						
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMA	TION					
EVA	EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						EVAP EMISSION STD VEHICLE CLASS				SPECIAL FEATURES				
	KKMXR01	ЗЗННС		LEV 3	OPTION2			. LDT1				HCT			
					EMISSION CI	REDIT		ORMATION							
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON-F						ZEV	ZEV NMOG CREDIT FOR DOR				OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N				N						
				NMOG	AND FLEET	T AVE	RAG		TION						
NMOG RAF					0-375				IMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)						
*	*	1.10		*	0	. 072			0.083 *						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



### BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

Ruren

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_day of April 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division



FUEL TYPE

KIA MOTORS CORPORATION

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

### EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

				NMOG+NOx (g/mi)			CO (g/mi)			NOx g/mi)		HCH mg/i		Р <b>М</b> (g/mi)				
			c	ERT	ST	D	CER		D	CERT		CER	T	STD	CE		STD	
FTP@5	ок	*		*	*		*	*		*	*	*		*	*	,	*	
FTP@L		GASOLINE- LEV3 E10		0.008 0.		30	0.3	1.	0	*	*	*	*		4 *		0.01	
50°F @4	4KI	OLIN V3 E1	- 10	.013	0.0	60	0.2	1.	0	*	*	*		8				
					FUEL	түрі	=			N	MOG+N	Ox (g/mi)				g/mi)		
										C	ERT	STD		CER	Т		STD	
HWFE	Т @ 50К		_		*						*	*						
HWFE	T @ UL			GASC	LINE-	LEV	3 E10			0	. 007	0.030						
20°F	@ 50K		GASO	LINE-	COLD	co i	LOW OC	TANE						1.3	3	1	L0.0	
			SF	TP EXI	HAUST	EMI	SSION	STAND	ARDS	AND (	CERTIFIC	CATION LE	EVEL	S				
						U	IS06				SC0	3		CC	MPO	SITE	_	
	FUEL T	YPE		NMO	G+NOx		со	F	M		G+NOx	со	NM	OG+NO	x (	00	PM	
				(g/	'mi)		(g/mi)	(mg	g/mi)	(9	g/mi)	(g/mi)		(g/mi)	(g	/mi)	(mg/mi)	
@ 4K	*		CERT		*	*				*		*						
		STD			*		*				*	*						
			CERT	T *		*			*		*	*	0.013		1.2		*	
@ UL	GASOLI LEV3		STD		*		*		*		*	*		0.090		1.2	*	
			BIN											0.030				
		WH	OLE VE	HICLE	EVAP	ORA	TIVE E	MISSIO	N STA	NDAR	DS AND	CERTIFIC	ATIO	N LEVE	LS			
						WH	IOLE V	EHICLE	EVAF	PORAT	IVE TES	TING						
1	FORATIVE FUEL TYPE		Έ	3DHS (g/test) @ UL					2DH	) @ UL	@ UL		RL (g/mi) (		<u>⊅</u> UL			
					CERT	S	STD		CERT		STD	FEL	EL CE		ERT		STD	
KKMXP	ко133нно	2	ASOLINE LEV3 E1	- 10	.248	0.300		*	0.3	171	0.300	*.		0.01		0.05		
C	DRVR / F	UEL C	DNLY/C	ANIST	ER BL	EED	EVAP	ORATIV	E EMI	SSION	STANDA		) CE	RTIFICA	TION	LEVE	LS	
									F	UEL O	NLY EVA	P & CAN	STE	R BLEEI	D			
	ORATIVE	E ORVR (g/gall		/gallo			L TYPE			G TEST @ UL	2DHS RIG (g/test) @				BLEED CANISTER EST (g/test) @ 4K			
		FU	EL TYPE	CE	RT S	TD	1		CE	ERT	STD	CERT			CEF	CERT ST		
KKMXF	0133нн	2	SOLINE- ER3 E10	1 0 0	0 0	.20		OLINE- 3 E10		*	*	*	* *		0.0	0.011 0.		

A	CALIFORNIA AIR RESOURCES BOARD	
TT	AIR RESOURCES BOARD	

KIA MOTORS CORPORATION Executive Order: A-314-0295 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)							
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD				
KKMXR0133HHG	KKMXR0133HHG-QL1	0.00	0.02				

not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR.3751-5750#LVW: LDT3: LDT 6001-8500#GVWR.3751-5750#ALVW: LDT4: LDT 6001-8500#GVWR.5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liguefied natural gas; LPG: liguefied petroleum gas; E85: "85%" ethanol (\*15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2019 MODEL YEAR: VEHICLE MODELS I	FORMATION
-----------------------------------	-----------

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
KIA	SPORTAGE AWD	LDT2	2.4	SA6	KKMXR0133HHG	1	P
KIA	SPORTAGE FE AWD	LDT2	2.4	SA6	KKMXR0133HHG	1	P
KIA	SPORTAGE FE FWD	LDT1	2.4	SA6	KKMXR0133HHG	1	P
KIA	SPORTAGE FWD	LDT2	2.4	SA6	KKMXR0133HHG	1	P