

Executive Order: A-314-0296

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP II	NFOR	MATION				
MODE	г	EST GROUP		VEHICLE CLASS(ES)				FUEL C	ATEGORY		FUEL TYPE	
2019	K	MXT02.4HH5		LD	T1, LDT2				SINGLE FUEL HICLE		GASOLINE	
	USEFUL	L LIFE (miles)		VEH	IICLE EMISS	ION C	CATEGORY INTERIM / INTERMEDIATE				MEDIATE IN-USE STD	
EXH	I/ORVR	EVAP			FTP		SF	TP	FTP		SFTP	
15	50000	15000	0	LEV3	ULEV70	LEV	3 C	MPOSITE	*		*	
SPE	CIAL F	EATURES & EX	(HAU		ON CONTRO	L		OBD S	TATUS	EN	IGINE DISPLACEMENT	
1	V	WR-HO2S, HO2	S, ¥	W-TWC, TW	C, DFI			FULL	*			
*			1	+			Р	ARTIAL	ALL MODELS	2.4		
*	* *						1	TIAL WITH	*	*		
		E	VAP	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	/ INFORMATIO	N		
EVA	P / ORV	R FAMILY	EV	APORATIVE	STD CATE	CATEGORY EVAP EMISSION STD VEHICLE CLASS SPECIAL			PECIAL FEATURES			
1	KKMXR01	133ннG		LEV 3	OPTION2	LDT1 H			HCT			
					EMISSION C	REDIT	INFO	ORMATION				
	REDIT FO	OX FLEET AVE OR EXTENDED RRANTY	- 1		EDIT FOR N ZERO-EVAP	MMOG CBEDIL FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N				N		N	
				NMOG	AND FLEET	Γ AVE	RAGI	E INFORMA	TION			
NMOG CH4 NMOG/NMHC HCHO/NMHC PC+LDT				NMOG+NO PC+LDT (V) LDT	+NOX FLEET S (3751 LVW-850 R) + MDPV (g/m	0	MOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.072		0.083			*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



Executive Order: A-314-0296

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles
Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ______ day of April 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-314-0296

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

- 1	EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS
	EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)
	CH4: methane: NMOG: non-CH4 organic gas: HC: hydrocarton: NMHC: non-CH4 HC: CO: carb

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

			S+NOx	1	0	N		1	НО	1	M _.
		(g/mi)		(g/	mi)	(g/	mi)	(mg	/mi)	(g/	mi)
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- LEV3 E10	0.028	0.070	0.5	1.7	*	*	*	4	*	0.01
50°F @4K	GASOLINE- LEV3 E10	0.027	0.140	0.3	1.7	*	*	*	16		

	FUEL TYPE	NMOG+N	Ox (g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	*	*	*			
HWFET @ UL	GASOLINE-LEV3 E10	0.018	0.070			
20°F @ 50K	GASOLINE-COLD CO LOW OCTANE			1.0	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COM	IPOSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
		STD	*	*		*	*			
		CERT	*	*	*	*	*	0.029	1.4	*
@ UL	GASOLINE- LEV3 E10	STD	*	*	*	*	*	0.090	4.2	*
		BIN						0.070		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE \	/EHICLE	EVAPORA	TIVE TESTI	NG		
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test) (g UL	2DI	HS (g/test) (@ UL	RL (g/n	ni) @ UL
		CERT	SID	FEL	CERT	SID	FEL	CERT	STD
KKMXR0133HHG	GASOLINE- LEV3 E10	0.248	0.300	*	0.171	0.300	*	0.01	0.05

ORVR / FIJEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
KKMXR0133HHG	GASOLINE- TIER3 E10	0.00	0.20	GASOLINE- LEV3 E10	*	*	*	*	0.011	0.020		



Executive Order: A-314-0296

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIV	E LEAK DIAMETER STANDA	RD AND CERTIFICATION L	EVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
KKMXR0133HHG	KKMXR0133HHG-QL1	0.00	0.02

to not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR; gross vehicle weight rating; LVW; loaded vehicle weight; ALVW; adjusted LVW; LEV; low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%" gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

2019 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	ECS	OBD
KIA	SPORTAGE AWD	LDT2	2.4	SA6	KKMXR0133HHG	1	P
KIA	SPORTAGE FE AWD	LDT2	2.4	SA6	KKMXR0133HHG	1	P
KIA	SPORTAGE FE FWD	LDT1	2.4	SA6	KKMXR0133HHG	1	P
KIA	SPORTAGE FWD	LDT2	2.4	SA6	KKMXR0133HHG	1	P