

Executive Order: A-314-0301

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

			-		TEST GRO	UP II	NFOR	MATION				
MODI		TEST GROUP		VEHIC	LE CLASS(E	S)		FUEL CATEGORY			FUEL TYPE	
201	9 K	KMXT02.0HGF		LDT2 DEDICATED SINGLE FUEL VEHICLE					·	GASOLINE		
	USEFU	L LIFE (miles)		VEH	IICLE EMISS	ION (ATE	GORY	INTERIM / IN	ITE	RMEDIATE IN-USE STD	
EXI	1/ORVR	EVAP			FTP		SF	TP	FTP		SFTP	
1	20000	15000	0	LEV	2 ULEV	I	EV 2	SFTP DARD	*		*	
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS					L		OBD S	TATUS		ENGINE DISPLACEMENT (L)		
1 WR-HO2S, HO2S, WU-TWC, TWC, DFI, TC, C					FI, TC, CA	c		FULL	*	٦ſ		
*			4	7			P	ARTIAL	ALL MODELS	\parallel	2.0	
*	* *						4	TIAL WITH	*			
		E	VAP	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMATIO	N		
EV	AP / OR	VR FAMILY	EV	APORATIVE	DEATIVE STO CATEGODY				SSION STD E CLASS		SPECIAL FEATURES	
	KKMXR0	130HGE		L	LEV 2			LDT2			*	
				ı	EMISSION CI	REDIT	INFO	RMATION				
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY				CREDIT FOR NON-PZEV ZERO-EVAP			NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS	
N N				N				N		N		
				NMOG	AND FLEET	AVE	RAGE	INFORMA	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMH0 RATIO	НС	CHO/NMHC RATIO	NMOG+NO PC+LDT (6						NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)	
*	*	1.04		*	0	.072			0.083		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



Executive Order: A-314-0301

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

_ day of April 2018.

Annette Hebert, Chief

Emissions Compliance, Automotive Regulations and Science Division



Executive Order: A-314-0301

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP,	. HWFET, 50°F, 20°F)	
---	----------------------	--

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
1 110		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	GASOLINE - TIER 2 UNLEADED	0.022	0.040	0.3	1.7	0.02	0.05	*	8	*	
FTP@UL	GASOLINE - TIER 2 UNLEADED	0.027	0.055	0.3	2.1	0.03	0.07	*	11	*	0.01
50°F @4K	GASOLINE - TIER 2 UNLEADED	0.034	0.080	0.2	1.7	0.01	0.05	*	16		

	FUEL TYPE	NOx	(g/mi)	CO	(g/mi)
	FUEL TYPE	CERT	STD	CERT	STD
HWFET @ 50K	GASOLINE - TIER 2 UNLEADED	0.01	0.07	15 (2)	
HWFET @ UL	GASOLINE - TIER 2 UNLEADED	0.02	0.09		
20°F @ 50K	GASOLINE-COLD CO LOW OCTANE			0.4	12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

	1			US06		SC03		COM	POSITE	
- 4	FUEL TYPE		NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMHC+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	GASOLINE - TIER 2 UNLEADED	CERT	0.04	4.2		0.05	0.4			
0		STD	0.25	10.5		0.27	3.5			
		CERT	*	*	*	*	*	0.065	*	*
@ UL	GASOLINE ~ TIER 2 UNLEADED	STD	*	*	*		*	0.090	*	*
		BIN	ung new distribution and p	STANCES STANDS OF THE	TERM - APRIL OF A STREET AND A STREET	ন্যালাক্ষাক চান্ত ভাষাক হয় বিবাসক	NA PARAMAN	0.130		1 1000 00000000

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE						
EVAPORATIVE FAMILY	FUEL TYPE	3DHS (g/test) @ UL			2DI	HS (g/test) @	RL (g/mi) @ UL		
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
KKMXR0130HGE	GASOLINE - CA PHASE 2	0.36	0.65	*	0.42	0.85	*	0.02	0.05



Executive Order: A-314-0301

New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

					FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTE TEST (g/test) @ 4				
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD			
KKMXR0130HGE	GASOLINE - TIER 2 UNLEADED	0.02	0.20	*					*	*			
	EFFECTIVE I	LEAK D	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INC	IES)				
EVAPORATIVE FAMILY		LEA	K FAMIL	Y	CERT				STD				
			*	7	* "			*					

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1; LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GWR,3751-5750#LVW; LDT3: LDT 6001-8500#GWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: seguential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%" gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi-automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle

	2019 MODEL	YEAR: VE	HICLE M	ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH	ОВО
KIA	SPORTAGE AWD	LDT2	2.0	SA6	KKMXR0130HGE	1	P
KIA	SPORTAGE FWD	LDT2	2:0	SA6	KKMXR0130HGE	1	P