

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO	UP IN	FOR	MATION						
MOD YEA								FUEL CATEGORY			FUEL TYPE			
2019 KKMXV02.0DG5 PC							DEDICATED SINGLE FUEL VEHICLE			L	GASOLINE			
	USEFUL	LIFE (miles)	VEH	EHICLE EMISSION CATEGORY				INTERIM / INTERMEDIATE IN-USE ST						
EXH/ORVR EVAP				FTP SI			SF	FTP FTP			SFTP			
150000 150000				LEV3	ULEV70 LEV 3 COMPC			OMPOSITE	NMOG+NOX A	DND	PM	PM PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L	OBD STATUS				ENGINE DISPLACEMEN (L)			
1 DFI, WR-HO2S, HO2S, WU-TWC, TC, CAC								FULL	*					
*	* *							ARTIAL	ALL MODEL	5	2.0			
* *							PAR	TIAL WITH	*					
		E١	/APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL)N				
EV	AP / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
	LEV 3	OPTION1	OPTION1 PC					HCT						
				1	EMISSION CI	REDIT								
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY NMOG CREDIT FOR NON ZERO-EVAP						ZEV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS				
	N N							N				N		
				NMOG	AND FLEET	AVE	RAG		TION					
NMOG RAF	NMOG CH4 FTP RAF RAF NMOG/NMHC RATIO RATIO (g/mi)					0-375		LVW) LDT (3751 LVW-8500 MD)			OG+NOX FLEET STD /IDV (10,001-14,000 GVWR) (g/mi)			
*	*	1.10		*	0	. 072		0.083 *				*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c)(3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 5 7 day of June 2018.

Annette Hebert, Chief Emissions Compliance, Automotive Regulations and Science Division



KIA MOTORS CORPORATION Executive Order: A-314-0311 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMI	ENT
----------	-----

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

	· •																
				N	MOG+N (g/mi))G+NOx g/mi)		CO g/mi)			lOx /mi)		HCH((mg/m			PM (g/mi)	
				CE	RT	STD	CERT	STI	D	CERT	STD	CER	r	STD	CE	RT	STD
FTP@5	ок	*		•	,	*	*	*		*	*	*		*	1		*
FTP@L		ASOL		0.0	046 C	.070	0.6	1.	7	*	*	*		4 0.		001	0.003
50°F @	50°F @4K GASOL TIER			0.0	046 0	.140	0.4	1.	7	*	*	*		16			
					FU	EL TYP	E			N	MOG+NC	Dx (g/mi)				g/mi)	
							-			CERT		STD		CERT		STD	
HWFE	т @ 50	ж				*					*		*				
HWFE	T @ U	JL		G	ASOLIN	E-TIE	R3 E10			0.021		0.070					
20°F	@ 50K	<	COLD	CO E1	0 REGU	LAR G	ASOLINE (TIER3)						0.0		5 10		10.0
SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS																	
				US06					SC03			-		OMPOSITE			
	FUEL TYPE		N	MOG+N		CO			NMOG+NOx (g/mi)		CO	NMOG+NO			00	PM	
					(g/mi)		(g/mi)	(mg	(mg/mi)			(g/mi)	(g/mi)		(9	/mi)	(mg/mi)
@ 4K		*	CERT		*	*					* *						
			ST	D	*		*				*	*					
			CE	RT	RT *		*		3	ļ	*	*	(0.048	0.9		*
@ UL		DLINE R3 E1	ISIDI		*	*		* 6			*	*	(0.090	4	1.2	*
			BI	N									0.070				
		V	VHOLE	VEHI	CLE EV	APORA	TIVE E	MISSION	STA	NDARD	S AND C	ERTIFIC		N LEVE	LS		
					WHOLE VEHICLE EVAPORATIVE TESTING												
	ORAT			: 3	DHS (g	/test) @) UL		2DHS	S (g/test)	@ UL		RL (g		/mi) @ UL		
					CEF	хт :	STD	FEL	CE	RT	STD	FEL		CERT		STD	
KKMXI	R01431	DGG		LINE- 3 E10	- 10 2581 (. 350	*	0.2	287	0.350	*		0.02		0.05	
(ORVR	/ FUE	LONL	Y/CA	NISTER	BLEED	EVAP	ORATIVE	EEMI	SSION	STANDA	RDS AND	CEI	RTIFICA	TION	LEVE	LS
												P & CAN					
	ORAT		OR\	/R (g/g	/gallon) @ UL FUEL T			L TYPE			HS RIG TEST g/test) @ UL		2DHS RIG (g/test) @			LEED CANISTER EST (g/test) @ 4	
			FUEL	TYPE	CERT	STD]		RT	STD	CERT	CERT		CERT		STD
KKMXI	R0143		GASOL TIER3		0.02	0.20	1	OLINE- V3 E10		.0	0.0	0.0		0.0	*		*

CALI AIR RESO	FORNIA URCES BOARD	KIA MOTORS CORPORATION	Executive Order: A-314-0311 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4			
EFFECTIV	E LEAK DIAMETER	STANDARD AND CEI	RTIFICATION LI	EVEL (INCHES)		
EVAPORATIVE FAMILY	LEAK FAMILY	CER	т	STD		
KKMXR0143DGG	KKMXR0143DGG-JE	F1 0.0	0	0.02		
duty passenger vehicle; HDV: emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3: continuous/periodic trap oxidi; heated/oxygen sensor; WR-H RDQS: reductant quality sens secondary air injection (belt d direct/indirect fuel injection; To fines on-board diagnostic; DO suffix: series; CNG/LNG: com E10: "10%" ethanol ("90%"gas continuously variable transmis	duty vehicle; MDV4: MD heavy-duty vehicle; EC vehicle weight rating; LV per ULEV; ZEV: zero-err AC: HC adsorbing catal selective catalytic redu zer; DPF: diesel particul O2S or AFS: wide range or; NH3S: ammonia ser riven)/(electric driven); F C/SC: turbo/super chargo R: direct ozone reducin pressed/liquefied natura soline) fuel; A: automatic ssion; SCV: selectable of	V 8501-10000#GVWR; M S: emission control syste M: loaded vehicle weight hission vehicle; TZEV: trar yst; WU: warm-up catalys ction-urea/ammonia; NH3 late filter (active); GPF: PM e/linear/heated air-fuel rat nsor; EGR: exhaust gas re PAIR: pulsed AIR; SFI/MF ger; CAC: charge air coole g; HCT: hydrocarbon trap al gas; LPG: liquefied petro c (with lockup); M: manual continuously variable trans	DV5: MDV 10001 m; CERT: certifica ; ALVW: adjusted isitional ZEV; TW0 t; NAC: NOx adso OC: ammonia oxid filter for spark-ig to sensor; NOXS: circulation; EGRO : sequential/multip r; FFH: fuel fired h BCAN: bleed car bleum gas; E85: "8 transmission; SA mission; AM: auto	-14000#GVWR; MDPV: medium- ntion; STD: standard; FEL: family LVW; LEV: low emission vehicle; C/OC: 3-way/oxidizing catalyst; orption catalyst; SCR-U or dation catalyst; CTOX/PTOX: inited engine; HO2S/O2S: NOx sensor; PMS: PM sensor; C: EGR cooler; AIR/AIRE:		

	2019 MODEL	EAR: VE	HICLE MO	ODELS INF	ORMATION		
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBC
KIA	OPTIMA (W/SCC)	PC	2.0	SA6	KKMXR0143DGG	1	P