

KOENIGSEGG AUTOMOTIVE AB

Executive Order: A-459-0002

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION													
MOD	I T	EST GROUP		VEHIC	ICLE CLASS(ES)			FUEL C	ATEGORY	FUEL TYPE			
201	9 KK	GGV05.0RH5			PC HYB				ELECTRIC HICLE		GASOLINE		
	USEFUL	LIFE (miles)		VEH	ICLE EMISS	ION C	ATEG	ORY	INTERIM / IN	NTERIM / INTERMEDIATE IN-USE STD			
EX	H/ORVR	EVAP			FTP		SF	TP	FTP		SFTP		
1	20000	150000)	LEV	72 LEV LEV 2 SFT STANDARD				*		*		
SP	ECIAL FI	EATURES & EX	HAU		ON CONTRO	L		OBD S	OBD STATUS		ENGINE DISPLACEMENT (L)		
1	2WU-TV	VC, 2TWC, 2W	R-HO		, SFI, 2T	C,		FULL	*	THE PERSON	* 4		
*			*			Signal	P	PARTIAL *			5.0		
*	* *						100.000.000.00	ARTIAL WITH ALL MODELS		STATE STATES			
		Е	VAPO	ORATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMATIO	N			
EV	AP / ORV	R FAMILY	EV	APORATIVE	STD CATE	GORY			SSION STD E CLASS		SPECIAL FEATURES		
	KKGGR0:	L30GBK		L	LEV 2			E	PC .	*			
				E	MISSION C	REDIT	INFC	RMATION					
0.00	REDIT FO	OX FLEET AVE. OR EXTENDED RRANTY			REDIT FOR NON-PZEV ZERO-EVAP			NMOG C	REDIT FOR DC	R	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N			N	-			N		N		
				NMOG	AND FLEE	T AVE	RAGE	INFORMA	TION				
NMO(NINAC YCZ/NINALAC				NMOG+NOX FLEET STD PC+LDT (0-3750 LVW) (g/mi)			/) LDT	+NOX FLEET S (3751 LVW-850 R) + MDPV (g/n	0	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.04		0.03	C	.125		0.125			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



KOENIGSEGG AUTOMOTIVE AB

Executive Order: A-459-0002 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have five (5) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of one hundred dollars (\$100) per vehicle for the third through fifth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2019 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this _

TOUNDON

Emissions Certification and Compliance Division

day of December 2019.



KOENIGSEGG AUTOMOTIVE AB Executive Order: A-459-0002

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

			NMOG (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)		
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
FTP@50K	GASOLINE - TIER 2 UNLEADED	0.074	0.075	1.0	3.4	0.02	0.05	*	15	*	*		
FTP@UL	GASOLINE - TIER 2 UNLEADED	0.082	0.090	1.1	4.2	0.03	0.07	*	18	*	0.01		
50°F @4K	GASOLINE - TIER 2 UNLEADED	0.134	0.150	1.0	3.4	0.03	0.05	*	*				

		NOx	(g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD	CERT	STD	
HWFET @ 50K	GASOLINE - TIER 2 UNLEADED	0.01	0.07			
HWFET @ UL	GASOLINE - TIER 2 UNLEADED	0.02	0.09			
20°F @ 50K	GASOLINE - TIER 2 UNLEADED			2.0	10.0	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

				US06		SC03	3	COMPOSITE			
	FUEL TYPE	•	NMHC+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMHC+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
@ 4K	GASOLINE - CA PHASE 2	CERT	0.09	2.2		0.04	0.4				
		STD	0.14	8.0		0.20	2.7				
		CERT	0.09	2.2	*	0.04	0.4	*	*	*	
@ UL	GASOLINE - CA PHASE 2	STD	*	*	*	*	*	*	*	*	
		BIN						*			

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

a a	FUEL TYPE		WHOLE \						
EVAPORATIVE FAMILY		3DH	S (g/test) @) UL	2Dł	HS (g/test) (RL (g/mi) @ UL		
-		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
KKGGR0130GBK	GASOLINE - TIER 2 UNLEADED	0.34	0.50	*	0.50	0.65	*	0.00	0.05



AUTOMOTIVE AB

KOENIGSEGG AUTOMOTIVE AB

Executive Order: A-459-0002 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS															
				FUEL ONLY EVAP & CANISTER BLEED											
EVAPORATIVE FAMILY	ORVR (g/	FUEL TYPE			IG TEST) @ UL		RIG TEST st) @ UL	BLEED CANISTER TEST (g/test) @ 4							
	FUEL TYPE	CERT	STD			CERT	STD	CERT	STD	CERT	STD				
KKGGR0130GBK	GASOLINE - KGGR0130GBK TIER 2 0. UNLEADED		0.20	*		*	*	*	**	*	*				
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)															
EVAPORATIVE FAMILY LEAK FAMIL			Y CERT					STD							
* *				*					*						
	t 1.01 c	C 1 1'C			10	Ti liabt dut	thursday I D	TALL DT	6000#6\0\1	0 0 3750#1	MAN I DTO				

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle, HDV: heavy-duty vehicle, ECS: emission control system, CERT: certification, STD: standard, FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits. Y = credits, S = credits for some/select models

2019 MODEL YEAR: VEHICLE MODELS INFORMATION **EVAPORATIVE EXH VEH CLASS ENGINE (L)** TRANS TYPE OBD MODEL MAKE **FAMILY ECS** KOENIGSEGG ОТ1 KKGGR0130GBK 1 \$ 5.0 REGERA PC