

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

TEST GROUP INFORMATION														
MOD YEA	I T	EST GROUP	2	VEHICI	LE CLASS(E	S)		FUEL C	ATEGORY		FUEL TYPE			
201	9 KS	UBV02.5HPE			PC				SINGLE FUEL HICLE		GASOLINE			
USEFUL LIFE (miles) VEHICLE EMISSION								GORY	RMEDIATE IN-USE STD					
EX	H/ORVR	EVAP			FTP		SF	SFTP FTP			SFTP			
1	50000	150000		LEV3	LEV160	LEV	3 CC	MPOSITE	PM		PM			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS								OBD STATUS			ENGINE DISPLACEMEN (L)			
1	TWC (2), WR-HO2S, I	102S,	TC, CA	C, SFI, AI	R		FULL	ALL MODELS					
*					Trad quarked a	Р	ARTIAL	*		2.5				
*						1	ARTIAL WITH * FINES *							
		EV	APOF	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	INFORMATIO	N				
EV	AP / ORV	R FAMILY	EVAF	PORATIVE	STD CATE	GORY	,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
14 H H	KSUBR01	L	EV 2			PC *								
				E	EMISSION CI	REDIT		RMATION						
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							NMOG C	REDIT FOR DO	OPTIONAL EXH. STD FOR WORK TRUCKS				
	N N							N N						
				NMOG	AND FLEET	T AVE	RAG	E INFORMA	TION					
NMOG RAF	CH4 FTP HCHO/NMHC RAF NMOG/NMHC RAFIO RATIO (0-37 (g/mi				0-375					NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)				
*	*	1.10	0	0.001 0.072 0.083 *							*			

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this <u>/4774</u> day of August 2019.

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

SUBARU TECNICA INTERNATIONAL INC. Executive Order: A-466-0001 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

											-	
			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HO /mi)	P (g/	
1910			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K		*	*	*	*	*	*	*	*	*	*	*
FTP@UL	LE	OLINE- V3 E10 PREM	0.0776	0.160	1.59	4.2	*	*	0.0	4	0.0003	0.003
50°F @4K	LE	OLINE- V3 E10 PREM	3 E10 0.0822		1.29	4.2	*	*	0.2	30		
							N	lOG+NOx	(g/mi)	CO (g/mi)		
no materi				FUEL TYP	E		CE	CERT		CER	Т	STD
HWFET @ 50K				*			,	*				
HWFET @ UL			GASOLIN	NE-LEV3 1	E10 PREM		0.0	369	0.160			e Canton
20°F @ 50K		COLD	CO E10 PH	REMIUM GA	ASOLINE	(TIER3)		desitive des		4.4	5	10.0

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		SI	- IP EXHA	USIE	EMISSION	STAND	ARDS A	ND CERTIFIC	ATION L	EVEL	S			
		V. LAST			US06			SC03			COMPOSITE			
FUEL TYPE		PE		NMOG+NOx (g/mi)		CO PM (g/mi) (mg/mi		MOG+NOx (g/mi)	CO (g/mi)		OG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	
@ 4K	*	CERT	*		*			*	*					
6		STD			*			*	*	1000				
		CERT	*	*		1	. 9	*	*	0.0716		1.54	*	
@ UL	GASOLINE LEV3 E1 PREM	Tool - Norman Area	*		*		6	*	*	0.090		4.2	*	
										0.150				
		WHOLE VI	EHICLE EV	APO	RATIVE E	MISSION	N STAND	ARDS AND	CERTIFIC	ATIO	N LEVELS	6		
					WHOLE V	/EHICLE	EVAPO	RATIVE TES	TING					
EVAPORATIVE FAMILY		FUEL T	PE 3DHS		3DHS (g/test) @ UL		:	2DHS (g/test) @ UL		RL	(g/mi) @	UL	
				RT	STD	FEL	CERT	T STD	FE	L CERT			STD	
I KSUBRO1303BC I		GASOLIN CA PHAS	10 3	471	0.50	*	0.463	9 0.65	*		0.000		0.05	

A	CALIF	ORN RCES BO	Construction of the State of the State of the State	SUBARU TECNICA New Passenger Cars, L						ight-Duty Trucks and				
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS														
										ANISTER BLEED HS RIG TEST BLEED CANISTER				
EVAPORATIVE FAMILY	ORVR (g/	gallon) @	UL	FUEL TY	(DE			DEST DUL						
	FUEL TYPE	CERT	STD	FUELI		CERT		STD	CEF				-	STD
KSUBR01303BC	GASOLINE - TIER 2 UNLEADED		0.20	*		*		*	*			*		*
E	FFECTIVE	LEAK D	AMET	ER STAN	DARD	AND (CER	TIFICAT	ΓΙΟΝ	LEV	EL (INCH	ES)		
EVAPORATIVE	FAMIL	.Y		C	ER	Г			CERTIFICATION LEVELS TER BLEED IG TEST BLEED CANISTER t) @ UL TEST (g/test) @ 4K STD CERT STD * //EL (INCHES) STD * 000#GVWR,0-3750#LVW; LDT2: T 6001-8500#GVWR,5751- 4000#GVWR; MDPV: medium- on; STD: standard; FEL: family /W; LEV: low emission vehicle; OC: 3-way/oxidizing catalyst; tion catalyst; SCR-U or tion catalyst; SCR-U or tion catalyst; SCR-U or tion catalyst; CTOX/PTOX: ted engine; HO2S/O2S: Ox sensor; PMS: PM sensor; EGR: High/Low Pressure EGR; AIR; SFI/MFI: sequential/multiport bler; FFH: fuel fired heater; F/P/\$: ap; BCAN: bleed carbon canister; ctionalities of the after treatment uefied petroleum gas; E85: "85%" M: manual transmission; SA: sem able transmission; AM: mission; AER: all-electric range; ixtended Warranty: N = no MATION					
*	* *						*					*		
LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751- 8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: medium- duty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOX: NOX sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$; full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; AM: automated manual transmission; AMS: automated manual-selectable continuously														
MAKE	MC	DDEL	VE	H CLASS	ENG	INE (L)	TR	ANS TYP	PE					OBD
											FAMILY	E	CS	

2.5

м6

KSUBR01303BC

1

F

PC

s209

STI