

Executive Order: A-003-0690-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	NFOR	MATION					
MODE		EST GROUP	VEHI	CLE CLASS(I	ES)		FUEL C	ATEGORY		FUEL TYPE		
2020	LM	BXT04.0U2B		LDT4				SINGLE FUEL HICLE	GASOLINE			
	USEFUL	. LIFE (miles)	VE	HICLE EMIS	SION C	ATE	GORY	INTERIM / IN	TERMEDIATE IN-USE ST			
EXH	/ORVR	EVAP		FTP		SF	TP	FTP	SFTP			
15	0000	150000	LEV	3 ULEV125	LEV	3 CC	MPOSITE	*		*		
SPE	CIAL FE	ATURES & EX	HAUST EMISS	ION CONTRO	DL		OBD S	TATUS	EN	GINE DISPLACEMENT		
1	DFI,	2TC, 2CAC, 2	WR-HO2S, 2H	02S, 2TWC(2)		FULL *					
*			*			P	ARTIAL	IAL *		4.0		
*			*				TIAL WITH FINES	ALL MODELS	.s			
		E,	VAPORATIVE	& REFUELING	G (EVA	P/OR	VR) FAMILY	INFORMATION				
EVAP / ORVR FAMILY EVAPORATIVE STD CATEGOR						,	EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES		
L	MBXR01	70LNC	LEV 3 OP	TION2 WITH	FEL		LD	T4		*		
				EMISSION C	REDIT	INFO	RMATION					
	EDIT FO	X FLEET AVE. OR EXTENDED RRANTY	NMOG C	REDIT FOR N		ZEV	NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS		
		N		N			N			N		
			NMO	G AND FLEE	TAVE	RAGE	INFORMA	TION				
NMOG RAF	OG CH4 FTP HCHO/NMHC NMOG+NOX FL				(0-375	0 LVW) LDT (OG+NOX FLEET STD OT (3751 LVW-8500 /WR) + MDPV (g/mi)		NMOG+NOX FLEET STE MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	0.018		0.065			0.074		*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-003-0690-1

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models have been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. This Executive Order hereby cancels and supersedes Executive Order A-003-0690 dated November 5, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 477 day of February 2020.

. .

Allen Lyons, Chief

Emissions Certification and Compliance Division

Executive Order: A-003-0690-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; N monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: par adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-sr ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SI	rticulate matter; RAF: reactivity toak; RL [g HC/mi]: running loss; rg: gram; mg: milligram; mi: mile; K:

Fl	JEL	TY	PE

721 721		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	. *	*
FTP@UL	GASOLINE- TIER3 E10 PREM	0.068	0.125	1.9	2.1	*	*	1	4	0.002	0.01
50°F @4K	GASOLINE- TIER3 E10 PREM	0.203	0.250	1.0	2.1	*	*	2.6	16		

		NMOG+N	IOx (g/mi)	co	(g/mi)
	WFET @ 50K	STD	CERT	STD	
HWFET @ 50K	* .	*	*		
HWFET @ UL	GASOLINE-TIER3 E10 PREM	0.040	0.125		
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			2.0	12.5

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

77.32				US06		SC03		COM	POSITE	
1.00	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	*		*	*			
	1	STD	*	*		*	*		СО	
		CERT	*	*	*	*	*	0.073	2.2	*
@ UL	GASOLINE- TIER3 E10 PREM	STD	*	*	*	*	*	0.083	4.2	*
		BIN						0.110	144.5	

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

			WHOLE							
EVAPORATIVE FAMILY	FUEL TYPE	3DH	S (g/test) (@ UL	2DI	HS (g/test) (D UL	RL (g/m	i) @ UL	
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD	
LMBXR0170LNC	GASOLINE- LEV3 E10 PREM	0.4544	0.500	0.500	0.3567	0.500	0.500	0.00	0.05	



Executive Order: A-003-0690-1
New Passenger Cars, Light-Duty Trucks and
Medium-Duty Vehicles
Page 4 of 4

				FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/g	gallon) @) UL	FUEL TYPE	The second secon	IG TEST) @ UL	2DHS R (g/test		BLEED C TEST (g/t CERT 0.017 HES)	CANISTER test) @ 4K		
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD		STD		
LMBXR0170LNC	GASOLINE- TIER3 E10 PREM	0.02	0.20	GASOLINE- LEV3 E10 PREM	*	*	*	*	0.017	0.020		
	FFECTIVE	LEAK D	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INC	IES)			
EVAPORATIVE	FAMILY	LEA	K FAMIL	Y	CE	RT		STD				
LMBXR0170	LNC	LMBXR0	170LNC	-LNC	*		00-11-12	OF STREET	0.02			

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION **EVAPORATIVE EXH VEH CLASS** ENGINE (L) TRANS TYPE OBD MAKE MODEL **FAMILY ECS** 4.0 LMBXR0170LNC \$ MERCEDES BENZ AMG G 63 LDT4 A9