

Executive Order: A-003-0691

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 1 of 4

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP I	NFORMA	NOITA				
MODE		EST GROUP	VEHICLE CLASS(ES)				FUEL C	ATEGORY	FUEL TYPE		
2020	Lb	BXT04.0HY1				HYBRID ELECTRIC VEHICLE			GASOLINE		
	USEFUI	_ LIFE (miles)	VEH	ICLE EMIS	SION	CATEGO	RY	INTERIM / INT	ERMEDIATE IN-USE STD		
EXH	I/ORVR	EVAP		FTP		SFTP		FTP	SFTP		
15	0000	150000	LEV3	ULEV70	LEV	3 COME	POSITE	PM	PM		
SPE	CIAL F	EATURES & EXI	HAUST EMISSISTEMS	ON CONTR	OL		OBD ST	TATUS	ENGINE DISPLACEMEN		
1	DFI,	2TC, 2CAC, 21	WR-HO2S, 2HO	2S, 2TWC(2)	FU	ULL	*			
*	•						RTIAL	*	4.0		
*	* New York						AL WITH NES	ALL MODELS			
		EV	APORATIVE &	REFUELIN	G (EVA	P/ORVR	R) FAMILY	INFORMATION			
EVA	P / ORV	R FAMILY	EVAPORATIVE	STD CATE	GORY	, E	VAP EMIS	SSION STD CLASS	SPECIAL FEATURES		
I	MBXR01	70LNF	LEV 3 OPTI	ON2 WITH	FEL	LDT4			*		
				EMISSION	REDIT	INFOR	MATION				
	EDIT FO	X FLEET AVE. OR EXTENDED RRANTY		EDIT FOR I		ZEV NMOG CREDI		REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS		
		N		N		1300	4. 6	N	N		
			NMOG	AND FLEE	TAVE	RAGE IN	NFORMAT	TION			
IMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO NMOG+NOX FLI PC+LDT (0-375 (g/mi)		(0-375		LDT (NOX FLEET STI 3751 LVW-8500 () + MDPV (g/mi)	MDV (10,001-14,000		
*	*	1.10 .	0.018		0.065			0.074	*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



Executive Order: A-003-0691

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The listed vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II (OBD) system of the vehicles has been determined to have four (4) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of fifty dollars (\$50) per vehicle for the third and fourth deficiencies in the listed test group that is produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 1914

Aller Lyons, Chief

Emissions Certification and Compliance Division

day of November 2019.



Executive Order: A-003-0691

New Passenger Cars, Light-Duty Trucks and

Medium-Duty Vehicles

Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE

		NMOG+NOx (g/mi)		CO (g/mi)		NOx (g/mi)		HCHO (mg/mi)		PM (g/mi)	
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
FTP@50K	*	*	*	*	*	*	*	*	*	*	*
FTP@UL	GASOLINE- TIER3 E10 PREM	0.055	0.070	0.7	1.7	*	*	0	4	0.001	0.003
50°F @4K	*	*	*	*	*	*	*	*	*		

	FUEL TYPE	NMOG+N	lOx (g/mi)	CO (g/mi)		
	FUEL TYPE	CERT	STD			
HWFET @ 50K	*	*	*	PAGE PROPERTY	4.00	
HWFET @ UL	GASOLINE-TIER3 E10 PREM	0.036	0.070			
20°F @ 50K	COLD CO E10 PREMIUM GASOLINE (TIER3)			0.9	12.5	

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

1				US06		SC03		COM	POSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)	NMOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi
@ 4K	*	CERT	*	*		*	*			
•		STD	*	*		* .	*	CATAL DI		
		CERT	*	*	2	*	*	0.055	1.4	*
@ UL	GASOLINE- TIER3 E10 PREM	STD	*	*	6	*	*	0.083	4.2	*
		BIN		31.7		1.5		0.070		

WHOLE VEHICLE EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	FUEL TYPE		WHOLE						
EVAPORATIVE FAMILY		3DHS (g/test) @ UL			2DHS (g/test) @ UL			RL (g/mi) @ UL	
		CERT	STD	FEL	CERT	STD	FEL	CERT	STD
LMBXR0170LNF	GASOLINE- LEV3 E10 PREM	0.454	0.500	0.475	0.357	0.500	0.475	0.00	0.05

ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

	ORVR (g/gallon) @ UL			FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY				FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTER TEST (g/test) @ 4K			
Tall and	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD		
LMBXR0170LNF	GASOLINE- TIER3 E10 PREM	0.02	0.20	GASOLINE- LEV3 E10 PREM	*	*	*	*	0.017	0.020		



Executive Order: A-003-0691

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Page 4 of 4

EFFECTIV	E LEAK DIAMETER STA	NDARD AND CERTIFICATION L	EVEL (INCHES)
EVAPORATIVE FAMILY	LEAK FAMILY	CERT	STD
LMBXR0170LNF	LMBXR0170LNF-LNF		0.02

: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR,0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALWW: adjusted LVW; LEV: low emission vehicle; ULEV; ultra LEV; SULEV; super ULEV; ZEV; zero-emission vehicle; TZEV; transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC: HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler, AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES BENZ	GLE 580 4MATIC	LDT4	4.0	A9	LMBXR0170LNF	1	\$
MERCEDES BENZ	GLS 580	LDT4	4.0	A9	LMBXR0170LNF	1	\$