A	CALIFORNIA

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO		VEOR	MATION	-					
MODE	=1		1		TEOT ONC				-					
YEA		EST GROUP		LE CLASS(E		FUEL CATEGORY				FUEL TYPE				
202	2020 LMBXT04.0U2A LDT4							DEDICATED SINGLE FUEL VEHICLE				GASOLINE		
USEFUL LIFE (miles) VEHICLE EMISSION								CATEGORY INTERIM / INTERMEDIATE IN-U						
EXH/ORVR EVAP FTP							TP SFTP			FTP		SFTP		
150000 150000 LEV3 ULEV12						LEV 3 COMPOSITE			*		*			
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS							OBD \$			BD STATUS		ENGINE DISPLACEMENT		
1	DF	I, 2TC, 2CAC, 2	WR-HO	2S,2H02	S,2TWC(2)			FULL	Τ	*				
*				F	ARTIAL *			4.0						
*						PAR	TIAL WITH	I ALL MODELS I						
		E	APO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL	Y	INFORMATION				
EVA	P / ORV	R FAMILY	EVA	PORATIVI	E STD CATE	GORY		EVAP EMISSION STD VEHICLE CLASS			SPECIAL FEATURES			
:	LMBXR01	70LNC	LE	V 3 OPT	ION2 WITH	FEL		LDT4				*		
				I	EMISSION CI	REDIT	INFO	ORMATION						
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY							PZEV NMOG CREDIT FOR DOR			OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N			N N						
				NMOG	AND FLEET	AVE	RAGI	E INFORMA	TI	ION				
NMOG RAF							0 LVW) LDT (37			NOX FLEET STD 3751 LVW-8500 t) + MDPV (g/mi)		NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	0	0.018	0	.065		0.074				*		
		And the second s	-						-		-	steel Custome Dhees		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models has been determined to have three (3) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of twenty five dollars (\$25) per vehicle for the third deficiency for the vehicles in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

This Executive Order hereby cancels and supersedes Executive Order A-003-0693 dated November 15, 2019.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed on this Z3PP day of June 2020.

Allen Lyons, Chief Emissions Certification and Compliance Division



DAIMLER AG

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

FUEL TYPE
FUELTIPE

					OG+N (g/mi)	Ox		CO (g/mi)			NOx (g/mi)			HCH mg/			PM (g/mi)		
				CER	Г	STD	CER	RT S	TD	CER	Т	STD	CER	Т	STD	CE	RT	STD	
FTP@5	IOK	*		*		*	*		*	*		*	*		*	* *		*	
FTP@UL TIEF		R3 E PREM		0.06	3 0	.125	1.0	2	.1	*		*	1		4		001	0.01	
50°F @	4K	*		*		*	*		*	*		*	*		*	*			
					CIII		DE				NM	IOG+NC)x (g/mi)			CO	(g/mi)		
	120				101		/ L			(CERT S				CER	T		STD	
HWFE	T @ 50K					*		it is a second second			*		*						
HWFE	T @ UL			GASOL	INE-1	IER3	E10 P	REM		C	0.0	46	0.125						
20°F	@ 50K	CC	DLD CC	E10	PREM	IUM (GASOLII	NE (TIE	R3)						0.8	1		12.5	
			S	FTP E	XHAU	ST E	VISSIO		DARDS	AND	CE	RTIFIC	TION LE	VEL	S				
							US06					SC03			CC	MPO	SITE		
	FUEL T	YPE		1	OG+N	Ox	CO		PM		-	+NOx	co		OG+NO		co	PM	
					(g/mi)		(g/mi)	(m	g/mi)	mi) (ç		ni)	(g/mi)		(g/mi) (g		j/mi)	(mg/mi)	
@ 4K	@4K *		CERT		*		*				*		*						
		STE			*		*				*		*			Τ			
	GASOLINE- @ UL TIER3 E10 PREM		CERT		*	r			*		*		*	0.061		1.2		*	
@ UL			STD		*	*		*			*		*		0.083		1.2	*	
			BIN											1	0.110				
		WH	OLE V	EHICL	EEVA	POR	ATIVE E	MISSIO	N STA	NDAR	DS	AND C	ERTIFIC	ATIO	N LEVE	.S			
						V	HOLE	VEHICLI	EVA	PORA	TIVI	E TEST	NG		_				
	ORATIVE	F	UEL T	YPE	31	DHS (g/test) (DUL		2Dł	HS	(g/test)	test) @ UL RL				(g/mi) @ UL		
					CER	т	STD	FEL	CE	RT		STD	FEL		CER	T		STD	
LMBXF	LMBXR0170LNC		ASOLI LEV3 I PREN	210	0.45	44 (0.500	0.500	0.3	567	567 0		0.500		0.00		0.05		
0	DRVR / F	UELO		-	STER	BLEE	D EVAP	ORATIV	EEMI	SSION	1 51	TANDAR	RDS AND	CEI	RTIFICA	TION	LEVE	LS	
		Τ					1		and the second se	and the second second second	ALC: NO.		& CAN				×.		
	ORATIVE		ORVR (g/gallon) @ UL								HS RIG TEST (/test) @ UL		2DHS RIG T (g/test) @				ED CANISTER (g/test) @ 4K		
	MILY	FU	EL TY	PEC	ERT	STD	-	L TYPE			STD				STD CE		1	STD	
LMBXF	R0170LN0	GA	SOLIN ER3 E PREM	E-	.02	0.20	GAS	OLINE- /3 E10 PREM		*	*		*	*		0.0	17	0.020	

	FORNIA DURCES BOARD		DAIMLER AG	Executive Order: A-003-0693-1 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4						
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)										
EVAPORATIVE FAMILY	LEAK FAMILY		CERT	г	STD					
LMBXR0170LNC	LMBXR0170LNC-L	NC	*		0.02					
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: sup ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen EGRC: EGR cooler; AIR/AIR fuel injection; DFI/IFI: direct/i full/partial/partial with fines or prefix 2: parallel; (2) suffix: set device (ex. DPF-SCRC: SCR ethanol ("15%"gasoline) fuel; -automatic transmission; CV: automated manual transmiss	0#LVW; LDT3: LDT 600 duty vehicle; MDV4: MD 7: heavy-duty vehicle; E0 vehicle weight rating; L ber ULEV; ZEV: zero-en fAC: HC adsorbing cata 5: selective catalytic redu izer; DPF: diesel particu f02S or AFS: wide rang sor; NH3S: ammonia se E: secondary air injection ndirect fuel injection; TC h-board diagnostic; DOF eries; a hyphen (-) betwee coated DPF); CNG/LNF E10: "10%" ethanol ("90 continuously variable tr ion; AMS: automated m V: plug-in hybrid electric	11-850 V 850 CS: en /W: lo hission lyst; W uction- late fil e/linea nsor; I n (belf c/SC: tr C: direc een aft G: con 0% "ga ansmi anual-	0#GVWR,3751-5750 11-10000#GVWR; ME hission control system aded vehicle weight; h vehicle; TZEV: trans VU: warm-up catalyst urea/ammonia; NH30 ter (active); GPF: PM ar/heated air-fuel ratio EGR: exhaust gas read t driven)/(electric drive urbo/super charger; C ct ozone reducing; H0 ter treatment ECS ind npressed/liquefied na isoline) fuel; A: autom ssion; SCV: selectable selectable transmissi	#ALVW; LDT4: I DV5: MDV 1000 n; CERT: certifica ALVW: adjusted itional ZEV; TW NAC: NOX ads DC: ammonia ox filter for spark-io sensor; NOXS circulation; HP/L en); PAIR: pulse CAC: charge air CT: hydrocarbon icates multiple f tural gas; LPG: atic (with lockup e continuously v on; OT: other tra	kidation catalyst; CTOX/PTOX: gnited engine; HO2S/O2S: : NOx sensor; PMS: PM sensor; P EGR: High/Low Pressure EGR; d AIR; SFI/MFI: sequential/multiport cooler; FFH: fuel fired heater; F/P/\$: trap; BCAN: bleed carbon canister; functionalities of the after treatment liquefied petroleum gas; E85: "85%" b); M: manual transmission; SA: semi					

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
MERCEDES BENZ	G 550	LDT4	4.0	A9	LMBXR0170LNC	1	\$