

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-19-095;

IT IS ORDERED AND RESOLVED: The following vehicles produced by the manufacturer are certified as plug-in hybrid electric vehicles pursuant to Title 13, California Code of Regulations (13 CCR) Sections 1961 or 1961.2, 1962.2, 1976, 1978 and the incorporated test procedures. Production vehicles shall be in all material respects the same as those for which certification is granted.

				TEST GR	OUP IN	FORMATIO	ON		130	ally see a first	
MODE		EST GROUP	VEHICLE CLASS(ES)			FUEL CATEGORY			1	FUEL TYPE	
2020	20 LMBXT02.0HY1		LDT2			PLUG-IN HYBRID ELECTRIC VEHICLE				GASOLINE	
1	USEFUL	LIFE (miles)	VEH	ICLE EMIS	SION C	ATEGORY	.	INTERIM / INT	ERM	MEDIATE IN-USE STD	
EXH	/ORVR	EVAP		TP	1.00	SFTP FTP		FTP	SFTP		
15	0000	150000	LEV3	ULEV70	LEV	3 COMPOS	SITE	*		*	
SPE	CIAL FE	EATURES & EXH	AUST EMISSIC	ON CONTRO	DL	0	OBD S	TATUS	E	NGINE DISPLACEMENT (L)	
1		DFI, TC, CAC,	WR-HO2S, HO2S	, TWC		FULI	L	*			
*			*	a dela	PARTI	AL	* 2.		2.0		
*			* PA				WITH S	I ALL MUDELS I			
		EV	APORATIVE &	REFUELIN	G (EVA	P/ORVR) F	AMIL	Y INFORMATION		and a state of the state of the	
EVA	P / ORV	R FAMILY	EVAPORATIVE	STD CATE	GORY			SSION STD E CLASS	s	PECIAL FEATURES	
I	LMBXR0155LNP LE			LEV 3 OPTION2 WITH FEL			LDT2			*	
			Store Hillstore	MISSION C	CREDIT	INFORMA	TION	E trans to should be			
ALL		E FOR TEST OUP	NMOG+NOX AVE. CRED	TFOR		CREDIT F		NMOG CREDIT F	OR	OPTIONAL EXH. STD FOR WORK TRUCKS	
	TZ	EV	EXTENDED W	ARRANTY	EVAP		DON				
* N					N		N		N		
			NMOG	AND FLEE		RAGE INFO	ORMA	TION			
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO	NMOG+N PC+LDT			LDT	+NOX FLEET ST (3751 LVW-8500 R) + MDPV (g/mi)	D NMOG+NOX FLEET ST MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10	0.018		0.065			0.074		*	

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.) CALIFORNIA AIR RESOURCES BOARD Executive Order: A-003-0703 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 4

BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The vehicle models are conditionally certified in accordance with 13 CCR Section 1968.2(k) (deficiency and fines provisions for certification of malfunction and diagnostic system) because the on-board diagnostic II system of the listed vehicle models have been determined to have five (5) deficiencies. The listed vehicle models are approved subject to the manufacturer paying a fine of seventy five dollars (\$75) per vehicle for the third through the fifth deficiencies for vehicles in the listed test group that are produced and delivered for sale in California.

On a quarterly basis, the manufacturer shall submit to the California Air Resources Board reports of the number of vehicles produced and delivered for sale in California and pay the full fine owed for that quarter pursuant to this conditional certification. Payment shall be made payable to the State Treasurer for deposit in the Air Pollution Control Fund no later than thirty (30) days after the end of each calendar quarter during the 2020 model-year production period. Failure to pay the quarterly fine, in full, in the time provided, may be cause for the Executive Officer to rescind this conditional certification, effective from the start of the quarter in question, in which case all vehicles covered under this conditional certification for that quarter and all future quarters would be deemed uncertified and subject to a civil penalty of up to \$37,500 per violation per vehicle pursuant to HSC Section 43154.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this ____/D day of March 2020.

the second second second for the second second second second

Allen Lyons, Chief Emissions Certification and Compliance Division



FUEL TYPE

MERCEDES-BENZ AG

Executive Order: A-003-0703 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

The shade to be													
				6+NOx mi)		O mi)		Ox mi)	HC (mg			M mi)	
The State of State			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	-	*	+	*	*	*	+	*	+	*	*	*	
FTP@UL	TIEF	NLINE- R3 E10 REM	0.045	0.070	0.69	1.7	* *	*	0.1	4	0.001	0.01	
50°F @4K	TIER	NLINE- R3 E10 REM	0.021	0.140	0.29	1.7	*	*	0.3	16		antina Ali Linggi di Linggi dir	
			1.1.1		_		NN	NMOG+NOx (g/mi)			CO (g/mi)		
				FUEL TYP	E		CE	RT	STD	CEF	RT	STD	
HWFET @ 50K			-	+			*		+	an part an			
HWFET @ UL			GASOLIN	E-TIER3	E10 PREM	4	0.0	13	0.070	San Malan			
20°F @ 50K		COLD	CO E10 PI	REMIUM G	ASOLINE	(TIER3)		Ruga:	ant all us	1.2	2	12.5	
and the			SFTP EXH	AUST EM	ISSION S	TANDAR	DS AND CE	ERTIFIC	ATION LEVE	LS			
difference -	12.1	42.4	6.S		US06	20000	C. Carlo	SC03		C	OMPOSITE		

and sha	1.2.2.	Al polici		US06	SUS N	2362	SC03		CON	POSITE	
	FUEL TYPE		NMOG+NOx (g/mi)	CO (g/mi)	PI (mg/	the state of the state of	/IOG+NOx (g/mi)	CO (g/mi)	NMOG+NOx (g/mi)	CO (g/mi)	PM (mg/mi)
@ 4K	*	CERT	*	+		and the first state of the second state of the	*	+	AND ADDED		
		STD	+	*	作得到	n Carl	+	*	1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	An Court	- Salar
@ UL		CERT	*	+	*		*	*	0.030	0.66	*
	GASOLINE- TIER3 E10 PREM		*	+	*	1000	+	+	0.083	4.2	*
8.4		BIN	Temporales and		and all the	And the state	ALC: NO WERE	Janei - A	0.050	18.3.35	a state of the
	W	HOLE VE	HICLE EVAPO	RATIVE	MISSION	STANDA	RDS AND	CERTIFIC	ATION LEVELS	5	
0.25				WHOLE	VEHICLE	EVAPOR	ATIVE TEST	TING			
EVAPORATIVE		FUEL TY	PE 3DHS	3DHS (g/test) @ UL				2DHS (g/test) @ UL			UL
			CERT	STD	FEL	CERT	STD	FE	L CERT	·	STD
LMBXF	RO155LNP	GASOLIN LEV3 E	10 2621	0.400	0.275	*	0.400	0.2	75 0.00		0.05

MERCEDES-BENZ AG

CALIFORNIA AIR RESOURCES BOARD Executive Order: A-003-0703 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4

		FUEL ONLY EVAP & CANISTER BLEED								
EVAPORATIVE FAMILY	ORVR (g/gallon) @ UL			FUEL TYPE	3DHS RIG TEST (g/test) @ UL		2DHS RIG TEST (g/test) @ UL		BLEED CANISTE TEST (g/test) @ 4	
	FUEL TYPE	CERT	STD		CERT	STD	CERT	STD	CERT	STD
LMBXR0155LNP	CR0155LNP GASOLINE- TIER3 E10 0.03 0.20 PREM		0.20			*			*	*
100	EFFECTIVE	LEAK D	IAMET	ER STANDAR	D AND CE	RTIFICA	TION LEV	EL (INCH	IES)	
EVAPORATIVE FAMILY		LEA	K FAMIL	Y	CE	RT		STD		
LMBXR0155LNP		LMBXRO	155LNP	-LNP	Land and the state of the state			0.02		

*: not applicable; #: pounds; UL: useful life; PC: passenger car; LDT: light-duty truck; LDT1: LDT<6000#GVWR.0-3750#LVW; LDT2: LDT<6000#GVWR,3751-5750#LVW; LDT3: LDT 6001-8500#GVWR,3751-5750#ALVW; LDT4: LDT 6001-8500#GVWR,5751-8500#ALVW; MDV: medium-duty vehicle; MDV4: MDV 8501-10000#GVWR; MDV5: MDV 10001-14000#GVWR; MDPV: mediumduty passenger vehicle; HDV: heavy-duty vehicle; ECS: emission control system; CERT: certification; STD: standard; FEL: family emission limit; GVWR: gross vehicle weight rating; LVW: loaded vehicle weight; ALVW: adjusted LVW; LEV: low emission vehicle; ULEV: ultra LEV; SULEV: super ULEV; ZEV: zero-emission vehicle; TZEV: transitional ZEV; TWC/OC: 3-way/oxidizing catalyst; ADSTWC: adsorbing TWC; HAC: HC adsorbing catalyst; WU: warm-up catalyst; NAC: NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3: selective catalytic reduction-urea/ammonia; NH3OC: ammonia oxidation catalyst; CTOX/PTOX: continuous/periodic trap oxidizer; DPF: diesel particulate filter (active); GPF: PM filter for spark-ignited engine; HO2S/O2S: heated/oxygen sensor; WR-HO2S or AFS: wide range/linear/heated air-fuel ratio sensor; NOXS: NOx sensor; PMS: PM sensor; RDQS: reductant quality sensor; NH3S: ammonia sensor; EGR: exhaust gas recirculation; HP/LP EGR: High/Low Pressure EGR; EGRC: EGR cooler; AIR/AIRE: secondary air injection (belt driven)/(electric driven); PAIR: pulsed AIR; SFI/MFI: sequential/multiport fuel injection; DFI/IFI: direct/indirect fuel injection; TC/SC: turbo/super charger; CAC: charge air cooler; FFH: fuel fired heater; F/P/\$: full/partial/partial with fines on-board diagnostic; DOR: direct ozone reducing; HCT: hydrocarbon trap; BCAN: bleed carbon canister; prefix 2: parallel; (2) suffix: series; a hyphen (-) between after treatment ECS indicates multiple functionalities of the after treatment device (ex. DPF-SCRC: SCR coated DPF); CNG/LNG: compressed/liquefied natural gas; LPG: liquefied petroleum gas; E85: "85%" ethanol ("15%"gasoline) fuel; E10: "10%" ethanol ("90%"gasoline) fuel; A: automatic (with lockup); M: manual transmission; SA: semi -automatic transmission; CV: continuously variable transmission; SCV: selectable continuously variable transmission; AM: automated manual transmission; AMS: automated manual-selectable transmission; OT: other transmission; AER: all-electric range; EAER: equivalent AER; PHEV: plug-in hybrid electric vehicle; NMOG + NOx Fleet Ave. Credit for Extended Warranty: N = no credits, Y = credits, S = credits for some/select models

2020 MODEL YEAR: VEHICLE MODELS INFORMATION

MODEL NUMBER	MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
1	MERCEDES BENZ	GLC 350E 4MATIC	LDT2	2.0	A9	LMBXR0155LNP	1	\$

ELECTRIC RANGE AND ZEV ALLOWANCE INFORMATION

MODEL NUMBER	PHEV TYPE	UDDS AER	UDDS EAER (MILES)	US06 AER	HIGHW	ZEV	
	FREVITE	(MILES)		(MILES)	AER	EAER	ALLOWANCE
1.419	(innig) 🖈	29.4	30.0	0	29.0	30.00	0.00