

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRC		FOR	MATION	,				
MODE	- T	EST GROUP	VEHICLE CLASS(ES)			FUEL CATEGORY			FUEL TYPE				
2020	LG	MXT03.6161	je T	LDT2 DE			DEDICATED SINGLE FUEL VEHICLE			GASOLINE			
	USEFUL	LIFE (miles)	VEHICLE EMISSION CATEGO				GORY	INTERIM / IN	TER	ERMEDIATE IN-USE STD			
EXH/ORVR EVAP				FTP S			SF	SFTP FTP			SFTP		
150000 150000				LEV3	3 ULEV70 LEV 3 C			COMPOSITE *			PM		
SPECIAL FEATURES & EXHAUST EMISSION CONTROL SYSTEMS						L		OBD S	D STATUS		ENGINE DISPLACEMENT (L)		
1	DFI, 2TWC, 2HO2S(2), TWC							FULL	*				
*	*						F	PARTIAL	AL ALL MODELS 3.6				
*	*							RTIAL WITH * FINES					
		E	APOF	RATIVE &	REFUELING	(EVA	P/OF	RVR) FAMIL	(INFORMATIO	N			
EVA	P / ORV	R FAMILY	EVAI	PORATIVE	E STD CATE	GORY	DRY EVAP EMISSION STD VEHICLE CLASS			5	SPECIAL FEATURES		
I	LGMXR01	.3835A	LE	V 3 OPTI	CON2 WITH	FEL	LDT2				HCT		
					EMISSION CI	REDIT	[INF	ORMATION					
	NMOG+NOX FLEET AVE. CREDIT FOR EXTENDED WARRANTY									OPTIONAL EXH. STD FOR WORK TRUCKS			
		N			N				N				
				NMOG	AND FLEET	AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHC RATIO	HCHO/NMHC RATIO NMOG+NOX FLI PC+LDT (0-375 (g/mi)			0-375				0	NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	0	.065		0.074			*		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



BE IT FURTHER RESOLVED:

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this <u>17774</u> day of May 2019.

Allen Lydns, Chief Emissions Compliance, Automotive Regulations and Science Division



FUEL TYPE

GASOLINE-

TIER3 E10

0.02

0.20

LGMXR013835A

GENERAL MOTORS LLC. Executive Order: A-006-2186 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 4

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

			-															
				N	MOG+N (g/mi)			CO (g/mi)			NOx g/mi)		HCH (mg/n		PM (g/mi)			
				CEF	RT	STD	CER	T STI	D	CERT	STD	CER	т	STD	CE	RT	STD	
FTP@5	0K	*		*		*	*	*		*	*	*		*			*	
FTP@		OLIN R3 E		0.0	48 C	0.070	0.5	1.	7	*	*	*		4	0.0	0.001 0.0		
50°F @	50°F @4K			*		*	*	*		*	*	*		*		16.110	CHANNE!	
					EU		E			Ν	MOG+NC	Dx (g/mi)			CO (g	g/mi)		
			FUEL TYPE							CERT		STD		CERT		STD		
HWFE	T @ 50K					*					*	*				100		
HWFE	T @ UL			G	ASOLIN	E-TIE	R3 E10)		0	.011	0.070						
20°F	@ 50K	C	OLD CO) E1	0 REGU	LAR G	ASOLIN	E (TIER	FIER3)					1.9			12.5	
			S	FTP	EXHAL	JST EN	ISSION	STAND	ARDS	AND	CERTIFIC		EVEL	S				
						US06				SC03			CO		MPOSITE			
	FUEL T			TYPE NMOG+NOx CO (g/mi) (g/mi)			M /mi)	ni) (g/mi)		CO (g/mi)				:0 /mi)	PM (mg/mi)			
@ 4K	*	* -		ERT *		*		$ \begin{array}{c} \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right] \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right) \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right) \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right) \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} \right)^{2} \right) \\ \left[\left(\frac{1}{2} \right)^{2} + \left(\frac{1}{2} $		*								
e					*	*		*		*		*						
		CEF GASOLINE- SIER3 E10 BI			*		*	0.	. 8		*	*	0.042		0.042 0.6		*	
@ UL					*		*		6 *		*	*	C	0.083 4		. 2	*	
													0.080					
		WH	IOLE V	EHIC	CLE EV	APOR/	TIVE E	MISSION	STA	NDARI	DS AND C	ERTIFIC	ATIO	N LEVE	LS			
						W	HOLE \	/EHICLE	EVAF	ORAT	IVE TEST	ING						
	ORATIVI	= F	UEL T	YPE	YPE 3DHS (g		/test) (/test) @ UL			IS (g/test)	@ UL		RL (g/mi) @ UL			UL	
				CEF	RT	STD	FEL	CE	RT	STD	FEL		CERT		STD			
LGMXR013835A			GASOLI FIER3		0.2	57 0	. 400	0.400	.400 0.3		0.400	0.400		0.00			0.05	
	ORVR / F	UEL	ONLY	CAN	VISTER	BLEE	D EVAP	ORATIVE	EEMI	SSION	STANDA	RDS AND) CEF	RTIFICA	TION	LEVE	ELS	
									F	UEL O	NLY EVA	P & CANI	STER	RBLEE	D			
		E	ORVR	(g/g	allon) @	DUL	FUE			HS RIG TEST g/test) @ UL			2DHS RIG T (g/test) @					
		FL	JEL TY	PE	CERT	STD	1		CE	RT	STD	CERT		STD	CER		STD	
							1		1			1	-					

GASOLINE-

TIER3 E10

*

*

*

*

0.006

0.020

A	CALI	FOR	NIA
MATTA	AIR RESC	URCES	BOARD

			-									
EFFECTIVE LEAK DIAMETER STANDARD AND CERTIFICATION LEVEL (INCHES)												
EVAPORATIVE FAMILY	EVAPORATIVE FAMILY LEAK FAMILY CERT STD											
LGMXR013835A	LGMXR013835A-LK1	*	0.02									
LDT<6000#GVWR,3751-575 8500#ALVW; MDV: medium- duty passenger vehicle; HDV emission limit; GVWR: gross ULEV: ultra LEV; SULEV: su ADSTWC: adsorbing TWC; H SCRC/SCR-N or SCRC-NH3 continuous/periodic trap oxid heated/oxygen sensor; WR-H RDQS: reductant quality sen secondary air injection (belt of direct/indirect fuel injection; T fines on-board diagnostic; D0 suffix: series; CNG/LNG: cor E10: "10%" ethanol ("90%"ga continuously variable transm automated manual-selectabl	50#LVW; LDT3: LDT 6001-850 -duty vehicle; MDV4: MDV 85 /: heavy-duty vehicle; ECS: en vehicle weight rating; LVW: Id per ULEV; ZEV: zero-emission -AC: HC adsorbing catalyst; N 3: selective catalytic reduction lizer; DPF: diesel particulate fit -HO2S or AFS: wide range/line sor; NH3S: ammonia sensor; driven)/(electric driven); PAIR: FC/SC: turbo/super charger; C OR: direct ozone reducing; HC npressed/liquefied natural gas asoline) fuel; A: automatic (with ission; SCV: selectable contir e transmission: OT: other tran	r car; LDT: light-duty truck; LDT1: LD 00#GVWR;3751-5750#ALVW; LDT4: 01-10000#GVWR; MDV5: MDV 1000 mission control system; CERT: certific baded vehicle weight; ALVW: adjuste in vehicle; TZEV: transitional ZEV; TV WU: warm-up catalyst; NAC: NOx ads -urea/ammonia; NH3OC: ammonia or liter (active); GPF: PM filter for spark- ear/heated air-fuel ratio sensor; NOXS EGR: exhaust gas recirculation; EGF pulsed AIR; SFI/MFI: sequential/mul CAC: charge air cooler; FFH: fuel fired CT: hydrocarbon trap; BCAN: bleed ci s; LPG: liquefied petroleum gas; E85: th lockup); M: manual transmission; S muously variable transmission; AM: au ismission; AER: all-electric range; EA Extended Warranty: N = no credits, N	LDT 6001-8500#GVWR,5751- 11-14000#GVWR; MDPV: medium- cation; STD: standard; FEL: family d LVW; LEV: low emission vehicle; VC/OC: 3-way/oxidizing catalyst; sorption catalyst; SCR-U or xidation catalyst; CTOX/PTOX: ignited engine; HO2S/O2S: S: NOx sensor; PMS: PM sensor; RC: EGR cooler; AIR/AIRE: Itiport fuel injection; DFI/IFI: 4 heater; F/P/\$: full/partial/partial with arbon canister; prefix 2: parallel; (2) "85%" ethanol ("15%"gasoline) fuel; GA: semi-automatic transmission; CV: itomated manual transmission; AMS: LER: equivalent AER; PHEV: plug-in									

2020 MODEL	YEAR: VEHICLE MODELS INFORMATION
------------	----------------------------------

MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD
CHEVROLET	COLORADO 2WD	LDT2	3.6	A8	LGMXR013835A	1	P
CHEVROLET	COLORADO 4WD	LDT2	3.6	A8 .	LGMXR013835A	1	P
GMC	CANYON 2WD	LDT2	3.6	A8	LGMXR013835A	1	P
GMC	CANYON 4WD	LDT2	3.6	A8	LGMXR013835A	1	P