

Pursuant to the authority vested in California Air Resources Board by Health and Safety Code (HSC), Division 26, Part 5, Chapter 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 and 39516 and Executive Order G-14-012;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

					TEST GRO		FOR	MATION					
MODE	- 1 - 16	EST GROUP		VEHICLE CLASS(ES)				FUEL CATEGORY			FUEL TYPE		
2020	LG	MXT02.5200	00 LDT2 DEDICATED SINGLE FUEL GASOLINE GASOLINE							GASOLINE			
	USEFUL	LIFE (miles)		VEH	ICLE EMISS		ATE	GORY	INTERIM / IN	RMEDIATE IN-USE STD			
EXH	/ORVR	EVAP		FTP				SFTP FTP			SFTP		
15	150000 150000			LEV3	ULEV70 LEV 3 COM			MPOSITE	*		*		
SPE	CIAL FE	ATURES & EX						TATUS	ENGINE DISPLACEMENT				
1	DFI, TWC(2), HO2S(2)							FULL	*				
*			*				P	ARTIAL	ALL MODELS		2.5		
*		* PARTIA FIN							* *				
		E	VAPO	RATIVE &	REFUELING	(EVA	P/OR	VR) FAMIL		N			
EVA	P / ORV	R FAMILY	EVA	PORATIVE	E STD CATE	GORY	(		SSION STD E CLASS		SPECIAL FEATURES		
I	GMXR01	2637A	LI	EV 3 OPTI	CON2 WITH	FEL		LI	DT2	НСТ			
I	GMXR01	3835A	LI	EV 3 OPTI	LON2 WITH	FEL		LI	HCT				
					EMISSION C	REDIT		ORMATION					
	EDIT FO	X FLEET AVE R EXTENDED RANTY			REDIT FOR N ZERO-EVAP		ZEV	NMOG CREDIT FOR DO			R OPTIONAL EXH. STD FOR WORK TRUCKS		
		N		1	N			N N					
				NMOG	AND FLEE	T AVE	RAG	E INFORMA	TION				
NMOG RAF	CH4 RAF	FTP NMOG/NMHO RATIO		HO/NMHC RATIO							NMOG+NOX FLEET STD MDV (10,001-14,000 GVWR) (g/mi)		
*	*	1.10		*	C	0.065			0.074		*		
See th	e Attach	ment for Veh	icle M	odels, Ev	aporative Fa	amily.	Engi	ne Displace	ement, Emissio	n C	Control Systems, Phase-		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations. (As applicable, heavy-duty vehicles (HDV) over 14,000 pounds in GVWR listed in this Executive Order are certified to the requirements in 13 CCR Section 1961.2 applicable to MDV pursuant to 13 CCR Section 1956.8(c)(3) or 13 CCR Section 1956.8(h)(5), as applicable.)



## **BE IT FURTHER RESOLVED:**

The exhaust and evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's fleet average compliance requirement for NMOG+NOx or Vehicle Equivalent Credit (13 CCR Sections 1961.2(b)(1), 1961.2(b)(3), or 1961.2(c) (3), and the incorporated test procedures, as applicable), or Greenhouse Gas Emissions (13 CCR Section 1961.3, or 17 CCR Section 95663, and the incorporated test procedures, as applicable), for PC, LDT, MDPV or MDV shall be equalized as required.

#### BE IT FURTHER RESOLVED:

For the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards and Test Procedures and 2017 and Subsequent Model Greenhouse Gas Exhaust Emission Standards and Test Procedures for PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of May 2019.

Ilen Lyons, Chief

HEmissions Compliance, Automotive Regulations and Science Division



FUEL TYPE

GENERAL MOTORS LLC.

# ATTACHMENT

## EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

## EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS (FTP, HWFET, 50°F, 20°F)

CH4: methane; NMOG: non-CH4 organic gas; HC: hydrocarbon; NMHC: non-CH4 HC; CO: carbon monoxide; NOx: oxides of nitrogen; HCHO: formaldehyde; PM: particulate matter; RAF: reactivity adjustment factor; 2DHS/3DHS [g HC/test]: 2/3 days diurnal+hot-soak; RL [g HC/mi]: running loss; ORVR [g HC/gallon dispensed]: on-board refueling vapor recovery; g: gram; mg: milligram; mi: mile; K: 1000 miles; F: degrees Fahrenheit; FTP: federal test procedure; SFTP: supplemental FTP

中国ないになる													
			NMOG+NOx (g/mi)		CO (g/mi)			NOx (g/mi)		HCHO (mg/mi)		M mi)	
			CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	
FTP@50K	*		*	*	*	*	*	*	*	*	*	*	
FTP@UL	JL GASOLINE- TIER3 E10		0.036	0.070	0.4	1.7	*	*	*	4	0.001	0.003	
50°F @4K	*		*	*	*	*	*	*	*	*		$= \sum_{\substack{i=1\\j \in \mathcal{I}}} dh  \varphi_{ij} + e_{ij}$	
				FUEL TYP	C		N	IOG+N	Ox (g/mi)	CO (g/mi)			
	i jeko Erten s			FUEL ITP	C	-	CE	RT	STD	STD CEI		STD	
HWFET @ 50K				*				*		an a		khenduka Khenduka	
HWFET (	@ UL		GASOLINE-TIER3 E10					010	0.070	和理论			
20°F @ 50K		COLD	CO E10 RE	EGULAR G	ASOLINE	(TIER3)		$[1 + I_{ij}]$	物资素包括	1.	5	12.5	

## SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

			SF	TP EX	HAUST	EMISSION	N STAND	ARDS A	AND C	CERTIFIC	ATION L	EVEL	S		
					US06				SC03				COMPOSITE		
	FUEL TY	PE			G+NOx /mi) <sup>.</sup>	CO (g/mi)	-	PM g/mi)		G+NOx ı/mi)	CO (g/mi)		OG+NOx (g/mi)	CO (g/mi) 2.7 4.2 g/mi) @ l	PM (mg/mi)
@ 4K	*		CERT	4	*	*				*	*			· 限制的) (教術 家)	
-			STD	~	*	*				*	*			famile a	i geralseit s
		ASOLINE- DIER3 E10 STD		*		*		.1	* *		*	0.025		2.7	*
@ UL				*		* *		6		*		0	0.083	4.2	*
	· · · · ·		BIN					(2)、(A).(A)	1634	(4.3.) (73.) (4.3.)		(	0.080		11 June
		wн	OLE VE	HICLE	EVAPO	ORATIVE E	MISSION	STAN	DAR	S AND	CERTIFIC	ATIO	N LEVELS		-
						WHOLE	VEHICLE	EVAPO	ORAT	IVE TEST	TING				
	EVAPORATIVE FAMILY		FUEL TYPE		3DH	S (g/test) (	st) @ UL		2DHS (g/test) @ UL		) @ UL	RL		(g/mi) @ UL	
					CERT	STD	FEL	CER	RT	STD	FE	L	CERT		STD
LGMXI	LCMYR012637A		ASOLINE- IER3 E10		0.219	0.400	0.400	0.2	32	0.400	0.4	00 0.00		į	0.05
LGMXI	R013835A		ASOLIN IER3 E		0.257	0.400	0.400	0.34	40	0.400	0.4	00	0.00		0.05

AR	CALII Ir reso	FORN URCES B	<b>NA</b> OARD	GENERAL MOTORS LLC.			N	Executive Order: A-006-2194 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 4 of 4					
ORVR / FUEL ONLY / CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS													
1.5				FUEL ONLY EVAP & CANISTER BLEED									
EVAPORATIVE FAMILY	ORVR (	g/gallon) @	DUL	FUEL	ΓΥΡΕ	3DHS R (g/test)	G TEST @ UL				ANISTER est) @ 4K		
	FUEL TYP	E CERT	STD			CERT	STD	CER	T STD	CERT	STD		
LGMXR012637A	GASOLINE TIER3 E1		0.20	GASOLINE- TIER3 E10		*	*	*	*	0.004	0.020		
LGMXR013835A	GASOLINE- TIER3 E10 0.02 0.20		-	GASOLINE- TIER3 E10		*	*	*	*	0.006	0.020		
E	EFFECTIV	E LEAK D	IAMET	ER STA	NDAR	D AND CE	RTIFICA	TION L	EVEL (INCH	IES)			
EVAPORATIVE	EVAPORATIVE FAMILY LEAK FAMI					Y CERT STD							
LGMXR0126	37A	KGMXR0	12637A	A-LK1 *					0.02				
LGMXR0138	35A	KGMXR0	13835A	A-LK1 *				0.02					

	2020 MODEL YEAR: VEHICLE MODELS INFORMATION												
MAKE	MODEL	VEH CLASS	ENGINE (L)	TRANS TYPE	EVAPORATIVE FAMILY	EXH ECS	OBD						
BUICK	ENVISION AWD	LDT2	2.5	A6	LGMXR012637A	1	P						
BUICK	ENVISION FWD	LDT2	2.5	A6	LGMXR012637A	1	P						
CHEVROLET	COLORADO 2WD	LDT2	2.5	A6	LGMXR013835A	1	P						
CHEVROLET	COLORADO 4WD	LDT2	2.5	A6	LGMXR013835A	1	P						
GMC	CANYON 2WD	LDT2	2.5	A6	LGMXR013835A	1	P						
GMC	CANYON 4WD	LDT2	2.5	A6	LGMXR013835A	1	P						